MATERIAL SAFETY DATA SHEET

MSDS #: PAN

Page 1 of 3

Chartpak, Inc.
One River Road

Emergency Medical Number: 888-786-0972

December 31, 2011

Creation Date:

Leeds, MA 01053 Phone: 413-584-5446 or 800-628-1910

Section One:	Product Inform	mation		
Product Name:	Grumbacher Watercolor Sets- Opaque Watercolor, Transparent Watercolor, See For Yourself Watercolor			
Product Sizes:	12 and 24 color sets			
Product Class:	PAN Watercolors			
Section Two:	Ingredients			
Ingredients		CAS Number	% by Weight	PEL/TLV
None				

This product is considered safe under normal use conditions.

Section Four: First Aid Measures

Inhalation: None under normal use conditions.

Skin Contact: None under normal use conditions.

None under normal use conditions.

Ingestion: None under normal use conditions.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: WC012.Set, WC024.SET, WCT12.SET, WCT24.SET, 2412

Eye Contact:

MATERIAL SAFETY DATA SHEET

MSDS #: PAN

Page 2 of 3

Section Five: **Fire Fighting Measures**

Flash Point: Not flammable

Flammability Limits (% by volume): Upper: Not explosive Lower: Not explosive

Extinguishing Media: As appropriate for surrounding area. No special fire fighting procedures. Special Fire Fighting Measures:

Unusual Fire and Explosion

Hazards:

Not combustible

Section Six: **Accidental Release Measures**

No special spill procedures required

Section Seven: **Handling and Storage**

Handling: No special handling requirements.

No special handling requirements. Storage:

Section Eight: **Exposure Controls and Personal Protection**

Respiratory Protection and

Special Ventilation Requirements:

None required

Other Protective Equipment

(Gloves, Goggles, Etc.):

None

Work/Hygiene Practices: Studio hygiene rules should be observed. Wash thoroughly before eating, drinking, or smoking.

Section Nine: Physical and Chemical Properties

Boiling Point: Melting Point: Not determined Not determined

Vapor Pressure: Not determined Specific Gravity: 1.2

Specific Vapor Density (AIR = 1): Not determined Evaporation Rate (Butyl Acetate = 1): Not determined

Solubility in Water: Dispersible Reactivity in Water: Non-reactive

Colored solid watercolors; no odor Appearance and Odor:

Section Ten: Stability and Reactivity

Stability: Stable

Conditions to Avoid: None known Chemical Incompatibility: None known Hazardous Decomposition: None known Hazardous Polymerization: Will not occur

MATERIAL SAFETY DATA SHEET

MSDS #: PAN

Page 3 of 3

Section Eleven: Toxicological Information

IARC Monographs: No
National Toxicology Program: No
OSHA Regulated: No

Effects/Symptoms of Acute Exposure:

None expected

Effects/Symptoms of Chronic Exposure:

None expected

Medical Conditions Usually Aggravated By Overexposure of This Product:

None known

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose in accordance with Federal, State, and Local Regulations.

Section Fourteen: Transport Information

Not regulated as a hazardous material by DOT, IMO, or IATA.

Section Fifteen: Regulatory Information

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

Section Sixteen: Other Information

HMIS Code

Flammability 0

Health 0

Reactivity 0

Personal Protection N/A

Chartpak, Inc. is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the AP (Cautionary Label) Seal. Products bearing the AP Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236.

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.