

00378-0189

MATERIAL SAFETY DATA SHEET

(Required under OSHA's Hazard Communication Standard 29 CFR 1910.1200)

Page 1 of 2

(#15262)

IDENTITY (As Used on Label and List)
Koi Watercolors 18 Colors Laminate Tube Set (#15262)

Section I

Manufacturer's Name: Sakura Color Products Corporation	Telephone Number: +81 (0)6 - 6910 - 8824 (Japan)
Address: 1-6-20, Morinomiya Chuo, Chuo-ku, Osaka, 540-8508 Japan	FAX Number: +81 (0)6 - 6910 - 8834 (Japan)
Published Date: November 18, 2009	Publisher: Takahiro Shirai

Section II - Hazardous Ingredients / Identity Information

Hazardous Components	CAS No.	WT %	OSHA PEL	ACGIH TLV
----------------------	---------	------	----------	-----------

This product is approved by ACMI (The Art & Creative Material Institute, Inc.), and carries the "AP" seal of non-toxic approval in USA.

Section III - Physical / Chemical Characteristics for Ink

Boiling Point:	about 100°C	Specific Gravity: (H ₂ O = 1 at 25°C)	1.0 -1.1
Vapor Pressure: (mmHg)	N.D.	Melting Point:	N.D.
Vapor Density: (Air = 1)	N.D.	Evaporation Rate: (Butyl Acetate = 1)	N.D.
Solubility in Water	Soluble		
Appearance and Odor	Liquid, Little starch odor		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Uses): N.D.	Flammable Limits: LEL: N.D.	UEL: N.D.
Extinguish Media: In case of fire, use water spray, foam or dry chemical powder.		
Special Fire Fighting Procedures: No special mention		
Unusual Fire and Explosion Hazards: Toxic gases (carbon monoxide, nitrogen oxides and sulfur oxide) will form upon combustion.		
N.A.: Not Applicable		N.D.: Not Determined

