

Material Safety Data Sheet

Manufacturer or Distributor: Jack Richeson & Co., Inc.
557 Marcella Drive
Kimberly, Wi 54136

Information Telephone Number: 920-738-0744

Emergency Telephone Number: 800-233-2404

----- Section I – Product Identification -----

Product Name: Shiva Copal Painting Medium

Item Numbers: 120710, 120711

----- Section II – Hazardous Ingredients -----

INGREDIENT	CAS#	PPM
Turpentine CAS	8006-64-2	100

----- Section III – Physical and Chemical Characteristics -----

Boiling Point: 315 degrees F	Melting Point: N/A
Vapor Pressure: N/A	Specific Gravity: .96
Specific Vapor Density: (Air < 1)	Reactivity in Water: Non-Reactive
Solubility in Water: Insoluble	Evaporation rate: Slower than Butyl Acetate

Appearance and Odor: Amber Liquid with distinct pine odor

----- Section IV – Fire and Explosion Information -----

Flash Point (Method): 175 degrees F
Extinguishing Media: Halon, CO2, Dry Chemical
Special fire fighting procedures: This material floats and water will spread the flames
Unusual Fire and Explosion Hazards: Containers should be cooled with water stream to prevent exploding when heated from fire.

----- Section V – Physical Hazards / Reactivity -----

Hazardous Polymerization Products: None
Stability: Stable
Stable Conditions to Avoid: None
Incompatibility (Materials to Avoid): None
Hazardous Decomposition Products: None

----- Section VI – Health and Hazard Data -----

Primary Routes of Entry: Inhalation, Skin, Ingestion

Health Hazards:

This product can be hazardous and over exposure can cause narcosis, coma, and even be fatal. It can cause skin and eye irritation.

Signs and symptoms of exposure:

Dizziness, headache, rash, conjunctivitis

Medical Conditions Usually Aggravated by Over Exposure to This Product: CNS, Pulmonary, Skin, or Eye disorders

First Aid Measures: Remove to fresh air, wash the skin, and irrigate eyes. Call doctor if ingested. Do not induce vomiting.

-----Section VII – Precautions for Safe handling and use-----

Steps to be taken in case material is released or spilled: Dike the spill; then soak it up with inert absorbent. Keep contaminated materials and rags in approved containers rated for fire containment. Ventilate the area.

Waste disposal method: Dispose of in accordance with local, state, and federal laws where permitted.

Precautions to be taken in handling and storage: Store away from heat in a cool, dry area and use with adequate ventilation.

Other precautions: Rags and paper products soiled with solvent are a fire hazard. Dispose of properly in safety fire cans. Can spontaneously combust.

----- Section VIII – Protective Equipment / Control Measures -----

Respiratory Protection and Special Ventilation Requirements: NIDOSH Approved respirator if above threshold. Use in a well ventilated area.

Other Protective Equipment (Gloves, Goggles, ECT): Gloves, eye protection

Work / Hygiene Practices: Use ground straps when transferring materials – Handle with care.

Form Completed By: Jackie Brady, Safety and Compliance Manager

Last Updated: 9-9-11