

**00423-1002****MATERIAL SAFETY DATA SHEET****MSDS #: 576**

Page 1 of 3

Chartpak, Inc.  
One River Road  
Leeds, MA 01053  
Phone: 413-584-5446 or 800-628-1910

Emergency Medical Number: 888-786-0972

Creation Date: April 5, 2007

**Section One: Product Information**

Product Name: Grumbacher Oil Painting Medium II  
Product Sizes: 2.5 oz.  
Product Class: Mediums

**Section Two: Ingredients**

Ingredients	CAS Number	% by Weight	PEL/TLV
D-Limonene	5989-27-5	50%	N/A

**Section Three: Hazards Identification**

WARNING: COMBUSTIBLE. EXPOSURE MAY CAUSE ALLERGIC REACTIONS. SKIN IRRITANT.  
CONTAINS: D-LIMONENE.  
KEEP OUT OF REACH OF CHILDREN.

**Section Four: First Aid Measures**

Inhalation: Move to fresh air.  
Skin Contact: If skin contact occurs, wash with soap and water for 5 minutes.  
Eye Contact: Flush with flowing water.  
Ingestion: Get prompt medical attention. For further health information, contact a poison control center.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: 5762

**MATERIAL SAFETY DATA SHEET****MSDS #: 576**

Page 2 of 3

**Section Five: Fire Fighting Measures**

Flash Point: 100F

Flammability Limits (% by volume): Lower: Not explosive Upper: Not explosive

Extinguishing Media: Foam, carbon dioxide, dry chemical

Special Fire Fighting Measures: No special fire fighting procedures required.

Unusual Fire and Explosion Hazards: Combustible

**Section Six: Accidental Release Measures**

Wipe up with absorbent material.

**Section Seven: Handling and Storage**

Handling: Keep container tightly capped when not in use.

Storage: Do not store or use near heat or flame. KEEP OUT OF REACH OF CHILDREN.

**Section Eight: Exposure Controls and Personal Protection**

Respiratory Protection and Special Ventilation Requirements: Assure adequate cross-ventilation.

Other Protective Equipment (Gloves, Goggles, Etc.): Use impermeable protective gloves.

Work/Hygiene Practices: PRECAUTIONS: Avoid prolonged contact with skin. Wash hands immediately after use. When using, wear impermeable protective gloves. Do not store or use near heat or flame. Keep container tightly capped when not in use. KEEP OUT OF REACH OF CHILDREN.

**Section Nine: Physical and Chemical Properties**

Boiling Point: 176F Melting Point: Not determined

Vapor Pressure: 1.2 mm Hg Specific Gravity: 0.86

Specific Vapor Density (AIR = 1): Heavier than air Evaporation Rate (Butyl Acetate = 1): Not determined

Solubility in Water: Insoluble Reactivity in Water: Non-reactive

Appearance and Odor: Pale liquid; citrus odor

**Section Ten: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: None known

Chemical Incompatibility: None known

Hazardous Decomposition: None known

Hazardous Polymerization: Will not occur

## MATERIAL SAFETY DATA SHEET

MSDS #: 576

Page 3 of 3

**Section Eleven: Toxicological Information**

IARC Monographs: No  
 National Toxicology Program: No  
 OSHA Regulated: No  
 Effects/Symptoms of Acute Exposure: Skin irritation  
 Effects/Symptoms of Chronic Exposure: Skin irritation and/or allergic reactions  
 Medical Conditions Usually Aggravated By Overexposure of This Product: Unknown

**Section Twelve: Ecological Information**

Not available

**Section Thirteen: Disposal Considerations**

Dispose in accordance with Federal, State, and Local Regulations

**Section Fourteen: Transport Information**

Flammable Liquid, n.o.s. (Limonene), 3, UN1993, III (108F TCC), Ltd Qtys Marine Pollutant, EmS# F-E, S-E  
 Consumer Commodity, 9, ID8000, packing instruction 910

**Section Fifteen: Regulatory Information**

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

**Section Sixteen: Other Information**

HMIS Code	
Health	1
Flammability	2
Reactivity	0
Personal Protection	B

Chartpak, Inc. is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D-4236.

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.