00432-2557 -3850



# Certificate of Compliance & Material Safety Data Sheet

For Health Emergencies: CALL A POISON CONTROL CENTER For Transportation Emergencies ONLY: Call Chem-Tel USA, Canada, Puerto Rico, US Virgin Islands: Call 800-255-3924 Outside North America: Call Collect 813-248-0585

Date Prepared Rev: 7 July 2009 Replaces: 15 May 2007

#### Certificate of Compliance Section 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 PRODUCT NAME: John Howard Sanden ProMix® Oil Colors - Carrying the AP Non-Toxic Seal of the Art & Creative Materials Institute.

(Note: See additional MSDS for those John Howard Sanden ProMix® Oil Colors bearing the CL - Caution Label Required Seal of the Art & Creative Materials Institute.)

1.2 ITEM NUMBER AND SIZES: Colors Listed in Section 2 below - 37ml tubes

#### 1.3 CPSC SAFETY REGULATION CITATION

This adult product is certified to comply with the Consumer Product Safety Act (CPSA), the Federal Hazardous Substances Act, (FHSA) and its Labeling for Hazardous Art Materials Amendment, (LHAMA.)

#### 1.4 MANUFACTURER IDENTIFICATION:

Martin F. Weber Co.

2727 Southampton Road • Philadelphia, PA 19154 USA

Phone: 215-677-5600 • Fax: 215-677-3336

Email: compliance@weberart.com • Web: www.weberart.com

#### 1.5 CONTACT INFORMATION:

Regulatory & Compliance Manager

Martin/F. Weber Co.

2727 Southampton Road • Philadelphia, PA 19154 USA

Phone: 215-677-5600 • Fax: 215-677-3336

Email: compliance@weberart.com

#### 1.6 DATE & PLACE OF MANUFACTURE:

For purposes of the Consumer Product Safety Improvement Act, (CPSIA), this product is deemed to be manufactured as of the date of shipment, at the above address.

#### 1.7 DATE & PLACE PRODUCT TESTED FOR COMPLIANCE WITH THE REGULATIONS ABOVE (1.4):

Date: 24 April 2006

Place: Duke University Medical Center 2200 West Main Street, Suite 400

Durham NC 27705

#### 1.8 THIRD-PARTY LABORATORY(S) ON WHICH THIS CERTIFICATE DEPENDS

N/A

Item Numbers: 00432-2557, 00432-3850 Page 1 of 5

#### MSDS Section 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 PRODUCT NAME: John Howard Sanden ProMix® Oil Colors - Carrying the AP Non-Toxic Seal of the Art & Creative Materials Institute.

(Note: See additional MSDS for those John Howard Sanden ProMix® Oil Colors bearing the CL - Caution Label Required Seal of the Art & Creative Materials Institute.)

1.2 ITEM NUMBER AND SIZES: Colors Listed in Section 2 below - 37ml tubes

1.3 COMPANY IDENTIFICATION:

Martin/F. Weber Co.

2727 Southampton Road • Philadelphia, PA 19154 USA

Phone: 215-677-5600 • Fax: 215-677-3336

Email: compliance@weberart.com • Web: www.weberart.com

#### **SECTION 2 – COMPOSTION INFORMATION**

COMPONENT CAS# MAX. AMOUNT (% Weight)

Martin/F. Weber Company is a member of the Art & Creative Materials Institute, (ACMI) 1280 Main Street, 2nd Floor, PO Box 479, Hanson, MA 02341 USA. ACMI is a non-profit, international organization which tests and evaluates product formulations for toxicity, recommends and requires appropriate labeling. Our art and craft materials are certified by the institute to be labeled in accordance with the voluntary chronic hazard labeling standard, ASTM D-4236 of the American Society for Testing & Materials. This standard is incorporated into the US Federal Hazard Substances Act and it's LHAMA (Labeling for Hazardous Art Materials) amendment.

These products are appropriately labeled with the AP Non-Toxic Scal of ACMI. They have been certified in a program of toxicological evaluation by a medical expert, subject to review by the institute's Toxicological Advisory Board to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems.

Item No.	Color
2504	SANDEN PRO MIX O/C HALFTONE 1
2510	SANDEN PRO MIX O/C NEUTRAL 7

#### **SECTION 3 - HAZARDS IDENTIFICATION**

3.1 EMERGENCY OVERVIEW

Appearance:

Colored Paste

Physical State:

Paste

Odor:

Characteristic Linsced Oil or Safflower Oil

Hazards of Product: n.a.

3.2 POTENTIAL HEALTH EFFECTS

EFFECTS OF SINGLE ACUTE OVEREXPOSURE: n/a

CHRONIC, PROLONGED OR REPEATED OVEREXPOSURE: 11/a

Page 2 of 5 Item Numbers: 00432-2557, 00432-3850

#### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: n/a

3. 3 POTENTIAL ENVIRONMENTAL EFFECTS: n/a

#### **SECTION 4 - FIRST AID PROCEDURES**

4.1 INHALATION: n/a.

4.2 EYE CONTACT: n/a

4.3 SKIN CONTACT: n/a.

4.4 SWALLOWING n/a.

4.2 NOTES TO PHYSICIAN: n/a

#### **SECTION 5 - FIRE FIGHTING MEASURES**

5.1 FLAMMABLE PROPERTIES

**Identification Number:** 

 $\mathbf{n}/\mathbf{a}$ Flash Point - Closed Cup: Flash Point - Open Cup: >350°F (177°C)

n/a Auto-Ignition Temperature: n/a Flammable Limits in Air: n:a

5.2 EXTINGUISHING MEDIA

Foam, CO<sub>2</sub> Dry Chemical (Class B) or Halon R. Water Fog

5.3 EXTINGUISHING MEDIA

TO AVOID

5.4 SPECIAL FIRE FIGHTING

**PROCEDURES** 

**5.5 SPECIAL PROTECTIVE** 

**EQUIPMENT FOR FIREFIGHTERS** 

As with any fire situation, full face, self contained breathing apparatus

and appropriate protective clothing should be worn.

5.6 UNUSUAL FIRE AND **EXPLOSION HAZARDS** 

**PRODUCTS** 

n.a

n-a

n a

5.7 HAZARDOUS COMBUSTION

Under fire conditions, this product may release CO, CO2, and other decomposition products of undetermined hazard.

#### SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Clean up paint or paint mixed with solvents using rags or paper towels. Place in airtight containers for disposal.

#### SECTION 7 - HANDLING AND STORAGE

7.1 GENERAL HANDLING: After use, wash hands before eating drinking or smoking.

7.2 STORAGE:

n a

#### SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Page 3 of 5 Item Numbers: 00432-2557, 00432-3850

**8.1 EXPOSURE LIMITS:**  $\mathbf{n}/\mathbf{c}$ 

8.2 PERSONAL PROTECTION:

Respiratory Protection: n/a Ventilation: n/a Eye Protection:

**Protective Gloves:** Rubber or vinyl gloves or a barrier cream are useful for general

cleanliness

Other Protective Equipment: n/a

**8.3 ENGINEERING CONTROLS:** n/a

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Paste

Viscous Colored Paste Appearance:

pH:

Solubility in Water (by weight): Negligible

Odor:

Characteristic Linseed Oil or Safflower Oil

Flash Point - Closed Cup: > 350°F (177°C)

Flash Point - Open Cup: n/a

Percent Volatiles: Non-Volatile

Boiling Point (760mm Hg): n/a Freezing Point: n/a Specific Gravity  $(H_2O = 1)$ : D2 | Vapor Pressure at 20°C: n/a Vapor Density (air = 1): n/a **Evaporation Rate** n/a(Butyl Acetate = 1):

Melting Point: n/a

#### Section 10 - STABILITY AND REACTIVITY

10.1 STABILITY / INSTABILITY Stable under ordinary conditions of use and storage

Conditions to Avoid n/aIncompatible Materials n a

10.2 HAZARDOUS

POLYMERIZATION Will not occur

10.3 INHIBITORS / STABILIZERS n/a

#### SECTION 11 - TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: n/a CHRONIC TOXICITY: 11/3

#### SECTION 12 - ECOLOGICAL INFORMATION

12.1 ENVIRONMENTAL FATE 17/21 12.2 ECOTOXICITY  $\mathbf{n}/\mathbf{a}$ 12.3 FURTHER INFORMATION n/a

#### SECTION 13 - DISPOSAL CONSIDERATIONS

Page 4 of 5 Item Numbers: 00432-2557, 00432-3850

13.1 WASTE DISPOSAL METHOD
13.2 DISPOSAL CONSIDERATIONS
Dispose of in accordance with local, state and federal regulations in 3

## SECTION 14 - TRANSPORTATION INFORMATION

U.S. D.O.T

# SECTION 15 - REGULATORY INFORMATION

15.1 FEDERAL / NATIONAL

n a

15.2 STATE / LOCAL

n a

### SECTION 16 - OTHER INFORMATION

The information presented here is current as of the date of this Material Safety Data Sheet and is believed to be accurate but is not warranted to be, whether originating with the company or not. Since use of this information and the product are not under the control of Martin/F. Weber Company, it is the user's obligation to determine conditions of safe use, in advance of use, and to carefully read the product label and follow all instructions for safe use of the product.

Item Numbers: 00432-2557, 00432-3850 Page 5 of 5