Product Name:

LIQUITEX(R) SOFT BODY ARTIST ACRYLIC, CADMIUM COLORS

Product Family:

1. Chemical Product and Company Identification

ColArt Americas, Inc. **EMERGENCY TELEPHONE NUMBER:** 11Constitution Avenue 1-800-628-3385 PO Box 1396 Piscataway, NJ 08855

1-800-445-4278

SUBSTANCE:

LIQUITEX(R) SOFT BODY ARTIST ACRYLIC CADMIUM COLORS

TRADE NAMES/SYNONYMS:

LIQUITEX SOFT BODY ARTIST ACRYLIC CADMIUM COLORS

PRODUCT USE: Arts and Crafts

CREATION DATE: Mar 13 2000

REVISION DATE: 3rd November 2011

2. Composition, Information on Ingredients

COMPONENT:

Product has been certified by The Art and Creative Materials Institute, Inc. and conforms to ASTM D-4236 Standard Practice for Labeling Art Materials for Acute and Chronic Adverse Health Hazards.

Not assigned.

EC NUMBER: .Not assigned.

PERCENTAGE:

100.0

3. Hazards Identification

EC CLASSIFICATION (CALCULATED):

Not classified

EMERGENCY OVERVIEW:

COLOR:

various colors

PHYSICAL FORM:

liquid

LIQUITEX® MEDIUM VISCOSITY ADMIUM COLORS

MAJOR HEALTH HAZARDS: No significant target effects reported.

POTENTIAL HEALTH EFFECTS: INHALATION:

none

SKIN CONTACT:

none

EYE CONTACT:

none

INGESTION:

CARCINOGEN STATUS:

OSHA:

NTP: No

IARC:

No

4. First Aid Measures

INHALATION:

It is unlikely that emergency treatment will be required. Remove from exposure. Get medical attention, if needed.

SKIN CONTACT:

It is unlikely that emergency treatment will be required. If adverse effects occur, wash with soap or mild detergent and large amounts of water. Get medical attention, if needed.

EYE CONTACT:

It is unlikely that emergency treatment will be required. Wash with large amounts of water or normal saline until no evidence of chemical remains (at least 15-20 minutes). Get medical attention immediately.

INGESTION:

Contact local poison control center or physician immediately.

5. Fire Fighting Measures

FIRE AND EXPLOSION HAZARDS:

Slight fire hazard.

EXTINGUISHING MEDIA:

regular dry chemical, carbon dioxide, water, regular foam

FIRE FIGHTING:

Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products.

FLASH POINT:

No data available.

LIQUITEX® MEDIUM VISCOSITY ADMIUM COLORS

6. Accidental Release Measures

OCCUPATIONAL RELEASE:

Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal.

7. Handling and Storage

Store and handle in accordance with all current regulations and standards. See original container for storage recommendations. Keep separated from incompatible substances.

8. Exposure Controls, Personal Protection

EXPOSURE LIMITS:

LIQUITEX(R) JAR COLORS Cadmium colors only No occupational exposure limits established.

VENTILATION:

Based on available information, additional ventilation is not required.

EYE PROTECTION:

Eye protection not required under normal conditions.

Protective clothing is not required under normal conditions.

Protective gloves are not required under normal conditions.

RESPIRATOR:

No respirator is required under normal conditions of use.

9. Physical and Chemical Properties

PHYSICAL STATE:

liauid

COLOR:

various colors

ODOR:

Not available

BOILING POINT:

> 100 C

FREEZING POINT:

Not available

VAPOR PRESSURE:

Not available

VAPOR DENSITY:

Not available

SPECIFIC GRAVITY:

1.4

WATER SOLUBILITY:

Dilutable

PH: 8-9

VOLATILITY: <49.3 g/ litre

ODOR THRESHOLD:

Not available

EVAPORATION RATE: BuAc = 1

< 1

10. Stability and Reactivity

REACTIVITY:

Stable at normal temperatures and pressure.

CONDITIONS TO AVOID:

None reported.

INCOMPATIBILITIES:

oxidizing materials

HAZARDOUS DECOMPOSITION:

Thermal decomposition products: oxides of carbon

POLYMERIZATION:

Will not polymerize.

11. Toxicological Information

Not available

12. Ecological Information

Not available

13. Disposal Considerations

Dispose in accordance with all applicable regulations.

14. Transport Information

No classification assigned.

LAND TRANSPORT ADR/RID:

No classification assigned.

AIR TRANSPORT IATA/ICAO:

No classification assigned.

MARITIME TRANSPORT IMDG:

No classification assigned.

15. Regulatory Information U.S. REGULATIONS: TSCA INVENTORY STATUS: Yes TSCA 12(b) EXPORT NOTIFICATION: Not listed. CERCLA SECTION 103 (40CFR302.4): No SARA SECTION 302 (40CFR355.30): SARA SECTION 304 (40CFR355.40): SARA SECTION 313 (40CFR372.65): SARA HAZARD CATEGORIES, SARA SECTIONS 311/312 (40CFR370.21): ACUTE: No CHRONIC: No FIRE: No REACTIVE: No SUDDEN RELEASE: OSHA PROCESS SAFETY (29CFR1910.119): STATE REGULATIONS: California Proposition 65: WARNING: Do not spray apply. This product contains cadmium, a chemical known to the State of California to cause cancer by means of inhalation. **EUROPEAN REGULATIONS:**

16. Other Information

EC NUMBER: Not applicable

The information contained herein is provided for identification of hazards in normal use and does not constitute a product specification.

LIQUITEX® MEDIUM VISCOSITY ADMIUM COLORS