# **Material Safety Data Sheet**

Product Name: LIQUITEX® ACRYLIC SLOW-DRI® EXTENDER MEDIUM

#### **Product Family:**

### 1. Chemical Product and Company Identification

ColArt Americas, Inc. 11Constitution Avenue PO Box 1396 Piscataway, NJ 08855 1-800-445-4278 EMERGENCY TELEPHONE NUMBER: `1-800-628-3385

SUBSTANCE: LIQUITEX® ACRYLIC SLOW-DRI® EXTENDER MEDIUM

TRADE NAMES/SYNONYMS: LIQUITEX® ACRYLIC SLOW-DRI EXTENDER MEDIUM PRODUCT COLORS/CODES: 6704

PRODUCT USE: Arts and Crafts

CREATION DATE: Nov 14 1997

REVISION DATE: Sep 22 2005

#### 2. Composition, Information on Ingredients

COMPONENT:

Product has been certified as non-toxic by The Art and Creative Materials Institute, Inc. and conforms to ASTM D-4236 Standard Practice for Labelling Art Materials for Acute and Chronic Adverse Health Hazards.

CAS NUMBER: Not assigned.

EC NUMBER: Not assigned.

PERCENTAGE: 100

#### 3. Hazards Identification

None

EC CLASSIFICATION (CALCULATED): Not classified

EMERGENCY OVERVIEW:

PHYSICAL FORM: liquid

MAJOR HEALTH HAZARDS: No significant target effects reported.

POTENTIAL HEALTH EFFECTS:

INHALATION: none

LIQUITEX® ACRYLIC SLOW-DRI® EXTENDER MEDIUM Page 1

EYE CONTACT: none

INGESTION: none

CARCINOGEN STATUS:

OSHA: No

NTP: No

IARC: No

#### 4. First Aid Measures

INHALATION: It is unlikely that emergency treatment will be required. Remove from exposure. Get medical attention, if needed.

SKIN CONTACT:

It is unlikely that emergency treatment will be required. If adverse effects occur, wash with soap or mild detergent and large amounts of water. Get medical attention, if needed.

EYE CONTACT: It is unlikely that emergency treatment will be required. Wash with large amounts of water or normal saline until no evidence of chemical remains (at least 15-20 minutes). Get medical attention immediately.

INGESTION: Contact local poison control center or physician immediately.

## 5. Fire Fighting Measures

FIRE AND EXPLOSION HAZARDS: Slight fire hazard.

EXTINGUISHING MEDIA: regular dry chemical, carbon dioxide, water, regular foam

FIRE FIGHTING: Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products.

FLASH POINT: No data available.

## 6. Accidental Release Measures

OCCUPATIONAL RELEASE: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal.

# 7. Handling and Storage

Store and handle in accordance with all current regulations and standards. See original container for storage recommendations. Keep separated from incompatible substances.

LIQUITEX® ACRYLIC SLOW-DRI® EXTENDER MEDIUM Page 2

# 8. Exposure Controls, Personal Protection

#### **EXPOSURE LIMITS:**

LIQUITEX(R) ACRYLIC SLOW-DRI(R) EXTENDER MEDIUM: No occupational exposure limits established.

VENTILATION: Based on available information, additional ventilation is not required.

EYE PROTECTION: Eye protection not required under normal conditions.

CLOTHING: Protective clothing is not required under normal conditions.

GLOVES: Protective gloves are not required under normal conditions.

RESPIRATOR: No respirator is required under normal conditions of use. Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

## 9. Physical and Chemical Properties

PHYSICAL STATE: liquid

ODOR: Not available

BOILING POINT: > 100 C

FREEZING POINT: Not available

VAPOR PRESSURE: Not available

VAPOR DENSITY: Air = 1 > 1

SPECIFIC GRAVITY: 1.4

WATER SOLUBILITY: Miscible PH: Not available

VOLATILITY: Not available

ODOR THRESHOLD: Not available

EVAPORATION RATE: BuAc = 1 < 1

# 10. Stability and Reactivity

REACTIVITY: Stable at normal temperatures and pressure.

LIQUITEX® ACRYLIC SLOW-DRI® EXTENDER MEDIUM Page 3

CONDITIONS TO AVOID: None reported.

INCOMPATIBILITIES: oxidizing materials

HAZARDOUS DECOMPOSITION: Thermal decomposition products: oxides of carbon, various organic fragments

POLYMERIZATION: Will not polymerize.

## 11. Toxicological Information

Not available

**12. Ecological Information** Not available

## 13. Disposal Considerations

Dispose in accordance with all applicable regulations.

#### 14. Transport Information

No classification assigned.

LAND TRANSPORT ADR/RID: No classification assigned.

AIR TRANSPORT IATA/ICAO: No classification assigned.

MARITIME TRANSPORT IMDG: No classification assigned.

# 15. Regulatory Information

U.S. REGULATIONS:

TSCA INVENTORY STATUS: Yes

TSCA 12(b) EXPORT NOTIFICATION: Not listed.

CERCLA SECTION 103 (40CFR302.4): No

SARA SECTION 302 (40CFR355.30): No

SARA SECTION 304 (40CFR355.40): No

SARA SECTION 313 (40CFR372.65): No

SARA HAZARD CATEGORIES, SARA SECTIONS 311/312 (40CFR370.21):

ACUTE: No

CHRONIC: No

FIRE: No

LIQUITEX® ACRYLIC SLOW-DRI® EXTENDER MEDIUM Page 4

REACTIVE: No SUDDEN RELEASE: No OSHA PROCESS SAFETY (29CFR1910.119): No STATE REGULATIONS: California Proposition 65: No

EUROPEAN REGULATIONS: EC NUMBER: Not applicable

# 16. Other Information

The information contained herein is provided for identification of hazards in normal use and does not constitute a product specification.

Item Numbers: 00618-2045, 00618-2046, 00618-2055, 00618-2056

Page 5