# **MATERIAL SAFETY DATA SHEET**

## SECTION 1 – IDENTIFICATION AND COMPANY DETAILS

EMERGENCY:	If swallowed, call your poison control center at 1-800-222-1222.
DATE PREPARED:	November 7, 2014
PHONE: FAX: WEBSITE:	800-257-8278 717-626-9292 www.chromaonline.com
COMPANY NAME: ADDRESS:	CHROMA, INC. 205 Bucky Drive Lititz, PA 17543 U.S.A.
PRODUCT NAME:	CHROMACRYL PAINTING MEDIUM & VARNISH (All information the same for all sizes.)

Seek medical assistance for further treatment, observation and support, if necessary.

# SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Concentration
ACRYLIC EMULSION		PROPRIETARY
WATER	7732-18-5	PROPRIETARY
PRESERVATIVE		PROPRIETARY

### **SECTION 3 – HAZARDS IDENTIFICATION**

Hazardous Ingredients: NONE

Primary Routes of Entry:	NOT HAZARDOUS
Carcinogen Listing:	NOT LISTED
Health Hazards Acute:	NONE
Health Hazards Chronic:	NONE
Signs & Symptoms of Exposure:	NONE
Medical Conditions Generally Aggravated by Exposure:	NONE

# Health Effects: DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION Acute: Eye DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION Skin PROLONGED OR REPEATED CONTACT MAY CAUSE SLIGHT SKIN IRRITATION Inhaled NONE ALLOCATED Chronic NONE ALLOCATED

All Sizes – Chromacryl Painting Medium & Varnish Page 1 of 4 MSDS Date 11/14 While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

# **SECTION 4 – FIRST AID MEASURES**

Skin	WASH SKIN WITH SOAP AND WATER OR USE A PRODUCT SPECIFICALLY FORMULATED FOR WATER BASED ACRYLIC REMOVAL. IF IRRITATION PERSISTS SEEK MEDICAL HELP.
Eye	CHECK FOR AND REMOVE ANY CONTACT LENSES. FLUSH EYES UP TO 15 MINUTES WITH WATER, HOLDING EYE LIDS OPEN. IF IRRITATION PERSISTS SEEK MEDICAL HELP.
Inhaled	IF PERSON IS SHOWING ADVERSE EFFECTS, REMOVE PERSON TO FRESH AIR. SEEK MEDICAL HELP IF SYMPTOMS OCCUR.
Ingestion	TREAT SYMPTOMATICALLY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SEEK MEDICAL HELP IF SYMPTOMS OCCUR. IF SWALLOWED, CALL YOUR POISON CONTROL CENTER AT 1-800-222-1222.

# SEEK MEDICAL ASSISTANCE FOR FURTHER TREATMENT, OBSERVATION AND SUPPORT, IF NECESSARY.

### Advice to Doctor:

THIS PRODUCT CARRIES THE A.P. SEAL, CONFORMS TO ASTM D4236, AND IS CERTIFIED NON-TOXIC BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, HANSON, MA 02341 USA.

### SECTION 5 – FIRE FIGHTING MEASURES

Fire / Explosion Hazard:	NONE
Flash Point (Method):	N/A
Auto-Ignition Temperature:	N/A
Flammability Limits In Air (% by Volume):	N/A
LOWER EXPLOSIVE LIMIT (LEL):	UNKNOWN
UPPER EXPLOSIVE LIMIT (UEL):	UNKNOWN
Extinguisher Media:	N/A
Special Fire Fighting Procedures:	N/A
Unusual Fire & Explosion Hazards:	N/A

### **Extinguishing Media:**

THIS PRODUCT IS NOT FLAMMABLE. USE FIRE-EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING MATERIALS.

Page 2 of 4 MSDS Date 11/14

All Sizes – Chromacryl Painting Medium & Varnish Page 2 of 4 MSDS Date 11/14 While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations

# SECTION 6 – ACCIDENTAL RELEASE MEASURES

# Leak & Spill Procedures:

TAKE CARE FLOOR SURFACE WILL BE SLIPPERY AT SITE OF SPILLAGE.

FOR MINOR SPILLS, MOP-UP WITH RAGS AND DISPOSE OF.

FOR LARGER QUANTITIES, CONTAIN ANY SPILLS WITH INERT MATERIALS (SAND, SAWDUST, ETC.) AND TRANSFER TO CONTAINERS FOR DISPOSAL.

DO NOT CONTAMINATE WATER SOURCES OR SEWER.

# SECTION 7 – HANDLING AND STORAGE

# Handling Procedures & Equipment:

AVOID SKIN AND EYE CONTACT.

WASH HANDS AFTER USE.

# Storage Requirements:

STORE AT ROOM TEMPERATURE.

KEEP FROM FREEZING.

RECOMMENDED STORAGE CONDITIONS ARE BETWEEN 34° F AND 122 °F (1° C AND 50 °C).

# SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

# **Protective Equipment:**

Respiratory Protection (Specific Type): Protective Gloves: Eye Protection: Other Protective Equipment: Hygienic Work Practices: NONE NEEDED UNDER NORMAL CONDITIONS OF USE NOT REQUIRED NOT REQUIRED NOT REQUIRED AS WITH ANY WATER BASED PRODUCT

# Ventilation To Be Used:

Local Exhaust:	
Mechanical (General):	
Special:	
Other (Specify):	

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 215°-275°F Vapor Pressure: NOT KNOWN Specific Vapor Density (AIR=1): LIGHTER THAN AIR Solubility in Water: COMPLETELY SOLUBLE Specific Gravity (H2O=1): NOT KNOWN Melting Point: NOT KNOWN Evaporation Rate: SLOWER THAN ETHER Reactivity in Water: NOT KNOWN

Appearance & Odor: MILKY WHITE LIQUID. MAY HAVE SLIGHT AMMONIA SMELL.

N/A N/A N/A N/A

All Sizes – Chromacryl Painting Medium & Varnish Page 3 of 4 MSDS Date 11/14 While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.

# SECTION 10 - STABILITY AND REACTIVITY

Stability:	STABLE
Conditions To Avoid:	N/A
Incompatibility (Materials to Avoid):	NONE
Hazardous Decomposition Products:	NONE
Hazardous Polymerization Products:	NONE
Conditions To Avoid:	N/A

# **SECTION 11 – TOXICOLOGICAL INFORMATION**

### The toxicological information for the components is: NON-TOXIC

THIS PRODUCT CARRIES THE A.P. SEAL, CONFORMS TO ASTM D4236, AND IS CERTIFIED NON-TOXIC BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, HANSON, MA 02341 USA.

### SECTION 12 – ECOLOGICAL INFORMATION

NOT REGARDED AS DANGEROUS FOR THE ENVIRONMENT.

### **SECTION 13 – DISPOSAL CONSIDERATIONS**

### Waste Disposal Methods:

DIŠPOSE OF IN ACCORDANCE WITH LOCAL AND NATIONAL REGULATIONS FOR INERT NON-HAZARDOUS WASTE MATERIAL.

# SECTION 14 – TRANSPORT INFORMATION

NON-HAZARDOUS FOR RAIL, ROAD, SEA AND AIR TRANSPORT.

### SECTION 15 – REGULATORY INFORMATION

NONE

### SECTION 16 – OTHER INFORMATION

THIS PRODUCT DOES NOT CONTAIN EGG, DAIRY, WHEAT, GLUTEN, SOY OR PEANUT PRODUCTS, BY-PRODUCTS OR DERIVATIVES.

THIS PRODUCT DOES NOT CONTAIN LATEX MATERIALS OR ANIMAL DERIVED INGREDIENTS.

All Sizes – Chromacryl Painting Medium & Varnish Page 4 of 4 MSDS Date 11/14 While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for your consideration and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State, and Local laws and regulations.