MSDS for #00676 - LASCAUX SIRIUS MIX Material Safety Data Sheet

according to Regulation (EC) 1907/2006

Lascaux Sirius® Acryl (770-781) Product name: Revision: 25.05.2011

Print date : 29.06.2011

01. Identification of the substance/preparation and of the company/undertaking

Product name

Lascaux Sirius[®] Acryl (770-781)

Manufacturer/Supplier

Lascaux Colours & Restauro

Barbara Diethelm AG

Street/P.O.Box

Zürichstrasse 42

Country code/Postal code/Town/City

8306 Brüttisellen

Telephone / Telefax

+41 44 807 41 41 / +41 44 807 41 40

Contact

techsupport@lascaux.ch

Emergency information

+41 44 251 51 51 (Tox Center)___ ____++1 800 468 6942 (for U.S.A.)

02. Hazards identification

Hazard designation

03. Composition/information on ingredients

Chemical characterization

Pure acrylic polymer with high-quality pigments and stabilizing additives.

Hazardous components

04. First-aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

After skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

05. Fire-fighting measures

Page: 1/5

(EN/D)

Page 1 of 5

according to Regulation (EC) 1907/2006

Product name: Lascaux Sirius® Acryl (770-781)

25.05.2011

29 06 2011

Print date :



Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray.

Unsuitable extinguishing media

Waterjet.

Revision:

Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Version:

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Special protective equipment

Appropriate breathing apparatus may be required.

Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

06. Accidental release measures

Personal precautions

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

Methods for cleaning up/collecting

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferabily with a detergent; avoid use of solvents.

07. Handling and storage

Information for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws. For personal protection see Section 8. Gas mask in case of spray processing.

Information about protection against explosions and fires

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Requirements to be met by storerooms and containers

Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical equipment should be pr.tected to the appropriate standard. Floors should be of the conducting type.

Information about separation of incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Page: 2/5

(EN/D)

Page 2 of 5

MSDS for #00676 - LASCAUX SIRIUS MIX Material Safety Data Sheet

according to Regulation (EC) 1907/2006

Product name: Lascaux Sirius® Acryl (770-781) Revision: 25.05.2011

Print date : 29.06.2011

Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep away from ignition sources - No smoking. Keep containers dry and cool. Keep containers in a well-ventilated place. Comply with the health and saftey at work laws.

Storage class (VCI): 12

08. Exposure controls/personal protection

Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

Hand protection

Solvent-resistent protective gloves must be worn. For prolonged or repeated handling, use barrier creams to protect the exposed areas of the skin.

Eve protection

Use safety glasses.

Body protection

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact. After skin contact wash thorougly with soap and water or use recognised skin cleanser. Do Not use solvents or thinners.

09. Physical and chemical properties

Image

Form: Liquid. Colour: Coloured. Odour: Characteristic.

Relevant safety data

Boiling point / range : (1013 hPa) 100 °C ca. Flash point : not applicable Density: (20 °C) ca. 1.2 g/cm³ pH value : 9 ca. Viscosity : (20 °C) 3000 mPa.s ca.

10. Stability and reactivity

Conditions to avoid

Stable under recommended storage and handling conditions (See section 7).

Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

Page: 3 / 5

(EN/D)

Page 3 of 5

according to Regulation (EC) 1907/2006

Product name: Lascaux Sirius® Acryl (770-781)

Revision: 25.05.2011 Version:

Print date : 29.06.2011



When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Experience on practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatique, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

Additional toxicological information

There no data availble on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 15 for details.

12. Ecological information

Additional ecological information General ecological information

There are no data available on the product itself. Do not empty into waters or drains.

13. Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

14. Transport information

Land transport ADR/RID

Classification

Class:

Maritime transport IMDG/GGVSea

Classification

IMDG-Code:

Air transport ICAO-TI and IATA-DGR

Classification

Class:

Packaging

15. Regulatory information

National regulatory information Water pollution classification

Class: 1 according VwVwS

International regulatory information

Page: 4/5

(EN/D)

Page 4 of 5

according to Regulation (EC) 1907/2006

the spirit of colours

Lascaux Sirius® Acryl (770-781) Product name: Revision: 25.05.2011

Print date : 29.06.2011

U.S.A. Conforms to ASTM D-4236. "No health labeling required"

16. Other information

Further information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

Relevant changes

07. Information about separation of incompatible products · 08. References to the thresholds · 14. Land transport ADR/RID and GGVS/GGVE · 14. Maritime transport IMDG/GGVSea · 14. Air transport ICAO-TI and IATA-DGR · 15. Regulation on inflammable liquids (VbF) · 15. Water pollution classification

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Page: 5 / 5

(EN/D)

Page 5 of 5