00751-XXXX

DELTA SOY PAINT (ALL COLORS)

DELTA CREATIVE, INC. Material Safety Data Sheet									
IDENTITY (As Use	an label and	d Liet)			In the Brown of				
		1 LISt)			Date Prepared				
Delta Soy Paint	(All Colors)	-15701-50			August 6, 2	010	45/45/5-19/5	TO THE OWNER OF THE OWNER.	
SECTION I Manufacturer's Name Emergency Telephone Number									
Manufacturer's Name				(800) 423-4					
Delta Creative, Inc.				Telephone Numb					
2690 Pellissier Place				(562) 695-7					
2030 1 611133101	ice				Revision	000			
City Of Industry, C	alifornia 9060	11-1507			August 6, 2	010			
SECTION II - Hazard				ation	1,10,500				
Hazardous Components (*			OSHA PEL	ACGIH TLV	CA Prop 65	% (optional)
Water Based Soy		Ulling, _		(3))		N/A	N/A	N/A	N/A
Chemical Family:									
Proprietary Soy Es	ster-Alkyd Emu	Ilsion M	ixture			N/A	N/A	N/A	N/A
Chemical Formula							177		
Trade Secret: Specific chemical identities will be made available to medical professionals and others as required by 29 CFR 1910.1200. (i) (iv). This product contains a non-hazardous mixture of a modified alkyd-soy ester emulsion N/A N/A N/A							N/A	N/A	
DOT Information:						NI/A	NI/A	NI/A	NI/A
Not Regulated, No	n Hazardous					N/A	N/A	N/A	N/A
Note: No known chemical compounds listed as carcinogens under OSHA, NTP, IARC, California Prop 65, or Other.						N/A	N/A	N/A	N/A
SECTION III -Physic	cal/Chemical Ch	naracteri	istics						
Boiling Point				>212°F/100°C Specific Gravity (H ₂ O = 1)					1.0 - 1.03
Vapor Pressure (mm Hg.)				N/A	Melting Point	N/A			
Vapor Density (AIR = 1)				Evaporation Rate (Butyl Acetate = 1)					<1
Solubility in Water									
Dilutable									
Appearance and Odor									
Various colored lic		-	and the state of t						
SECTION IV -Fire a		azard D	ata						
Flash Point (Method Used	20.00	144.4			Flammable Limits			LEL	UEL N/A
Not combustible.						Not Flammable. N/A			
Extinguishing Media									
Dry chemical, CO									
Special Fire Fighting Prod									
For precaution use	e self contained	d breatr	ning appa	aratus.					
Unusual Fire and Explosion		atter if to	emperat	ure exceeds boili	na point. Pla	estic bottle ma	v burn and give	e off oxides of	Carbon/Nitroge
1100001	mi but may ep	atto	orripo. a	THE CAUCULE CO.	ng pon	10110 001110 1	y barri and gi	0 011 07.000	04.00
SECTION V -Reacti	vity Data	No.	THOMAS			The Property of			
Stability									
	Stable		None known						
	Stable	×							

Page 1 of 3

DELTA SOY PAINT (ALL COLORS)

Incompatability (Materials to Avoid)								
Strong acids an	nd alkalis.							
Hazardous Decomposit	ion or Byproducts							
None known								
Hazardous Polymerization	May Occur		Conditions to Avoid None known					
	Will Not Occur	,				-		
OFOTION III	- (4)- 11 1 D-4-	X	L	***				
SECTION VI -He	aith Hazaro Data			Inhalation?	Skin		Ingestion?	
Routes of Entry:				Yes	Skiii	Yes	Yes	
Health Hazards (Acut	e and Chronic)							
None.								
Carcinogenicity:				NTP?	IARC	Monographs	OSHA Regulated?	
				No	<u> </u>	No	No	
carcinogens								
Signs and Symptoms	of Exposure							
Inhalation: No I	known signs or sy	mptoms	s associated w	th exposure to product	t.			
Eye Contact: Slightly irritating. Does not injure eye tissue								
Ingestion: No known signs or symptoms associated with exposure to product.								
Skin Contact: Mild skin irritation is possible.								
Medical Conditions Generally Aggravated by Exposure N/A								
Emergency and First Aid Procedures Inhalation: Move exposed person to fresh air. If irritation persists, get medical attention promptly.								
Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation develops, consult a physician.								
Ingestion: Do not induce vomiting. If victim is conscious give plenty of water or milk to drink. Get medical attention immediately.								
Skin Contact: Flush contaminated skin with plenty of water. Consult a physician if irritation develops.								
SECTION VII -Precautions for Safe Handling and Use								
Steps To Be Taken in Case Material is Released or Spilled Control spill with paper towel. Dried refuse may be disposed of according to local, state and federal regulations.								
Waste Disposal Method								
Dried refuse may be disposed of according to local, state and federal regulations. Check with local authorities for details on disposal.								
Precautions to Be Taken in Handling and Storing								
Store material in a cool, dry and well ventilated area between 40°F-90°F. Keep containers closed and air tight. Avoid freezing.								
Other Precautions Keep container tightly closed when not in use.								
KEEP OUT OF REACH OF CHILDREN.								
SECTION VIII -Control Measures								
Respiratory Protection (Specify Type)								
Ventilation	Local Exhaust				Special			
		R	ecommended		ļ	None		
.	Mechanical (General)				Other			

Page 2 of 3

DELTA SOY PAINT (ALL COLORS)

	May	be used.			None			
Protective Gloves	Protective Gloves							
Impervious pla	stic or rubber.							
Protective Glasses								
Safety glasses	may be worn to avoid eye co	ntact.						
Other Protective Clothing or Equipment								
Long sleeve g	Long sleeve garments may be worn to avoid contact with skin.							
Work/Hygenic Practices								
	Clean-up with soap and water. Wash hands with soap and water after using product. Close container tightly.							
SECTION IX - D	Disclaimer							
Delta Creative, Inc. Assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the product. Such vendees assumes all risks associated with the use of this product.								
THE INFORMATION GIVEN AND RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. ALL SUCH INFORMATION IS BELIEVED TO BE TRUE AND ACCURATE TO THE BEST OF OUR KNOWLEDGE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THE OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS								
	HMIS SYMBOL	RATING		Transportation	information:			
RE	AMMABILITY 0 EACTIVITY 0 EOTECTION 0	SEVERE SERIOUS MODERATE SLIGHT	4 3 2 1		Not Regulated Not Regulated			
		MINIMAL	ó	CERCLA RQ:	None			