

Page 1/9

**Safety Data Sheet**  
acc. to ISO/DIS 1101401425-1403, 1404, 1405  
1400

Printing date 01/28/2013

Reviewed on 01/28/2013

1720  
1730**1 Identification of the substance/mixture and of the company/undertaking**

- **Product identifier**
- **Trade name:** MONTANA Primer: Universal, Metal, Plastic, Styropor
- **Article number:** T2000, T2200, T2300, T2400
- **Relevant identified uses of the substance or mixture and uses advised against --**
- **Application of the substance / the preparation**  
Anticorrosion additive  
Priming
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
L&G Vertriebs GmbH  
Häusserstr. 36  
D-69115 Heidelberg  
Tel. +49-6221-36333-30  
Fax +49-6221-36333-33  
info@montana-cans.de  
www.montana-cans.com
- **Information department:** Department Product Safety
- **Emergency telephone number:**  
Tel.: +49 6266-75-310  
Fax +49 6266-75-362  
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

**2 Hazards identification**

- **Information concerning particular hazards for human and environment:**  
Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.  
The product has to be labelled due to the calculation procedure of international guidelines.  
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.  
Warning! Pressurized container.  
Has a narcotizing effect.
- **Label elements**
- **Risk phrases:**  
Extremely flammable.  
Irritating to eyes.  
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
Repeated exposure may cause skin dryness or cracking.  
Vapours may cause drowsiness and dizziness.
- **Safety phrases:**  
Keep out of the reach of children.  
Keep away from sources of ignition - No smoking.  
Do not breathe spray.  
Avoid contact with skin and eyes.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
If swallowed, seek medical advice immediately and show this container or label.  
Use only in well-ventilated areas.
- **Special labelling of certain preparations:**  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.  
Buildup of explosive mixtures possible without sufficient ventilation.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**  
Health = 1  
Fire = 0  
Reactivity = 3

(Contd. on page 2)

USA

Page 2/9

### Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/28/2013

Reviewed on 01/28/2013

Trade name: MONTANA Primer: Universal, Metal, Plastic, Styropor

(Contd. of page 1)

- **HMIS-ratings (scale 0 - 4)**
- Health = 1
- Fire = 0
- Reactivity = 3
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT: Not applicable.**
- **vPvB: Not applicable.**

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description: Mixture of the substances listed below with nonhazardous additions.**

#### · **Dangerous components:**

67-64-1	acetone	Xi R36; F R11 R66-67	20-<25%
74-98-6	propane	F+ R12	12.5<20%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	Xn R65; N R51/53 R10-66-67	12.5<20%
106-97-8	butane	F+ R12	12.5<20%
64742-49-0	Naphtha (petroleum), hydrotreated light	Xn R65; Xi R38; F R11; N R51/53 R67	5-<10%
75-28-5	isobutane	F+ R12	5-<10%
1330-20-7	xylene, mixture of isomers	Xn R20/21; Xi R38 R10	2.5-<5.0%

- **Additional information:**
- The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.
- For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

- **Description of first aid measures**
- **General information: Take affected persons out into the fresh air.**
- **After inhalation: Supply fresh air; consult doctor in case of complaints.**
- **After skin contact: Generally the product does not irritate the skin.**
- **After eye contact:**
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.**
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed No further relevant information available.**
- **Indication of any immediate medical attention and special treatment needed**
- No further relevant information available.

### 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.**
- **For safety reasons unsuitable extinguishing agents:**
- Water
- Water with full jet
- **Special hazards arising from the substance or mixture No further relevant information available.**
- **Advice for firefighters -**

(Contd. on page 3)

USA

Page 3/9

## Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/28/2013

Reviewed on 01/28/2013

**Trade name: MONTANA Primer: Universal, Metal, Plastic, Styropor**

(Contd. of page 2)

- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Keep away from ignition sources  
Ensure adequate ventilation  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.  
Do not allow product to reach sewage system or any water course.
- **Methods and material for containment and cleaning up:**  
Do not flush with water or aqueous cleansing agents  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**  
Fumes can combine with air to form an explosive mixture.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility: Not required.**
- **Further information about storage conditions:**  
Do not gas tight seal receptacle.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **Storage class: 2B**
- **Specific end use(s) No further relevant information available.**

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems: No further data; see item 7.**
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL ( ) 2400 mg/m<sup>3</sup>, 1000 ppm

(Contd. on page 4)

USA

Page 4/9

**Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/28/2013

Reviewed on 01/28/2013

Trade name: MONTANA Primer: Universal, Metal, Plastic, Styropor

(Contd. of page 3)

REL ()	590 mg/m <sup>3</sup> , 250 ppm
TLV ()	Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm Long-term value: (1188) NIC-475 mg/m <sup>3</sup> , (500) NIC-200 ppm BEI
<b>74-98-6 propane</b>	
PEL ()	1800 mg/m <sup>3</sup> , 1000 ppm
REL ()	1800 mg/m <sup>3</sup> , 1000 ppm
TLV ()	Varies mg/m <sup>3</sup> , 1000 ppm
<b>106-97-8 butane</b>	
REL ()	1900 mg/m <sup>3</sup> , 800 ppm
TLV ()	Varies mg/m <sup>3</sup> , 1000 ppm
<b>75-28-5 isobutane</b>	
REL ()	1900 mg/m <sup>3</sup> , 800 ppm
TLV ()	Varies mg/m <sup>3</sup> , 1000 ppm
<b>1330-20-7 xylene, mixture of isomers</b>	
PEL ()	435 mg/m <sup>3</sup> , 100 ppm
REL ()	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV ()	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
<b>Ingredients with biological limit values:</b>	
<b>67-64-1 acetone</b>	
BEI ()	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
<b>1330-20-7 xylene, mixture of isomers</b>	
BEI ()	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

• **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

• **Breathing equipment:**

Filter AX  
Not necessary if room is well-ventilated.

• **Protection of hands:**

Protective gloves  
Solvent resistant gloves  
In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

USA

Page 5/9

### Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/28/2013

Reviewed on 01/28/2013

Trade name: MONTANA Primer: Universal, Metal, Plastic, Styropor

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Butyl rubber, BR
- Penetration time of glove material  
Butyl rubber gloves with a thickness of 0.4 mm are resistant to:  
Acetone: 480 min  
Butyl acetate: 60 min  
Ethyl acetate: 170 min  
Xylene: 42 min
- Eye protection: Safety glasses
- Body protection: Light weight protective clothing

#### 9 Physical and chemical properties

##### · Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

- |                  |                 |
|------------------|-----------------|
| Form:            | Aerosol         |
| Color:           | Grey            |
| Odor:            | Characteristic  |
| Odour threshold: | Not determined. |

- |             |                 |
|-------------|-----------------|
| · pH-value: | Not determined. |
|-------------|-----------------|

##### · Change in condition

- |                              |                             |
|------------------------------|-----------------------------|
| Melting point/Melting range: | Undetermined.               |
| Boiling point/Boiling range: | Not applicable, as aerosol. |

- |                |                             |
|----------------|-----------------------------|
| · Flash point: | Not applicable, as aerosol. |
|----------------|-----------------------------|

- |                                  |                 |
|----------------------------------|-----------------|
| · Flammability (solid, gaseous): | Not applicable. |
|----------------------------------|-----------------|

- |                              |                 |
|------------------------------|-----------------|
| · Decomposition temperature: | Not determined. |
|------------------------------|-----------------|

- |                  |                              |
|------------------|------------------------------|
| · Auto igniting: | Product is not selfigniting. |
|------------------|------------------------------|

- |                        |  |
|------------------------|--|
| · Danger of explosion: | In use, may form flammable/explosive vapour-air mixture. |
|------------------------|--|

##### · Explosion limits:

- |        |            |
|--------|------------|
| Lower: | 1.5 Vol %  |
| Upper: | 13.0 Vol % |

- |                                    |                       |
|------------------------------------|-----------------------|
| · Vapor pressure at 20 °C (68 °F): | 8300 hPa (6226 mm Hg) |
|------------------------------------|-----------------------|

- |                             |  |
|-----------------------------|--|
| · Density at 20 °C (68 °F): | 0.82 g/cm <sup>3</sup> (6.843 lbs/gal) |
|-----------------------------|--|

- |                    |                 |
|--------------------|-----------------|
| · Relative density | Not determined. |
|--------------------|-----------------|

- |                  |                 |
|------------------|-----------------|
| · Vapour density | Not determined. |
|------------------|-----------------|

- |                    |                 |
|--------------------|-----------------|
| · Evaporation rate | Not applicable. |
|--------------------|-----------------|

##### · Solubility in / Miscibility with

- |        |                                   |
|--------|-----------------------------------|
| Water: | Not miscible or difficult to mix. |
|--------|-----------------------------------|

- |  |                 |
|--|-----------------|
| · Partition coefficient (n-octanol/water): | Not determined. |
|--|-----------------|

##### · Viscosity:

- |            |                 |
|------------|-----------------|
| Dynamic:   | Not determined. |
| Kinematic: | Not determined. |

##### · Solvent content:

- |         |           |
|---------|-----------|
| VOC-USA | 49.3 %    |
| VOC-EU  | 713.8 g/l |

(Contd. on page 6)

USA

Page 6/9

## Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/28/2013

Reviewed on 01/28/2013

**Trade name: MONTANA Primer: Universal, Metal, Plastic, Styropor**

(Contd. of page 5)

· **Other information** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**67-64-1 acetone**

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

**64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy**

Oral	LD50	>5000 mg/kg (rat) (OECD 403)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>13.1 mg/l (rat) (OECD 403)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
Vapors have narcotic effect.

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7 xylene, mixture of isomers

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**

· **Aquatic toxicity:**

**64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy**

EC50 / 48h	43.98 mg/l (bel) (berechnet)
NOEC	10-20 mg/l (daphnia magna / Wasserfloh) (OECD 202)
	0.22 mg/l (Pseudokirchneriella subcapitata) (OECD 201 (72h))

- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)

USA

Page 7/9

**Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/28/2013

Reviewed on 01/28/2013

Trade name: MONTANA Primer: Universal, Metal, Plastic, Styropor

(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Dispose of packaging according to regulations on the disposal of packagings.

**14 Transport information**

- |  |                     |
|--|---------------------|
| · <b>UN-Number</b>   | UN1950              |
| · <b>DOT, ADR, IMDG, IATA</b>  |                     |
| · <b>UN proper shipping name</b>   | AEROSOLS, flammable |
| · <b>DOT, IATA</b>   | 1950 AEROSOLS       |
| · <b>ADR</b>   | AEROSOLS            |
| · <b>IMDG</b>  |                     |
| · <b>Transport hazard class(es)</b>  |                     |
| · <b>DOT, IMDG, IATA</b>   |                     |
| · <b>Class</b>   | 2.1                 |
| · <b>Label</b>   | 2.1                 |
| · <b>ADR</b>   |                     |
| · <b>Class</b>   | 2 SF Gases          |
| · <b>Label</b>   | 2.1                 |
| · <b>Packing group</b>   |                     |
| · <b>DOT, ADR, IMDG, IATA</b>  | Void                |
| · <b>Environmental hazards:</b>  |                     |
| · <b>Marine pollutant:</b>   | No                  |
| · <b>Special precautions for user</b>  | Warning: Gases      |
| · <b>Danger code (Kemler):</b>   | -                   |
| · <b>EMS Number:</b>   | F-D,S-U             |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.     |

(Contd. on page 8)

USA

Page 8/9

**Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/28/2013

Reviewed on 01/28/2013

Trade name: MONTANA Primer: Universal, Metal, Plastic, Styropor

(Contd. of page 7)

UN "Model Regulation": UN1950, AEROSOLS, 2.1

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

## · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

## · Section 313 (Specific toxic chemical listings):

1330-20-7 xylene, mixture of isomers

## · TSCA (Toxic Substances Control Act):

67-64-1 acetone

74-98-6 propane

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

106-97-8 butane

64742-49-0 Naphtha (petroleum), hydrotreated light

75-28-5 isobutane

64742-48-9 Naphtha (petroleum), hydrotreated heavy

## · Proposition 65

## · Chemicals known to cause cancer:

None of the ingredients is listed.

## · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

## · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

## · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

## · Cancerogenity categories

## · EPA (Environmental Protection Agency)

67-64-1 acetone

I

1330-20-7 xylene, mixture of isomers

I

## · TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone

A4

1330-20-7 xylene, mixture of isomers

A4

## · MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

## · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

## · OSHA-Ca (Occupational Safety &amp; Health Administration)

None of the ingredients is listed.

## · Product related hazard informations:

## · Hazard symbols:

Xi Irritant

F+ Extremely flammable

(Contd. on page 9)

USA



Page 9/9

**Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/28/2013

Reviewed on 01/28/2013

Trade name: MONTANA Primer: Universal, Metal, Plastic, Styropor

(Contd. of page 8)

- **Risk phrases:**  
Extremely flammable.  
Irritating to eyes.  
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
Repeated exposure may cause skin dryness or cracking.  
Vapours may cause drowsiness and dizziness.
- **Safety phrases:**  
Keep out of the reach of children.  
Keep away from sources of ignition - No smoking.  
Do not breathe spray.  
Avoid contact with skin and eyes.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
If swallowed, seek medical advice immediately and show this container or label.  
Use only in well-ventilated areas.
- **Special labeling of certain preparations:**  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray on a naked flame or any incandescent material.  
Buildup of explosive mixtures possible without sufficient ventilation.
- **Information about limitation of use:** Employment restrictions concerning young persons must be observed.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Contact:** Anwendungstechnik
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organization  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent

USA