MSDS for #01425 - MONTANA GOLD ACRYLIECC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

1 Identification

- · Product identifier
- · Trade name: MONTANA NightGlow
- · Article number: NG1000, 376245
- · Relevant identified uses of the substance or mixture and uses advised against --
- · Application of the substance / the mixture Lacquer
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MONTANA CANS

Häusserstr. 36

D-69115 Heidelberg

Tel. +49-6221-36333-30

Fax +49-6221-36333-33

info@montana-cans.de www.montana-cans.com

- · Information department: Department Product Safety
- · Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

2 Hazard(s) identification

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurized container.

Has a narcotizing effect.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms GHS02, GHS07, GHS08
- · Signal word Danger
- · Hazard statements

Extremely flammable aerosol. Pressurized container: May burst if heated.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe spray.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents / container in accordance with local/regional/national/international regulations.

· Classification system:

NFPA ratings (scale 0 - 4)

Health = 0

Fire = 0

Reactivity = 3

· HMIS-ratings (scale 0 - 4)

Health = 0

Fire = 0

Reactivity = 3

(Contd. on page 2)

JSA -

Item Numbers: 01425-1408 Page 1 of 10

Safety Data Sheet MSDS for #01425 - MONTANA GOLD ACRYLIECC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

(Contd. of page 1)

(Contd. on page 3)

Trade name: MONTANA NightGlow

- · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

• •	tances listed below with nonhazardous additions.	
· Dangerous components:		
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000 Reg.nr.: 01-2119486944-21	propane F+ R12	12.5-<20
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 RTECS: AF 7350000 Reg.nr.: 01-2119485493-29	n-butyl acetate R10-66-67	12.5-<20
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 RTECS: EJ 4200000 Reg.nr.: 01-2119474691-32	butane F+ R12	12.5-<20
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49	acetone Xi R36; F R11 R66-67	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 RTECS: TZ 4300000 Reg.nr.: 01-2119485395-27	isobutane F+ R12	5-<10%
CAS: 68920-06-9 EC number: 920-750-0 Reg.nr.: 01-2119473851-33-xxx	Kohlenwasserstoffe, C7-9 Xn R65; F R11; N R51/53 c R66-67	2.5-<5.0
CAS: 92128-66-0 EC number: 926-605-8	Kohlenwasserstoffe, C6-7 Xn R65; Xi R38; N R51/53 R67	2.5-<5.0
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1 RTECS: GU 6300000	cyclohexane Xn R65; Xi R38; F R11; N R50/53 R67	2.5-<5.0

Page 2 of 10 Item Numbers: 01425-1408

MSDS for #01425 - MONTANA GOLD ACRYLICCC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

Trade name: MONTANA NightGlow

		(Contd. of page 2)
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 RTECS: EO 1400000 Reg.nr.: 01-2119484630-38	butan-1-ol Xn R22; Xi R37/38-41 R10-67	<2.5%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0 RTECS: MN 9275000	n-hexane Xn R48/20-62-65; Xi R38; F R11; N R51/53 R67 Repr. Cat. 3	≤0.5%

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply. For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

*

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

· Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

MSDS for #01425 - MONTANA GOLD ACRYLIECC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

Trade name: MONTANA NightGlow

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- $\cdot \textit{Further information about storage conditions:} \\$

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 2B
- · Specific end use(s) No further relevant information available.

Addition	nal information about design of technical systems: No further data; see item 7.	
	parameters	
-	nents with limit values that require monitoring at the workplace:	
74-98-6	propane	
PEL ()	Long-term value: 1800 mg/m³, 1000 ppm	
REL ()	Long-term value: 1800 mg/m³, 1000 ppm	
TLV()	refer to Appendix F	
123-86-4	4 n-butyl acetate	
PEL ()	Long-term value: 710 mg/m³, 150 ppm	
REL ()	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm	
TLV()	Short-term value: 950 mg/m^3 , 200 ppm Long-term value: 713 mg/m^3 , 150 ppm	
106-97-	8 butane	
REL ()	Long-term value: 1900 mg/m³, 800 ppm	
TLV()	Short-term value: 2370 mg/m³, 1000 ppm	
67-64-1	acetone	
PEL ()	Long-term value: 2400 mg/m³, 1000 ppm	
REL ()	Long-term value: 590 mg/m³, 250 ppm	
TLV ()	Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm BEI	
108-65-	6 2-methoxy-1-methylethyl acetate	
WEEL (Long-term value: 50 ppm	
75-28-5	isobutane	

Page 4 of 10

MSDS for #01425 - MONTANA GOLD ACRYLICCC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

Trade name: MONTANA NightGlow

	(Contd. of page 4
110-82	2-7 cyclohexane
PEL ()	Long-term value: 1050 mg/m³, 300 ppm
REL ()	Long-term value: 1050 mg/m³, 300 ppm
TLV()	Long-term value: 344 mg/m³, 100 ppm
71-36-	3 butan-1-ol
PEL ()	Long-term value: 300 mg/m³, 100 ppm
REL ()	Ceiling limit value: 150 mg/m³, 50 ppm
	Skin
TLV()	Long-term value: 61 mg/m³, 20 ppm
· Ingred	lients with biological limit values:
67-64-	1 acetone
BEI ()	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Breathing equipment:

 $Filter\,AX$

Not necessary if room is well-ventilated.

· Protection of hands:

Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Butyl rubber, BR
- · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

· Eye protection: Safety glasses

0.707			
9 Phvs	ical and	t chemic	al properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:

Aerosol

Color:

According to product specification

· Odor:

Characteristic

· Odour threshold:

Not determined.

· pH-value:

Not determined.

(Contd. on page 6)

USA

MSDS for #01425 - MONTANA GOLD ACRYLIECC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

Trade name: MONTANA NightGlow

	(Contd. of page
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits: Lower: Upper:	1.2 Vol % 10.9 Vol %
· Vapor pressure at 20 °C (68 °F):	8300 hPa (6226 mm Hg)
· Density at 20 °C (68 °F): · Relative density · Vapour density · Evaporation rate	0.76 g/cm³ (6.342 lbs/gal) Not determined. Not determined. Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: VOC-USA · Other information	68.6 % No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

110-82-7 cyclohexane

Oral LD50 12705 mg/kg (rat)

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 7)

MSDS for #01425 - MONTANA GOLD ACRYLIECC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

(Contd. of page 6)

Trade name: MONTANA NightGlow

- · Additional toxicological information: Vapors have narcotic effect.
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN1950
UN proper shipping name	
DOT	Aerosols, flammable
ADR	UN1950 Aerosols, ENVIRONMENTALLY HAZARDOUS
<i>IMDG</i>	AEROSOLS
IATA	AEROSOLS, flammable
Transport hazard class(es)	
DOT, IMDG, IATA	
Class	2.1

Safety Data Sheet MSDS for #01425 - MONTANA GOLD ACRYLIECC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

Trade name: MONTANA NightGlow

	(Contd. of page
· Label	2.1
\cdot ADR	
· Class	2 5F Gases
· Label	2.1
· Packing group	
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Gases
· Danger code (Kemler):	-
· EMS Number:	F- D , S - U
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
\cdot $IMDG$	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, Aerosols, ENVIRONMENTALLY HAZARDOUS, 2.1

15 Regulatory information

· Section 355 (extremely hazardous substances):

- $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture} \; . \\$
- · Sara

None of the i	ngredient is listed.
· Section 313 (Specific toxic chemical listings):
71-36-3 bu	tan-1-ol
110-54-3 n-l	nexane
	Substances Control Act):
74-98-6	propane
123-86-4	n-butyl acetate
106-97-8	butane
68611-70-1	Zinc sulfide (ZnS), copper chloride-doped
67-64-1	acetone
108-65-6	2-methoxy-1-methylethyl acetate
75-28-5	isobutane
68920-06-9	Kohlenwasserstoffe, C7-9
71-36-3	butan-1-ol
110-54-3	n-hexane
2687-91-4	1-Ethylpyrrolidin-2-on
64742-95-6	Solvent naphtha (petroleum), light arom.
147900-93-4	fatty acids
	(Contd. on page 9)

MSDS for #01425 - MONTANA GOLD ACRYLICCC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

Trade name: MONTANA NightGlow

85711-55-3 Fatty acids, tall-oil, compds. with oleylamine
7447-41-8 lithium chloride

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· Cancerog	tenity categories	
· EPA (En	vironmental Protection Agency)	
67-64-1	acetone	I
71-36-3	butan-1-ol	D
110-54-3	n-hexane	II
· TLV (Thr	eshold Limit Value established by ACGIH)	
67-64-1 d	acetone	A4
· MAK (Ge	rman Maximum Workplace Concentration)	
None of th	he ingredients is listed.	
· NIOSH-C	Ca (National Institute for Occupational Safety and Health)	
None of th	he ingredients is listed.	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms GHS02, GHS07, GHS08
- · Signal word Danger
- · Hazard statements

Extremely flammable aerosol. Pressurized container: May burst if heated.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe spray.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents / container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

R10 Flammable.

R11 Highly flammable.

R12 Extremely flammable.

R22 Harmful if swallowed.

(Contd. on page 10)

USA

MSDS for #01425 - MONTANA GOLD ACRYLIECC. to OSHA HCS

Printing date 08/05/2014

Reviewed on 08/05/2014

(Contd. of page 9)

Trade name: MONTANA NightGlow

R36 Irritating to eyes.

R37/38 Irritating to respiratory system and skin.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· Contact: Anwendungstechnik

· Date of preparation / last revision 08/05/2014 / -

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3