



Certificate of Compliance & Material Safety Data Sheet

01514-1004

For Health Emergencies: CALL A POISON CONTROL CENTER
For Transportation Emergencies ONLY: Call Chem-Tel
USA, Canada, Puerto Rico, US Virgin Islands: Call 800-255-3924
Outside North America: Call Collect 813-248-0585

Date Prepared Rev: 15 October 2009 Replaces: 8 July 2009

# Certificate of Compliance

1.1 PRODUCT NAME:

Weber® Pure Gum Spirits of Turpentine

1.2 ITEM NUMBER AND SIZES:

1691 - 118ml, 1692 - 236ml, 1693 - 473ml

1.3 CPSC SAFETY REGULATION CITATION

This adult product is certified to comply with the Consumer Product Safety Act (CPSA), the Poison Prevention Packaging Act, the Federal Hazardous Substances Act, (FHSA) and its Labeling for Hazardous Art

Materials Amendment, (LHAMA.)

1.4 MANUFACTURER IDENTIFICATION:

Martin/F. Weber Co.

2727 Southampton Road • Philadelphia, PA 19154 USA

Phone: 215-677-5600 • Fax: 215-677-3336

Email: compliance@weberart.com • Web: www.weberart.com

1.5 CONTACT INFORMATION:

Regulatory & Compliance Manager

Martin/F. Weber Co.

2727 Southampton Road • Philadelphia, PA 19154 USA

Phone: 215-677-5600 • Fax: 215-677-3336

Email: compliance@weberart.com

1.6 DATE & PLACE OF MANUFACTURE:

For purposes of the Consumer Product Safety Improvement Act, (CPSIA), this product is deemed to be manufactured as of the date of shipment, at

the above address.

1.7 DATE & PLACE PRODUCT TESTED FOR COMPLIANCE WITH THE REGULATIONS ABOVE (1.4):

Date: 21 March 2009

Place: Duke University Medical Center 2200 West Main Street, Suite 400

Durham NC 27705

1.8 THIRD-PARTY LABORATORY(S) ON WHICH THIS CERTIFICATE DEPENDS

N/A

# **Material Safety Data Sheet**

#### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 PRODUCT NAME:

Weber® Pure Gum Spirits of Turpentine

1.2 ITEM NUMBER AND SIZES:

1691 - 118ml, 1692 - 236ml, 1693 - 473ml

1.3 COMPANY IDENTIFICATION:

Martin/F. Weber Co.

2727 Southampton Road • Philadelphia, PA 19154 USA

Phone: 215-677-5600 • Fax: 215-677-3336

Email: compliance@weberart.com • Web: www.weberart.com

#### **SECTION 2 - COMPOSTION INFORMATION**

COMPONENT

CAS#

MAX. AMOUNT

9005-90-7

(% Weight) 100

Pure Gum Spirits of Turpentine (Contains Delta 3-Carene)

#### **SECTION 3 – HAZARDS IDENTIFICATION**

#### 3.1 EMERGENCY OVERVIEW

Appearance:

Clear liquid

**Physical State:** 

Liquid

Odor:

Typical pine derivative or turpentine odor

Hazards of Product: Flammable, Harmful or Fatal if Swallowed. Vapor harmful. Exposure may cause allergic

reactions.

# 3.2 POTENTIAL HEALTH EFFECTS

## EFFECTS OF SINGLE ACUTE OVEREXPOSURE:

DANGER: Flammable, Harmful or Fatal if Swallowed. Vapor harmful. Exposure may cause allergic reactions.

# CHRONIC, PROLONGED OR REPEATED OVEREXPOSURE:

Vapor harmful. Exposure may cause allergic reactions.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Eye skin and upper respiratory conditions

3. 3 POTENTIAL ENVIRONMENTAL EFFECTS: n/a

# **SECTION 4 – FIRST AID PROCEDURES**

- 4.1 INHALATION: Move to fresh air. Get prompt medical attention.
- 4.2 EYE CONTACT: Wash eyes with tap water for five to ten (5-10) minutes. If irritation persists, seek prompt medical attention.
- 4.3 SKIN CONTACT: Wash affected area with soap and water for five to ten (5 10) minutes. If irritation persists, seek prompt medical attention.

Page 2 of 5 Item Numbers: 01514-1004

4.4 SWALLOWING: If swallowed, do not induce vomiting. Call a physician or Poison Control Center immediately.

4.2 NOTES TO PHYSICIAN: n/a

#### **SECTION 5 - FIRE FIGHTING MEASURES**

5.1 FLAMMABLE PROPERTIES

Identification Number: Flash Point - Closed Cup: UN 1299 95°F (35°C)

Flash Point - Open Cup:

n/a

Auto-Ignition Temperature:

476°F (247°C)

Flammable Limits in Air:

n/a

5.2 EXTINGUISHING MEDIA

Foam, CO2, Dry Chemical (Class B) or Halon®

5.3 EXTINGUISHING MEDIA

TO AVOID

Water

5.4 SPECIAL FIRE FIGHTING

**PROCEDURES** 

n/a

5.5 SPECIAL PROTECTIVE

EQUIPMENT FOR FIREFIGHTERS

As with any fire situation, full face, self contained breathing apparatus and appropriate protective clothing should be worn.

5.6 UNUSUAL FIRE AND

**EXPLOSION HAZARDS** 

n/a

5.7 HAZARDOUS COMBUSTION

**PRODUCTS** 

Under fire conditions, this product may release CO, CO2 and other decomposition products of undetermined hazard.

# SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Keep sources of ignition away. Small quantities may be cleaned up with rags or paper towels and transferred to airtight containers for disposal. Rags or paper towels soaked with this material should be placed in approved waste cans and / or soaked with water, for disposal in accordance with local state and federal regulations.

# SECTION 7 - HANDLING AND STORAGE

7.1 GENERAL HANDLING: Avoid ingestion. Avoid breathing vapors. Use exhaust fan to remove vapors and assure adequate ventilation. Do not transfer contents to unlabeled containers. KEEP OUT OF THE REACH OF CHILDREN. Keep from sources of ignition, oxidizing materials, heat and flame. KEEP AWAY FROM OPEN FLAMES. NO SMOKING in areas of use or storage.

7.2 STORAGE: Keep from sources of ignition, oxidizing materials, heat and flame. Keep containers closed when not in use.

Page 3 of 5 Item Numbers: 01514-1004

#### SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

**8.1 EXPOSURE LIMITS:** 

100 PPM ACGIH TLV

8.2 PERSONAL PROTECTION:

**Respiratory Protection:** 

If TLV is exceeded, MSHA / NIOSH approved organic vapor

respiratory protection should be worn.

Ventilation: Eve Protection: **Protective Gloves:**  Use exhaust fan to remove vapors and assure adequate ventilation. Use OSHA approved chemical splash goggles with side shields

Neoprene or rubber – impervious gloves

Other Protective Equipment:

Body protection suitable for the work environment

8.3 ENGINEERING CONTROLS:

n/a

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Appearance:

Liquid Clear liquid

pH:

Solubility in Water (by weight):

Odor:

Negligible

Typical pine derivative or turpentine odor 91°F (33°C)

Flash Point - Closed Cup: Flash Point - Open Cup:

n/a

Percent Volatiles:

99%

Boiling Point (760mm Hg):

302° - 320° F (150° - 160°C)

Freezing Point: Specific Gravity ( $H_2O = 1$ ):

n/a 0.87 4mg Hg

Vapor Pressure at 20°C: Vapor Density (air = 1):

4.8

Evaporation Rate

 $\leq 1$ 

(Butyl Acetate = 1):

Melting Point:

n/a

## Section 10 - STABILITY AND REACTIVITY

10.1 STABILITY / INSTABILITY

Conditions to Avoid **Incompatible Materials**  Stable under ordinary conditions of use and storage Keep from heat, open flame and sources of ignition Strong oxidizing agents, acids or acidic materials

10.2 HAZARDOUS

**POLYMERIZATION** 

Will not occur

10.3 INHIBITORS / STABILIZERS

n/a

#### SECTION 11 - TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: DANGER. Flammable, Harmful or Fatal if Swallowed. Vapor harmful. Exposure may cause allergic reactions.

CHRONIC TOXICITY: Vapor harmful. Exposure may cause allergic reactions.

Page 4 of 5 Item Numbers: 01514-1004

SECTI	ON 12 – ECOLOGICAL INFORMATION
12.1 ENVIRONMENTAL FATE	n/a
12.2 ECOTOXICITY	n/a
12.3 FURTHER INFORMATION	n/a 
SECTI	ON 13 – DISPOSAL CONSIDERATIONS
13.1 WASTE DISPOSAL METHOD 13.2 DISPOSAL CONSIDERATIONS	Dispose of in accordance with local, state and federal regulations Keep from heat, open flame, sparks and sources of ignition
SECTION	14 – TRANSPORTATION INFORMATION
U.S. D.O.T	Domestic Ground: ORM-D Consumer Commodity
	Ocean Freight: UN 1263 Paint Related Material,
	Class 3 PG III, Limited Quantity Air Freight: DO NOT SHIP via air without special packaging and
	labeling. Contact your air carrier for detailed instructions
SECTI	ON 15 – REGULATORY INFORMATION
15.1 FEDERAL / NATIONAL	n/a
15.2 STATE / LOCAL	n/a

The information presented here is current as of the date of this Material Safety Data Sheet and is believed to be accurate but is not warranted to be, whether originating with the company or not. Since use of this information and the product are not under the control of Martin/F. Weber Company, it is the user's obligation to determine conditions of safe use, in advance of use, and to carefully read the product label and follow all instructions for safe use of the product.

ttem Numbers: 01514-1004 Page 5 of 5