

01558-5923 -5924

MAIMERI S.p.A.		Revision nr.28 Dated 08/01/2010 Printed on 08/01/2010 Page n. 1 / 4
CLASSICO OIL COLOURS 03405 King's Blue Light		
Safety Data Sheet		
1. Identification of the substance / preparation and the Company		
1.1 Identification of the substance or preparation		
Code:	03405	
Product name	CLASSICO OIL COLOURS 03405 King's Blue Light	
1.2 Use of the substance / preparation		
Intended use	Oil colour	
1.3 Company identification		
Name	MAIMERI S.p.A.	
Full address	Via Gianni Maimeri, 1	
District and Country	20060 Mediglia (MI) Italia	
	Tel. +39 02 906981	
	Fax +39 02 90698999	
e-mail address of the competent person responsible for the Safety Data Sheet	schedesicurezza@maimerispa.it	
Product distribution by	MAIMERI S.P.A. VIA G.MAIMERI 1 20060 BETTOLINO DI MEDIGLIA (MI) ITALY	
1.4 Emergency telephone		
For urgent inquiries refer to	+39 02 906981	
2. Hazards Identification.		
2.1 Substance/Preparation Classification.		
This product is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments. Therefore, this product requires a safety data sheet according to the Regulation (EC) 1907/2006 and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.		
Danger Symbols:	N	
R phrases:	50/53	
2.2 Danger Identification.		
VERY TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.		
3. Composition / Information on Ingredients.		
Contains:		
Name.	Concentration % (C).	Classification.
OSSIDO DI ZINCO	58<= C <62	N R 50/53
C.A.S. number	1314-13-2	
INDEX number	PW 4	
The complete text of -R- phrases is specified in section 16.		
4. First aid measures.		
No episodes of damage to health ascribable to the product have been reported. Nevertheless, observance of good industrial hygiene is recommended.		

MSDS EPT 0801

MAIMERI S.p.A. CLASSICO OIL COLOURS 03405 King's Blue Light	Revision nr.28 Dated 08/01/2010 Printed on 08/01/2010 Page n. 2 / 4
5. Fire-fighting measures. GENERAL INFORMATION Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SUITABLE EXTINGUISHING MEDIA The extinction equipment should be of the conventional kind: carbon dioxide, foam, powder and nebulised water. EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS None in particular. HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc). SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Hardhat with visor, fireproof clothing (fireproof jacket and trousers with straps around arms, legs and waist), work gloves (fireproof, cut proof and dielectric), a depressurised mask with facemask covering the whole of the operator's face or a self-respirator (self-protector) in the event of large quantities of fume.	
6. Accidental release measures. PERSONAL PRECAUTIONS Use breathing equipment if fumes or powders are released into the air. ENVIRONMENTAL PRECAUTIONS The product must not penetrate the sewers, surface water, ground water and neighbouring areas. METHODS FOR CLEANING UP Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.	
7. Handling and storage. Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity. Refer to the other sections of this data sheet for information relating to health and environmental risks.	
8. Exposure control / personal protection. 8.1 Exposure limit values. Not available. 8.2 Exposure controls. As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent. HAND PROTECTION Protect hands with category I (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in latex, PVC or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure. SKIN PROTECTION Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls. RESPIRATORY PROTECTION If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141). The use of breathing protection equipment, such as masks with organic vapour and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited. If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138). EYE PROTECTION Use of protective airtight goggles (ref. standard EN 166) recommended.	

MSDS EPT 0001

MAIMERI S.p.A.		Revision nr.28 Dated 08/01/2010 Printed on 08/01/2010 Page n. 3 / 4																																																																									
CLASSICO OIL COLOURS		03405 King's Blue Light																																																																									
9. Physical and chemical properties. <table style="width: 100%; border: none;"> <tr> <td style="width: 40%;">Colour</td> <td colspan="3">SKY BLUE</td> </tr> <tr> <td>Odour</td> <td colspan="3">LINSEED OIL</td> </tr> <tr> <td>Appearance</td> <td colspan="3">PASTE</td> </tr> <tr> <td>Solubility</td> <td colspan="3">INSOLUBLE, DILUTE WITH WHITE SPIRIT</td> </tr> <tr> <td>Viscosity</td> <td colspan="3">Not available.</td> </tr> <tr> <td>Vapour density</td> <td colspan="3">Not available.</td> </tr> <tr> <td>Evaporation Rate</td> <td colspan="3">Not available.</td> </tr> <tr> <td>Reactive Properties</td> <td colspan="3">Not available.</td> </tr> <tr> <td>Partition coefficient: n-octanol/water</td> <td colspan="3">Not available.</td> </tr> <tr> <td>pH.</td> <td colspan="3">Not available.</td> </tr> <tr> <td>Boiling point.</td> <td colspan="3">Not available.</td> </tr> <tr> <td>Flash point.</td> <td style="text-align: center;">></td> <td>61</td> <td>°C.</td> </tr> <tr> <td>Explosive properties.</td> <td colspan="3">Not available.</td> </tr> <tr> <td>Vapour pressure.</td> <td colspan="3">Not available.</td> </tr> <tr> <td>Specific gravity.</td> <td colspan="3">0,2 Kg/l</td> </tr> <tr> <td>Solid content:</td> <td colspan="3">72,38 %</td> </tr> <tr> <td>VOC (Directive 1999/13/EC) :</td> <td>0,09 %</td> <td>- 2,08</td> <td>g/litre of preparation.</td> </tr> <tr> <td>VOC (volatile carbon) :</td> <td>0,08 %</td> <td>- 1,76</td> <td>g/litre of preparation.</td> </tr> </table>				Colour	SKY BLUE			Odour	LINSEED OIL			Appearance	PASTE			Solubility	INSOLUBLE, DILUTE WITH WHITE SPIRIT			Viscosity	Not available.			Vapour density	Not available.			Evaporation Rate	Not available.			Reactive Properties	Not available.			Partition coefficient: n-octanol/water	Not available.			pH.	Not available.			Boiling point.	Not available.			Flash point.	>	61	°C.	Explosive properties.	Not available.			Vapour pressure.	Not available.			Specific gravity.	0,2 Kg/l			Solid content:	72,38 %			VOC (Directive 1999/13/EC) :	0,09 %	- 2,08	g/litre of preparation.	VOC (volatile carbon) :	0,08 %	- 1,76	g/litre of preparation.
Colour	SKY BLUE																																																																										
Odour	LINSEED OIL																																																																										
Appearance	PASTE																																																																										
Solubility	INSOLUBLE, DILUTE WITH WHITE SPIRIT																																																																										
Viscosity	Not available.																																																																										
Vapour density	Not available.																																																																										
Evaporation Rate	Not available.																																																																										
Reactive Properties	Not available.																																																																										
Partition coefficient: n-octanol/water	Not available.																																																																										
pH.	Not available.																																																																										
Boiling point.	Not available.																																																																										
Flash point.	>	61	°C.																																																																								
Explosive properties.	Not available.																																																																										
Vapour pressure.	Not available.																																																																										
Specific gravity.	0,2 Kg/l																																																																										
Solid content:	72,38 %																																																																										
VOC (Directive 1999/13/EC) :	0,09 %	- 2,08	g/litre of preparation.																																																																								
VOC (volatile carbon) :	0,08 %	- 1,76	g/litre of preparation.																																																																								
10. Stability and reactivity. The product is stable in normal conditions of use and storage. In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released.																																																																											
11. Toxicological information. According to currently available data, this product has not yet produced health damages. Anyway, it must be handled carefully according to good industrial practices. This product may have slight health effects on sensitive people, by inhalation and/or cutaneous absorption and/or contact with eyes and/or ingestion.																																																																											
12. Ecological information. This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it may even have negative effects on aquatic environment.																																																																											
13. Disposal consideration. Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.																																																																											
14. Transport Information. These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations. Road and rail transport: <table style="width: 100%; border: none;"> <tr> <td style="width: 30%;">ADR/RID Class:</td> <td style="width: 10%;">9</td> <td style="width: 10%;">UN:</td> <td style="width: 10%;">3082</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> </tr> <tr> <td>Packing Group:</td> <td>III</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Label:</td> <td>9</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Nr. Kemler:</td> <td>90</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Limited Quantity:</td> <td>LQ07</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Tunnel restriction code:</td> <td>(E)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Proper Shipping Name:</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>  				ADR/RID Class:	9	UN:	3082			Packing Group:	III					Label:	9					Nr. Kemler:	90					Limited Quantity:	LQ07					Tunnel restriction code:	(E)					Proper Shipping Name:																																			
ADR/RID Class:	9	UN:	3082																																																																								
Packing Group:	III																																																																										
Label:	9																																																																										
Nr. Kemler:	90																																																																										
Limited Quantity:	LQ07																																																																										
Tunnel restriction code:	(E)																																																																										
Proper Shipping Name:																																																																											

MSDS EPY 0801

MAIMERI S.p.A.		Revision nr.28 Dated 08/01/2010 Printed on 08/01/2010 Page n. 4 / 4																																																																																											
CLASSICO OIL COLOURS		03405 King's Blue Light																																																																																											
Carriage by sea (shipping): <table style="width: 100%; border: none;"> <tr> <td style="width: 30%;">IMO Class:</td> <td style="width: 10%;">9</td> <td style="width: 10%;">UN:</td> <td style="width: 10%;">3082</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> </tr> <tr> <td>Packing Group:</td> <td>III</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Label:</td> <td>9</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>EMS:</td> <td>F-A, S-F</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Marine Pollutant:</td> <td>YES</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Proper Shipping Name:</td> <td colspan="5">ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (OSSIDO DI ZINCO)</td> </tr> </table> Transport by air: <table style="width: 100%; border: none;"> <tr> <td style="width: 30%;">IATA:</td> <td style="width: 10%;">9</td> <td style="width: 10%;">UN:</td> <td style="width: 10%;">3082</td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> </tr> <tr> <td>Packing Group:</td> <td>III</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Label:</td> <td>9</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Cargo:</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Packaging instructions:</td> <td>914</td> <td>Maximum quantity:</td> <td>450 L</td> <td></td> <td></td> </tr> <tr> <td>Pass.:</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Packaging instructions:</td> <td>914</td> <td>Maximum quantity:</td> <td>450 L</td> <td></td> <td></td> </tr> <tr> <td>Special Instructions:</td> <td colspan="5">A97, A158</td> </tr> <tr> <td>Proper Shipping Name:</td> <td colspan="5">ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (OSSIDO DI ZINCO)</td> </tr> </table>				IMO Class:	9	UN:	3082			Packing Group:	III					Label:	9					EMS:	F-A, S-F					Marine Pollutant:	YES					Proper Shipping Name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (OSSIDO DI ZINCO)					IATA:	9	UN:	3082			Packing Group:	III					Label:	9					Cargo:						Packaging instructions:	914	Maximum quantity:	450 L			Pass.:						Packaging instructions:	914	Maximum quantity:	450 L			Special Instructions:	A97, A158					Proper Shipping Name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (OSSIDO DI ZINCO)				
IMO Class:	9	UN:	3082																																																																																										
Packing Group:	III																																																																																												
Label:	9																																																																																												
EMS:	F-A, S-F																																																																																												
Marine Pollutant:	YES																																																																																												
Proper Shipping Name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (OSSIDO DI ZINCO)																																																																																												
IATA:	9	UN:	3082																																																																																										
Packing Group:	III																																																																																												
Label:	9																																																																																												
Cargo:																																																																																													
Packaging instructions:	914	Maximum quantity:	450 L																																																																																										
Pass.:																																																																																													
Packaging instructions:	914	Maximum quantity:	450 L																																																																																										
Special Instructions:	A97, A158																																																																																												
Proper Shipping Name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (OSSIDO DI ZINCO)																																																																																												
15. Regulatory Information.  DANGEROUS FOR THE ENVIRONMENT <table style="width: 100%; border: none;"> <tr> <td style="width: 15%; vertical-align: top;"> R 50/53 S 2 S 29 S 46 S 61 </td> <td style="width: 85%; vertical-align: top;"> VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. KEEP OUT OF THE REACH OF CHILDREN. DO NOT EMPTY INTO DRAINS. IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL. AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS/SAFETY DATA SHEETS. </td> </tr> </table> Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.				R 50/53 S 2 S 29 S 46 S 61	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. KEEP OUT OF THE REACH OF CHILDREN. DO NOT EMPTY INTO DRAINS. IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL. AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS/SAFETY DATA SHEETS.																																																																																								
R 50/53 S 2 S 29 S 46 S 61	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. KEEP OUT OF THE REACH OF CHILDREN. DO NOT EMPTY INTO DRAINS. IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL. AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS/SAFETY DATA SHEETS.																																																																																												
16. Other Information. Text of (R) phrases quoted in section 3 of the sheet. <table style="width: 100%; border: none;"> <tr> <td style="width: 15%; vertical-align: top;"> R 50/53 </td> <td style="width: 85%; vertical-align: top;"> VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. </td> </tr> </table> GENERAL BIBLIOGRAPHY 1. Directive 1999/45/EC and following amendments; 2. Directive 67/548/EEC and following amendments and adjustments (technical adjustment XXIX); 3. Regulation (EC) 1272/2008 (CLP) of the European Parliament; 4. Regulation (EC) 1907/2006 (REACH) of the European Parliament; 5. The Merck Index. - 10th Edition; 6. Handling Chemical Safety; 7. Niosh - Registry of Toxic Effects of Chemical Substances; 8. INRS - Fiche Toxicologique (toxicological sheet); 9. Patty - Industrial Hygiene and Toxicology; 10. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition; Note for users: The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product . This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.				R 50/53	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.																																																																																								
R 50/53	VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.																																																																																												