

01565-1175

-1224

MAIMERI S.p.A.		Revision nr.50 Dated 18/01/2010 Printed on 18/01/2010 Page n. 1 / 5
AUXILIARY PRODUCTS 58661 Strog solvent for restoration		
Safety Data Sheet		
1. Identification of the substance / preparation and the Company		
1.1 Identification of the substance or preparation		
Code:	58661	
Product name	AUXILIARY PRODUCTS	58661 Strog solvent for restoration
1.2 Use of the substance / preparation		
Intended use	Thinner for oil painting	
1.3 Company identification		
Name	MAIMERI S.p.A.	
Full address	Via Gianni Maimeri, 1	
District and Country	20060 Mediglia	(MI)
	Italia	
	Tel.	+39 02 906981
	Fax	+39 02 90698999
e-mail address of the competent person responsible for the Safety Data Sheet	schesedicurezza@maimerispa.it	
Product distribution by	MAIMERI S.P.A. VIA G.MAIMERI 1 20060 BETTOLINO DI MEDIGLIA (MI) ITALY	
1.4 Emergency telephone		
For urgent inquiries refer to	+39 02 906981	
2. Hazards Identification.		
2.1 Substance/Preparation Classification.		
This product is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments. Therefore, this product requires a safety data sheet according to the Regulation (EC) 1907/2006 and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.		
Danger Symbols:	F	
R phrases:	11-52/53-66	
2.2 Danger Identification.		
Because of its chemical-physical features, this product is graded as highly flammable (flash-point below 21 °C). HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.		
3. Composition / Information on Ingredients.		
Contains:		
Name.	Concentration % (C).	Classification.
1,2,4-Trimethylbenzene	0,35<= C <0,4	R 10
C.A.S. number	95-63-6	Xn R 20
EC number	202-436-9	Xi R 36/37/38
INDEX number	601-043-00-3	N R 51/53
Acetato di pentile	54<= C <58	R 10
C.A.S. number	628-63-7	R 66
EC number	211-047-3	Note C
INDEX number	607-130-00-2	




MSDS EPI 0601

MAIMERI S.p.A.		Revision nr.50 Dated 18/01/2010 Printed on 18/01/2010 Page n. 2 / 5	
AUXILIARY PRODUCTS		58661 Strog solvent for restoration	
Acetato di isopentile		4<= C <4,5	R 10 R 66 Note C
<i>C.A.S. number</i>	123-92-2		
<i>EC number</i>	204-662-3		
<i>INDEX number</i>	607-130-00-2		
Acetato di 2-metilbutile		25,5<= C <27	R 10 R 66 Note C
<i>C.A.S. number</i>	624-41-9		
<i>EC number</i>	210-843-8		
<i>INDEX number</i>	607-130-00-2		
NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY		8,5<= C <10	R 10 R 66 R 67 Xn R 65 N R 51/53 Note ?
<i>C.A.S. number</i>	64742-82-1		
<i>EC number</i>	265-185-4		
MESITYLENE		0,15<= C <0,2	R 10 R 37 N R 51/53
<i>C.A.S. number</i>	108-67-8		
<i>EC number</i>	203-604-4		
<i>INDEX number</i>	601-025-00-5		
The complete text of -R- phrases is specified in section 16.			
4. First aid measures.			
<p>EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.</p> <p>SKIN: Immediately wash with plenty of water. Remove all contaminated clothing. Obtain immediate medical attention. Wash contaminated clothing separately before using them again.</p> <p>INHALATION: Remove to open air. If breathing is irregular or stopped, administer artificial respiration. Obtain immediate medical attention.</p> <p>INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Give nothing by mouth to an unconscious person.</p>			
5. Fire-fighting measures.			
<p>GENERAL INFORMATION Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Excess pressure may form in containers exposed to fire at a risk of explosion. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water and the remains of the fire according to applicable regulations.</p> <p>SUITABLE EXTINGUISHING MEDIA The extinction equipment should contain carbon dioxide, foam or chemical powders. For product leaks and spills that have not caught fire, nebulised water can be used to dispel flammable fumes and protect the individuals taking part in stemming the leak.</p> <p>EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.</p> <p>HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc).</p> <p>SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Hardhat with visor, fireproof clothing (fireproof jacket and trousers with ties around arms, legs and waist) work gloves (fireproof, cut proof and dielectric), self-respirator (self-protector).</p>			
6. Accidental release measures.			
<p>PERSONAL PRECAUTIONS Use breathing equipment if fumes or powders are released into the air.</p> <p>ENVIRONMENTAL PRECAUTIONS The product must not penetrate the sewers, surface water, ground water and neighbouring areas.</p> <p>METHODS FOR CLEANING UP Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.</p>			


MSDS EPT 0801

MAIMERI S.p.A.		Revision nr.50 Dated 18/01/2010 Printed on 18/01/2010 Page n. 3 / 5
AUXILIARY PRODUCTS	58661 Strog solvent for restoration	
7. Handling and storage.		
Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity. Refer to the other sections of this data sheet for information relating to health and environmental risks.		
8. Exposure control / personal protection.		
8.1 Exposure limit values.		
Not available.		
8.2 Exposure controls.		
As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent.		
HAND PROTECTION		
Protect hands with category I (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in latex, PVC or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.		
SKIN PROTECTION		
Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.		
RESPIRATORY PROTECTION		
If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an AX or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).		
The use of breathing protection equipment, such as masks with organic vapour and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited.		
If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).		
EYE PROTECTION		
Use of protective airtight goggles (ref. standard EN 166) recommended.		
9. Physical and chemical properties.		
Colour	COLOURLESS	
Odour	TYPICAL	
Appearance	LIQUID	
Viscosity	Not available.	
Vapour density	Not available.	
Evaporation Rate	Not available.	
Reactive Properties	Not available.	
Partition coefficient: n-octanol/water	Not available.	
pH.	Not available.	
Boiling point.	Not available.	
Flash point.	< 21	*C.
Explosive properties.	Not available.	
Vapour pressure.	Not available.	
Specific gravity.	0,1	Kg/l
VOC (Directive 1999/13/EC) :	5,20 % - 50,94	g/litre of preparation.
VOC (volatile carbon) :	2,78 % - 27,27	g/litre of preparation.
10. Stability and reactivity.		
The product is stable in normal conditions of use and storage. When heated or in the event of a fire, carbon oxides may be released and vapours which are dangerous to health. The vapours may also form explosive mixtures with the air.		
Ethanol reacts violently with strong oxidizing agents.		

MSDS EPT 0001

MAIMERI S.p.A.		Revision nr.50 Dated 18/01/2010 Printed on 18/01/2010 Page n. 4 / 5	
AUXILIARY PRODUCTS		58661 Strog solvent for restoration	
11. Toxicological Information.			
This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.			
ETHANOL: oral LD50 (mg/kg) 1501 (RAT) ; inhalation LC50 (rat) 5,9 mg/l/6h.			
12. Ecological information.			
This product is dangerous for the environment and the aquatic organisms. In the long term, it may even have negative effects on aquatic environment.			
13. Disposal consideration.			
Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.			
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.			
CONTAMINATED PACKAGING			
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.			
14. Transport Information.			
These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations.			
These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.			
Road and rail transport:			
ADR/RID Class:	3	UN:	1263
Packing Group:	II		
Label:	3		
Nr. Kemler:	33		
Limited Quantity:	LQ06		
Tunnel restriction code:	(D/E)		
Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL		
Special Provision:	640D		
			
Carriage by sea (shipping):			
IMO Class:	3	UN:	1263
Packing Group:	II		
Label:	3		
EMS:	F-E	S-E	
Marine Pollutant:	NO		
Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL		
			
Transport by air:			
IATA:	3	UN:	1263
Packing Group:	II		
Label:	3		
Cargo:			
Packaging instructions:	307	Maximum quantity:	60 L
Pass.:			
Packaging instructions:	305	Maximum quantity:	5 L
Special Instructions:	A3, A72		
Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL		
			

MSDS EPT 0801

MAIMERI S.p.A.		Revision nr.50 Dated 18/01/2010 Printed on 18/01/2010 Page n. 5 / 5
AUXILIARY PRODUCTS		58661 Strog solvent for restoration
15. Regulatory information.		
		
HIGHLY FLAMMABLE		
R 11	HIGHLY FLAMMABLE.	
R 52/53	HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.	
R 66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.	
S 2	KEEP OUT OF THE REACH OF CHILDREN.	
S 9	KEEP CONTAINER IN A WELL-VENTILATED PLACE.	
S 16	KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.	
S 43	IN CASE OF FIRE, USE SAND, EARTH, POWDER, FOAM.	
S 46	IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL.	
<p>Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.</p> <p>Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 95/24/EC directive is respected.</p>		
16. Other information.		
Text of (R) phrases quoted in section 3 of the sheet.		
R 10	FLAMMABLE.	
R 20	HARMFUL BY INHALATION.	
R 36/37/38	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.	
R 37	IRRITATING TO RESPIRATORY SYSTEM.	
R 51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.	
R 65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.	
R 66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.	
R 67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.	
GENERAL BIBLIOGRAPHY		
<ol style="list-style-type: none"> 1. Directive 1999/45/EC and following amendments; 2. Directive 67/548/EEC and following amendments and adjustments (technical adjustment XXIX); 3. Regulation (EC) 1272/2008 (CLP) of the European Parliament; 4. Regulation (EC) 1907/2006 (REACH) of the European Parliament; 5. The Merck Index. - 10th Edition; 6. Handling Chemical Safety; 7. Niosh - Registry of Toxic Effects of Chemical Substances; 8. INRS - Fiche Toxicologique (toxicological sheet); 9. Patty - Industrial Hygiene and Toxicology; 10. N.I. Sax - Dangerous properties of Industrial Materials-7. 1989 Edition; 		
<p>Note for users:</p> <p>The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .</p> <p>This document must not be regarded as a guarantee on any specific product property.</p> <p>The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.</p>		

MSDS EPI 0601