

01565-1275

MAIMERI S.p.A.		Revision nr.34 Dated 18/01/2010 Printed on 18/01/2010 Page n. 1 / 6
AUXILIARY PRODUCTS		58682 Mastic varnish
Safety Data Sheet		
1. Identification of the substance / preparation and the Company		
1.1 Identification of the substance or preparation		
Code:	58682	
Product name	AUXILIARY PRODUCTS	58682 Mastic varnish
1.2 Use of the substance / preparation		
Intended use	Final varnish	
1.3 Company identification		
Name	MAIMERI S.p.A.	
Full address	Via Gianni Maimeri, 1	
District and Country	20060 Mediglia	(MI)
	Italia	
	Tel.	+39 02 906981
	Fax	+39 02 90698999
e-mail address of the competent person responsible for the Safety Data Sheet	schedesicurezza@maimerispa.it	
Product distribution by	MAIMERI S.P.A. VIA G.MAIMERI 1 20060 BETTOLINO DI MEDIGLIA (MI) ITALY	
1.4 Emergency telephone		
For urgent inquiries refer to	+39 02 906981	
2. Hazards Identification.		
2.1 Substance/Preparation Classification.		
This product is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments. Therefore, this product requires a safety data sheet according to the Regulation (EC) 1907/2006 and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.		
Danger Symbols:	Xn-N	
R phrases:	10-20/21/22-36/38-43-51/53-65	
2.2 Danger Identification.		
Because of its chemical-physical features, this product is graded as flammable (flash-point 21 °C or higher and 55 °C or lower). HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED. IRRITATING TO EYES AND SKIN. MAY CAUSE SENSITIZATION BY SKIN CONTACT. TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.		


MSDS EPT 0801

MAIMERI S.p.A.		Revision nr.34 Dated 18/01/2010 Printed on 18/01/2010 Page n. 2 / 6
AUXILIARY PRODUCTS	58682 Mastic varnish	
3. Composition / Information on Ingredients.		
Contains:		
Name.	Concentration % (C).	Classification.
TURPENTINE	66<= C <70	R 10
C.A.S. number	8006-64-2	Xn R 20/21/22
EC number	232-350-7	Xn R 65
INDEX number	650-002-00-6	Xi R 36/38
		Xi R 43
		N R 51/53
		Note 4
The complete text of -R- phrases is specified in section 16.		
4. First aid measures.		
EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.		
SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists, seek medical attention. Wash contaminated clothing before using them again.		
INHALATION: Remove to open air. If breathing is irregular, seek medical advice.		
INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.		
5. Fire-fighting measures.		
GENERAL INFORMATION		
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Excess pressure may form in containers exposed to fire at a risk of explosion. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water and the remains of the fire according to applicable regulations.		
SUITABLE EXTINGUISHING MEDIA		
The extinction equipment should contain carbon dioxide, foam or chemical powders. For product leaks and spills that have not caught fire, nebulised water can be used to dispel flammable fumes and protect the individuals taking part in stemming the leak.		
EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS		
Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.		
HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE		
Do not breathe the combustion products (carbon oxide, toxic pyrolysis products, etc).		
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS		
Hardhat with visor, fireproof clothing (fireproof jacket and trousers with ties around arms, legs and waist) work gloves (fireproof, cut proof and dielectric), self-respirator (self-protector).		
6. Accidental release measures.		
PERSONAL PRECAUTIONS		
Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. If there are no contraindications, spray solid products with water to prevent the formation of dust. Use breathing equipment if fumes or powders are released into the air. Block the leakage if there is no hazard. Do not handle damaged containers or the leaked product before donning appropriate protective gear. For information on risks for the environmental and health, respiratory tract protection, ventilation and personal protection equipment, see the other sections of this sheet.		
ENVIRONMENTAL PRECAUTIONS		
The product must not penetrate the sewers, surface water, ground water and neighbouring areas.		
METHODS FOR CLEANING UP		
Use inert absorbent material (sand, vermiculite, diatomaceous earth, Kieselguhr, etc.) to soak up leaked product. Collect the majority of the remaining material and deposit it in containers for disposal. If there are no contraindications, use jets of water to eliminate product residues. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.		






MSDS EPT 0801

MAIMERI S.p.A.		Revision nr.34 Dated 18/01/2010 Printed on 18/01/2010 Page n. 3 / 6	
AUXILIARY PRODUCTS		58682 Mastic varnish	
7. Handling and storage.			
Store in a well ventilated place, keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, bright flames and sparks and other sources of ignition.			
8. Exposure control / personal protection.			
8.1 Exposure limit values.			
Not available.			
8.2 Exposure controls.			
As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent. If such operations do not make it possible to keep the concentration of the product below the permitted workplace exposure thresholds a suitable respiratory tract protection must be used. See product label for hazard details during use. Ask your chemical substance suppliers for advice when choosing personal protection equipment. Personal protection equipment must comply with the rules in force indicated below.			
HAND PROTECTION			
Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitril or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.			
EYE PROTECTION			
Wear protective airtight goggles (ref. standard EN 166).			
SKIN PROTECTION			
Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.			
RESPIRATORY PROTECTION			
If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).			
The use of breathing protection equipment, such as masks with organic vapour and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited.			
If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).			
An emergency eye washing and shower system must be provided.			
In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.			
9. Physical and chemical properties.			
Colour		COLOURLESS	
Odour		WHITE SPIRIT	
Appearance		LIQUID	
Solubility		SOLUBLE IN WHITE SPIRIT	
Viscosity		Not available.	
Vapour density		Not available.	
Evaporation Rate		Not available.	
Reactive Properties		Not available.	
Partition coefficient: n-octanol/water		Not available.	
pH.		Not available.	
Boiling point.		Not available.	
Flash point.	>	21	°C.
Explosive properties.		Not available.	
Vapour pressure.		Not available.	
Specific gravity.		0,1	Kg/l
Solid content:		31,55 %	
VOC (Directive 1999/13/EC) :		68,45 %	- 684,51 g/litre of preparation.
VOC (volatile carbon) :		60,40 %	- 603,98 g/litre of preparation.

MSDS EPY 0801

MAIMERI S.p.A.		Revision nr.34 Dated 18/01/2010 Printed on 18/01/2010 Page n. 4 / 6																																
AUXILIARY PRODUCTS	58682 Mastic varnish																																	
10. Stability and reactivity.																																		
<p>The product is stable in normal conditions of use and storage. When heated or in the event of a fire, carbon oxides may be released and vapours which are dangerous to health. The vapours may also form explosive mixtures with the air.</p> <p>Mineral white spirits (oil of turpentine) reacts violently with strong oxidizing agents and chlorine. May ignite on contact with stannic chloride; it dissolves rubber.</p>																																		
11. Toxicological information.																																		
<p>Acute effects: inhalation, cutaneous absorption and ingestion of this product are harmful. This product may irritate mucosas, the upper respiratory tract, and eyes. Exposure symptoms may include: stinging and irritated eyes, mouth, nose, throat; cough, respiratory disorders, dizziness, headache, nausea and sickness.</p> <p>In the most serious cases, inhalation of this product may cause larynx and bronchial tube edema and irritation, chemical pneumonia and pulmonary edema. Upon contact with skin, this product may irritate it, causing an increase in skin temperature, swelling and itchiness. Ingestion of even small amounts of this product may cause serious health problems (stomach pain, nausea, sickness, diarrhoea).</p> <p>Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurries, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.</p> <p>The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.</p> <p>Turpentine: oral rat LD50 = 5760 mg/kg inhalation rat LD50 = 3950 ppm/1 hour 2150 ppm/6 hours.</p>																																		
12. Ecological information.																																		
<p>This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it may even have negative effects on aquatic environment.</p> <p>Petroleum distillates, charcoal, vegetable extracts: they are mixtures of paraffinic, naphthenic, diterpenic and aromatic hydrocarbons. Their behaviour on the environment depends on the concentration. In each case use, according to good working practices, avoiding disposal in the environment. As a rule, the product is poorly biodegradable.</p>																																		
13. Disposal consideration.																																		
<p>Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.</p> <p>Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.</p> <p>CONTAMINATED PACKAGING</p> <p>Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.</p>																																		
14. Transport information.																																		
<p>These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.</p> <p>Road and rail transport:</p> <table> <tr> <td>ADR/RID Class:</td> <td>3</td> <td>UN:</td> <td>1263</td> </tr> <tr> <td>Packing Group:</td> <td>III</td> <td></td> <td></td> </tr> <tr> <td>Label:</td> <td>3</td> <td></td> <td></td> </tr> <tr> <td>Nr. Kemler:</td> <td>30</td> <td></td> <td></td> </tr> <tr> <td>Limited Quantity:</td> <td>LQ07</td> <td></td> <td></td> </tr> <tr> <td>Tunnel restriction code:</td> <td>(D/E)</td> <td></td> <td></td> </tr> <tr> <td>Proper Shipping Name:</td> <td colspan="3">PAINT or PAINT RELATED MATERIAL (,TURPENTINE)</td> </tr> <tr> <td>Special Provision:</td> <td colspan="3">640E</td> </tr> </table> <div style="text-align: right; margin-top: 10px;">  </div>			ADR/RID Class:	3	UN:	1263	Packing Group:	III			Label:	3			Nr. Kemler:	30			Limited Quantity:	LQ07			Tunnel restriction code:	(D/E)			Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL (,TURPENTINE)			Special Provision:	640E		
ADR/RID Class:	3	UN:	1263																															
Packing Group:	III																																	
Label:	3																																	
Nr. Kemler:	30																																	
Limited Quantity:	LQ07																																	
Tunnel restriction code:	(D/E)																																	
Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL (,TURPENTINE)																																	
Special Provision:	640E																																	

MSDS EPT 0801

MAIMERI S.p.A.		Revision nr.34 Dated 18/01/2010 Printed on 18/01/2010 Page n. 5 / 6	
AUXILIARY PRODUCTS		58682 Mastic varnish	
Carriage by sea (shipping):			
IMO Class:	3	UN:	1263
Packing Group:	III		
Label:	3		 
EMS:	F-E	S-E	
Marine Pollutant:	YES		
Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL (TURPENTINE)		
Transport by air:			
IATA:	3	UN:	1263
Packing Group:	III		
Label:	3		
Cargo:			
Packaging instructions:	310	Maximum quantity:	220 L
Pass.:			
Packaging instructions:	309	Maximum quantity:	60 L
Special Instructions:	A3, A72		
Proper Shipping Name:	PAINT or PAINT RELATED MATERIAL		
15. Regulatory information.			
			
R 10	FLAMMABLE.		
R 20/21/22	HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.		
R 36/38	IRRITATING TO EYES AND SKIN.		
R 43	MAY CAUSE SENSITIZATION BY SKIN CONTACT.		
R 51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.		
R 65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.		
S 2	KEEP OUT OF THE REACH OF CHILDREN.		
S 29	DO NOT EMPTY INTO DRAINS.		
S 36/37	WEAR SUITABLE PROTECTIVE CLOTHING AND GLOVES.		
S 46	IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL.		
S 61	AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS/SAFETY DATA SHEETS.		
Contains:	TURPENTINE		
Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.			
Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.			
16. Other Information.			
Text of (R) phrases quoted in section 3 of the sheet.			
R 10	FLAMMABLE.		
R 20/21/22	HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.		
R 36/38	IRRITATING TO EYES AND SKIN.		
R 43	MAY CAUSE SENSITIZATION BY SKIN CONTACT.		
R 51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.		
R 65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.		
GENERAL BIBLIOGRAPHY			
1. Directive 1999/45/EC and following amendments;			

MAIMERI S.p.A.		Revision nr.34 Dated 18/01/2010 Printed on 18/01/2010 Page n. 6 / 6
AUXILIARY PRODUCTS	58682 Mastic varnish	
<p>2. Directive 67/548/EEC and following amendments and adjustments (technical adjustment XXIX);</p> <p>3. Regulation (EC) 1272/2008 (CLP) of the European Parliament;</p> <p>4. Regulation (EC) 1907/2006 (REACH) of the European Parliament;</p> <p>5. The Merck Index. - 10th Edition;</p> <p>6. Handling Chemical Safety;</p> <p>7. Niosh - Registry of Toxic Effects of Chemical Substances;</p> <p>8. INRS - Fiche Toxicologique (toxicological sheet);</p> <p>9. Patty - Industrial Hygiene and Toxicology;</p> <p>10. N.I. Sax - Dangerous properties of Industrial Materials-7. 1989 Edition;</p> <p>Note for users: The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product . This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.</p>		

MSDS EPY 0801