



Safety Data Sheet

CLASSIFICATION IN ACCORDANCE WITH CLP/GHS

TURPENTINE

Product Name

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier	TURPENTINE
1.2 Relevant identified uses of the substance or mixture and uses advised against	THINNER FOR OIL BASED COLOURS
1.3 Details of the supplier	DALER-ROWNEY LTD PEACOCK LANE BRACKNELL RG12 8SS ENGLAND Telephone: +44 (0) 1344 461000 tom.stagles@daler-rowney.com
E-mail contact :	
1.4 Emergency Telephone	+44(0)1344 461083 (Monday to Friday 08:00-16:00)

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification (EC) No1272/2008

Flammable liquids (Category 3) Acute toxicity, Inhalation (Category 4)
Acute toxicity, Dermal (Category 4) Acute toxicity, Oral (Category 4)
Aspiration hazard (Category 1) Eye irritation (Category 2)
Skin irritation (Category 2) Skin sensitization (Category 1)
Chronic aquatic toxicity (Category 2)
According to European Directive 67/548/EEC as amended.
Flammable. Harmful by inhalation, in contact with skin and if swallowed.
Harmful by inhalation, in contact with skin and if swallowed.
Harmful: may cause lung damage if swallowed. Irritating to eyes and skin.
May cause sensitization by skin contact. Toxic to aquatic organisms,
may cause long-term adverse effects in the aquatic environment

2.2 Classification (CHIP 4)

FLAMMABLE LIQUID
Hazard Symbol(s) Xn, N
R-phrases (s) R10; R20/21/22; R36/38; R43; R51/53; R65

2.3 Label Elements



2.4 Signal Word

DANGER



Safety Data Sheet

CLASSIFICATION IN ACCORDANCE WITH CLP/GHS TURPENTINE

Product Name

2.5 Hazard Statement

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects

2.6 Precautionary Statement

P101 If medical advice is needed, have product container or label at hand
P102 Keep out of reach of children
P280 Wear protective gloves/ protective clothing.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/
physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.

2.7 Supplemental information

Not applicable

2.8 Other hazard Information

Harmful if swallowed.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Chemical Name

Name	Cas-No	EC No	Index- No	Classification			Conc'n %
Turpentine	8006-64-2	232-350-7	650-002-00-6	Dgr	GHS02	H226 H302	
					GHS08	H304	
					GHS07	H312 H315 H317 H319	
					GHS09	H332 H411	

Xn; N; R10; R20/21/22; R36/38; R43; R51/53; R65

3.2 Further Information

Key to abbreviation, hazard statements are risk phrases in Section 16

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

Consult a physician. Show this safety data sheet to the doctor in attendance.



Safety Data Sheet

CLASSIFICATION IN ACCORDANCE WITH CLP/GHS TURPENTINE

Product Name

Inhalation

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Skin contact

Wash off with soap and plenty of water. Consult a physician.

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

Irritation to eyes, skin, upper respiratory system; headache, drowsiness, dizziness, nausea, vomiting, visual disturbance

4.3 Indication of immediate medical attention and special treatment needed

If swallowed, obtain immediate medical attention.

SECTION 5. FIRE-FIGHTING MEASURES

5.1 General Hazard

THE PRODUCT IS CLASIFIED AS FLAMABLE LIQUID

5.2 Extinguishing media

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water

5.3 Extinguishing media not to be used

5.4 Special hazards arising from the substance or mixture

No data available

5.5 Advice for Fire Fighters

Wear self contained breathing apparatus for fire fighting if necessary

5.6 Other information

Use water spray to cool unopened containers

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations

6.4 Reference to other sections



Safety Data Sheet

CLASSIFICATION IN ACCORDANCE WITH CLP/GHS

TURPENTINE

Product Name

Section 8 – personal protective measures
Section 13- disposal and waste

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.
Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end uses

Thinner for oil base colours

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components	CAS-No.	EC No	Value	Control parameters	Basis
Turpentine	8006-64-2	232-350-7	TWA (8 hours)	100 ppm 566 mg/m ³	UK. EH40 WEL - Workplace Exposure Limits
			STEL (15 min)	150 ppm 850 mg/m ³	UK. EH40 WEL - Workplace Exposure Limits

8.2 Exposure controls

Eye / face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Other

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Thermal hazards

8.3 Environmental exposure controls

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical form	Liquid
Colour	Colourless
Odour	Pungent



Safety Data Sheet

CLASSIFICATION IN ACCORDANCE WITH CLP/GHS TURPENTINE

Product Name

pH	No data available
Melting point	-55 °C
Boiling point	153 - 175 °C
Flash point	36 °C - closed cup
Ignition temperature	233 °C
Lower explosion limit	0.8 %(V)
Upper explosion limit	6 %(V)
Vapour pressure	5 hPa at 20 °C
Density	0.86 kg/l at 23 °C
Water solubility	Insoluble
VOC	0.866 kg/l

9.2 Other information

Miscible with organic solvent

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity

May soften oil or acrylic coatings

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Strong oxidizing agents

10.4 Conditions to Avoid

Heat, flames and sparks

10.5 Incompatible materials

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Nature of decomposition products not known.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Acute toxicity

LC50 Inhalation - rat - 6 h - 12,000 mg/m³

Remarks: Behavioral: Convulsions or effect on seizure threshold. Lungs, Thorax, or Respiration:Dyspnea.

11.2 Skin corrosion/irritation

Skin - rabbit - Severe skin irritation - Draize Test

11.3 Serious eye damage/irritation

Causes serious eye irritation

11.4 Respiratory or skin sensitisation

May cause allergic skin reaction

11.5 CMR effects

no data available

11.6 Other information

Harmful if inhaled. Causes respiratory tract irritation. Harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage. Harmful if absorbed through skin. Causes skin irritation. Causes serious eye irritation.



Safety Data Sheet
CLASSIFICATION IN ACCORDANCE WITH CLP/GHS
TURPENTINE

Product Name

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity	no data available
12.2 Persistence and degradability	no data available
12.3 Bioaccumulative potential	no data available
12.4. Mobility in soil	no data available
12.5. Results of PBT and vPvB assessment	no data available
12.6. Other adverse effects	Toxic to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

13.2 Contaminated packaging

Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

ADR/RID

UN-Number: 1299 Class: 3 Packing group: III
Proper shipping name: TURPENTINE

IMDG

UN-Number: 1299 Class: 3 Packing group: III EMS-No: F-E, S-E
Proper shipping name: TURPENTINE
Marine pollutant: No

IATA

UN-Number: 1299 Class: 3 Packing group: III
Proper shipping name: TURPENTINE

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the product

Classification, Labelling and packaging Regulation (EC) 1272/2008
Control of Major Accident Hazards Regulations 1999

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

SECTION 16. OTHER INFORMATION

16.1 Key to Hazard Statements In Section 3



Safety Data Sheet

CLASSIFICATION IN ACCORDANCE WITH CLP/GHS TURPENTINE

Product Name

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects

16.2 Key to Risk Phrases In Section 3

R 10 Flammable
R 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R36/38 Irritating to the eyes and skin.
R43 May cause sensitisation by skin contact
R51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.

This information is based on our present state of knowledge and is intended to describe our products from the point of view of the safety requirement. It should not be construed as guaranteeing specific properties
Data sheet prepared by Daler-Rowney/Technical department Prepared December 2010