

Art Noise Colours & Mediums

MSDS Preparation Date (mm/dd/yyyy): 07/22/2011

Page 1 of 7

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product identifier : Art Noise Colours & Mediums, UVFX Black Light Poster Colours

Product Code(s) : Not available.

Product Use : Water-based acrylic paint.

Chemical Family : Mixture.

Manufacturer's name and address: Supplier's name and address:

Tri-Art Manufacturing Inc. Refer to Manufacturer

4 Harvey Street Kingston, ON, Canada

K7K 5B9

Information Telephone # : (613) 541-0299 (9:00 AM to 5:PM EST)

24 Hr. Emergency Tel # : Not available

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS information: This product is not a WHMIS controlled product in Canada. It does not

meet any of the criteria for a controlled product provided in Part IV of the Controlled

Products Regulations (CPR).

OSHA: This material is classified as hazardous under OSHA regulations (29CFR

1910.1200). Hazardous classification: Acute Health Hazard.

Emergency Overview : White or coloured liquid. Mild ammonia odour. Caution! May cause mild transient

irritation. Ingestion of large amounts may be harmful.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation: None expected, when used as intended. If product is heated or mists are formed, inhalation may cause

irritation to the nose, throat and respiratory tract.

Skin : Direct skin contact may result in little or no irritation. Prolonged contact, may be more irritating.

Eyes : May cause mild transient irritation.

Ingestion: May cause irritation of mouth, throat, and stomach. Swallowing may cause irritation, nausea and vomiting.

Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache).

Effects of long-term (chronic) exposure

: None known or reported by the manufacturer.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS#	Wt.%		
Art Noise Colours and Mediums, UVF	K Black Light Poster Colours contain the fo	ollowing ingredients:		
Titanium dioxide	13463-67-7	5.00 - 10.00		
Propylene glycol	57-55-6	1.00 - 2.50		
Art Noise Black also contains the folio	owing component:	metron eng a mana kanan pripalaganga arang metropolis a sa mana asang a sana arang a sana a mana arang a sa ma P		
Carbon black	1333-86-4	1.50 - 2.50		

Item Numbers: 01640-1020, 01640-2020, 01640-3010, 01640-3160, 01640-3480, 01640-3770, 01640-4270, 01640-4270, 01640-4510, 01640-4530, 01640-4570, 01640-4650, 01640-5240, 01640-5240, 01640-5460, 0164



Art Noise Colours & Mediums

MSDS Preparation Date (mm/dd/yyyy): 07/22/2011

Page 2 of 7

SECTION 4 - FIRST AID MEASURES

Inhalation : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration.

If irritation or symptoms develop, seek medical attention.

Skin contact : Remove contaminated clothing and shoes. Wash off with soap and plenty of water. If irritation persists, seek prompt medical attention. Launder clothing before reuse.

Eye contact : Immediately flush eyes with running water for at least 5 to 10 minutes. If irritation persists,

seek prompt medical attention.

Ingestion : Do not induce vomiting. Never give anything by mouth if victim is unconscious. Consult a physician.

Notes For Physician : Treat symptomatically

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

 Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.1200)

: Non-flammable

Oxidizing properties : None known.

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

Suitable extinguishing media : Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams,

carbon dioxide and dry chemical.

Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire

area if safe to do so. Use water to cool fire-exposed containers.

Hazardous combustion products

Carbon oxides; Sulphur oxides; Nitrogen oxides (NOx); Other unidentified organic

compounds.

NFPA Rating 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious

: Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions : Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with the clean-up should wear the appropriate

chemically protective equipment. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If

necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural

waterway or drinking supply.

Spill response/cleanup : Remove all sources of ignition. Ventilate area of release. Stop the spill at source if it is safe

to do so. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product.

Notify the appropriate authorities as required.

Prohibited materials : None known or reported by the manufacturer.

Special spill response procedures

: If a spill/release in excess of the EPA reportable quantity is made into the environment,

immediately notify the national response center in the United States (phone:

1-800-424-8002).

US CERCLA Reportable quantity (RQ): None reported

SECTION 7 - HANDLING AND STORAGE

Safe Handling procedures : Wear appropriate protective equipment. Use with adequate ventilation. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling

Keep away from extreme heat and flame. Keep away from incompatibles. Keep



Art Noise Colours & Mediums

MSDS Preparation Date (mm/dd/yyyy): 07/22/2011

Page 3 of 7

Storage requirements : Store in a cool, dry, well ventilated area. Keep away from incompatibles. periodically for damage or leaks. Do not freeze. Recommended storage temperature: 0 - 30°C (32 - 86°F).

Incompatible materials Oxidizing agents; Reducing agents; Strong acids; Strong bases.

Special packaging materials : Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits						
g beginning kanina dar Makerawa jijar rejining mana mangtar ra arkant dara dalam persaktir lijanin tegip mana mma pangton	3	ACGIH TLV		OSHA PEL		
Ingredients	<u>TWA</u>	STEL	<u>PEL</u>	STEL		
Art Noise Colours and Mediu	ms. UVFX Black Light Poste	er Colours contain	n the following ingredients	innersystem – et sin i santi sant i tribi valgania jenesarja Silah angleggias (1917) -		
Fitanium dioxide	10 mg/m³	N/Av	15 mg/m³ (total dust)	N/Av		
Propylene glycol	10 mg/m³ (AIHA WEEL)	N/Av	N/Av	N/Av		
Art Noise Black also contains	s the following component:	ik ya o yikiki mekinnekinin) mikiki degi kemikiti yakilada inganifendeninyi ya Amedian yenir m	ak inera apangan ng ministrangga pamarrana kalanggapan na bandan piyan abangangan palipa sa kalanir	estilini esti est in minera meneral in in interior en en en en en estilit minera della esta esta esta esta est		
Carbon black	3.5 mg/m³	N/Av	3.5 mg/m³	N/Av		

Ventilation and engineering measures

: Use with adequate ventilation. General room ventilation is normally adequate.

In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be Respiratory protection

done wearing adequate respirator. Seek advice from respiratory protection specialists. Respirators should be selected based on the form and concentration of contaminants in air,

and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

None required under normal conditions. For prolonged skin exposure, gloves impervious to Skin protection

the material are recommended. Advice should be sought from glove suppliers.

Eye / face protection Safety goggles or glasses as appropriate for the job.

An eyewash station and safety shower should be made available in the immediate working Other protective equipment

area. Other equipment may be required depending on workplace standards.

General hygiene considerations

Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

liquid : White or coloured liquid. Physical state Appearance

Odour Mild ammonia odour. Odour threshold : N/Av

N/Ap pH

Boiling point 100 - 130°C : 1.0 - 1.2 Specific gravity (212 - 266°F)

Melting/Freezing point N/Av Coefficient of water/oil distribution

: N/Av

Vapour pressure (mmHg @ 20° C / 68° F) Solubility in water : Dilutable. : N/Av

Vapour density (Air = 1) N/Av Evaporation rate (n-Butyl acetate = 1)

· N/Av

Volatile organic Compounds (VOC's) Volatiles (% by weight) : N/Av

: N/Av

Flash point Non-flammable.

Flash point Method Auto-ignition temperature

Item Numbers: 01640-1020, 01640-2020, 01640-3010, 01640-3160, 01640-3480, 01640-3480, 01640-3770, 01640-4270, 01640-4270, 01640-4510, 01640-4530, 01640-4570, 0164 $5920,\,01640\text{-}6000,\,01640\text{-}6910,\,01640\text{-}7010,\,01640\text{-}7090,\,01640\text{-}7270,\,01640\text{-}8000,\,01640\text{-}9010,\,01640\text{-}9330$



Ingestion: YES

Art Noise Colours & Mediums

MSDS Preparation Date (mm/dd/yyyy): 07/22/2011

Page 4 of 7

Lower flammable limit (% by vol.)

Upper flammable limit (% by vol.)

N/Ap Flame Projection Length : N/Ap

: N/Ap Flashback observed : N/Ap

Section 10: Stability And Reactivity

Stability and reactivity

: Stable under the recommended storage and handling conditions prescribed.

Hazardous polymerization

Will not occur.

Conditions to avoid

Toxicological data

Avoid heat and open flame. Keep away from incompatibles. Keep container tightly closed when not in use.

Materials To Avoid And Incompatibility

: Incompatible materials (see Section 7).

Hazardous decomposition products
: None known, refer to hazardous combustion products in Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs : Eyes, skin, respiratory system and digestive system.

Routes of exposure : Inhalation; YES Skin Absorption: NO Skin & Eyes: YES

There is no available data for the product itself, only for the ingredients. See

below for individual ingredient acute toxicity data.

	LC50(4hr)	LD50		
<u>Ingredients</u>	inh, rat	(Oral, rat)	(Rabbit, dermal)	
Art Noise Colours and Med	iums, UVFX Black Light Poster	Colours contain the fol	lowing ingredients:	
Titanium dioxide	> 6820 mg/m³	> 25,000 mg/kg	> 10,000 mg/kg	
Propylene glycol	N/Av	21,800 mg/kg	20,800 mg/kg	
Art Noise Black also contai	ns the following component:		en francisco de la composición del composición de la composición del composición de la composición de la composición de la composición del composición de la composición de la composición del composición del composición del composición del composición del composici	
Carbon black	6750 mg/m³	> 15,400 mg/kg	> 3000 mg/kg	

Carcinogenic status

This product contains titanium dioxide, an IARC Group 2B carcinogen. However, the Titanium dioxide used in this product is in a non-respirable form and under normal conditions of use, Titanium dioxide cannot become airbourne. The carcinogenic effects of

Titanium dioxide are therefore not applicable to this product.

Art Noise Black also contains Carbon black, an IARC 2B carcinogen. However, the Carbon black used in this product is in a non-respirable form and under normal conditions of use, Carbon black cannot become airbourne. The carcinogenic effects of Carbon black are

therefore not applicable to this product.

Reproductive effects

Not expected to have other reproductive effects.

Teratogenicity

Not expected to be a teratogen.

Mutagenicity

Not expected to be mutagenic in humans. Art Noise Black contains Carbon black. Carbon black is suspected of causing mutations in non-reproductive cells, based on animal

data. However, the Carbon black used in this product is in a non-respirable form and under normal conditions of use, Carbon black cannot become airbourne. The mutagenic effects

of Carbon black are therefore not applicable to this product.

Epidemiology

Not available

Sensitization to material

Not expected to be a skin or respiratory sensitizer.

Synergistic materials Irritancy

Not available. Slightly irritating

other important hazards

CNS depression may result from extreme exposures.

Conditions aggravated by overexposure

: Pre-existing skin and respiratory disorders.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity : No data is available on the product itself. The product should not be allowed to enter drains



Art Noise Colours & Mediums

MSDS Preparation Date (mm/dd/yyyy): 07/22/2011

Page 5 of 7

Mobility : No data is available on the product itself. Persistence : No data is available on the product itself. Bioaccumulation potential : No data is available on the product itself. Other Adverse Environmental effects

: No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle waste according to recommendations in Section 7.

Methods of Disposal

Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

RCRA

If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14: TRANPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label	
TDG	None	Not regulated.	Not regulated	none	\otimes	
TDG Additional information	None.					
49CFR/DOT	None	Not regulated.	Not regulated	none		
49CFR/DOT Additional information	None.					

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Immediate (Acute) health hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: Art Noise Black contains Carbon black. Carbon black is known by the state of California to cause However, Carbon black is listed when found in unbound, airborne particles of respirable size.

Other U.S. State "Right to Know" Lists: The following chemicals are specifically listed by individual States: titanium dioxide (MA, MN, NJ, PA, RI); Propylene glycol (MN, NJ, PA, RI); Carbon black (CA, MA, MN, NJ, PA, RI).



Art Noise Colours & Mediums

MSDS Preparation Date (mm/dd/yyyy): 07/22/2011

Page 6 of 7

International Information:

Canadian WHMIS Classification: Refer to Section 2 for a WHMIS Classification for this product.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16 - OTHER INFORMATION

3 - Serious *- Chronic hazard 1 - Slight 0 - Minimal 2 - Moderate **HMIS Rating**

Health: Flammability: Reactivity: O

ACGIH: American Conference of Governmental Industrial Hygienists Leaend

AIHA: American Industrial Hygiene Association

CA: California CAS: Chemica

Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of

1980

CFR: Code of Federal Regulations CNS: Central Nervous System DOT: Department of Transportation EPA: **Environmental Protection Agency**

EST: Eastern Standard Time

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank IARC: International Agency for Research on Cancer

Inhalation

IUCLID: International Uniform Chemical Information Database

LC: Lethal Concentration LD: Lethal Dose MA: Massachusetts MN: Minnesota N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NJ: New Jersey NTP: National Toxicology Program OSHA: Occupational Safety and Health Administration

PA: Pennsylvania
PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act

RI: Rhode Island

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TWA: Time Weighted Average WEEL: Workplace Environment

Workplace Environmental Exposure Level

WHMIS: Workplace Hazardous Materials Identification System

References

1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2011.

2. International Agency for Research on Cancer Monographs, searched 2011.

3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2011

(Chempendium, HSDB, RTECs).

4. Material Safety Data Sheet from manufacturer.5. US EPA Title III List of Lists - October 2006 version.

6. California Proposition 65 List - May 20, 2011 version.



Art Noise Colours & Mediums

MSDS Preparation Date (mm/dd/yyyy): 07/22/2011

Page 7 of 7

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by Tri-Art Manufacturing and obtained from supplier information. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Tri-Art Manufacturing Inc. disclaims all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Tri-Art Manufacturing Inc.

Tri-Art Manufacturing Inc. 4 Harvey Street Kingston, ON, Canada, K7K 5B9 Telephone: (613) 541-0299 Please direct all enquiries to Tri-Art Manufacturing.