

<b>02102-2573 -2574 -3013 -3014</b>
<b>-3513 -3514 -4013 -4014 -5013</b>
<b>-5014</b>

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH)

Version 3.1 (25/05/2010) - Page 1/6

Name: Huile fine XL Glacis toutes couleurs / XL oil glaze all colours Compo 2014 PEPEO ARTIST COLORS (KUNSHAN) Co. LTD

## SAFETY DATA SHEET

### 1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Identification of the substance or preparation:**

Name: Huile fine XL Glacis toutes couleurs / XL oil glaze all colours.  
Product code: 200402.

**Company/undertaking identification:**

Registered company name: PEPEO ARTIST COLORS (KUNSHAN) Co. LTD.  
Address: 19 Jin Sha Jiang road, JIANG SU Province.215300.KUNSHAN.PRC.  
Telephone: 86 (0) 512 577 17 092. Fax: 86 (0) 512 577 17 096.  
cdeedeyne@pebeo.com  
www.pebeo.com

Emergency telephone: 33 (0)1.45.42.59.59.

Association/Organisation: INRS / ORFILA <http://www.centres-antipoison.net>.

**Use of the substance/preparation:**

Paints & Varnishes for artists

### 2 - HAZARDS IDENTIFICATION

This product is not classified as flammable. Refer to the recommendations regarding the other products present on the site  
This preparation is not classified as hazardous to health by directive 1999/45/EC.

### 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Full text of risk phrases appearing in section 3: see section 16.

**Hazardous substances present on their own:**

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

This preparation contains no hazardous substance in this category.

**Other substances representing a hazard:**

No known substance in this category present.

**Substances present at a concentration below the minimum danger threshold:**

INDEX 603-108-00-1 CAS 78-83-1 CE 201-148-0 2-METHYLPROPAN-1-OL | Concentration >=1.00% and <2.50%.  
Symbol: Xi R: 10-37/38-41-67

**Other substances with occupational exposure limits:**

No known substance in this category present.

**Other components:**

DISTILLAT MOYEN (PETROLE) HYDROTRAITÉ | Concentration >=25.00% and <50.00%. Symbol: Xn R: 65  
INDEX 649-327-00-6 CAS 64742-48-9 CE 265-150-3 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY |  
Concentration >=0.00% and <1.00%. Symbol: Xn R: 65  
INDEX 649-356-00-4 CAS 64742-95-6 CE 265-199-0 SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. |  
Concentration >=0.00% and <1.00%. Symbol: Xn R: 65

### 4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

**In the event of exposure by inhalation:**

If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.

**In the event of splashes or contact with eyes:**

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH) Version 3.1 (25/05/2010) - Page 2/6  
 Name: Huile fine XL Glacis toutes couleurs / XL oil glaze all colours / 200402 PEBO ARTIST COLORS (KUNSHAN) Co. LTD

**In the event of splashes or contact with skin:**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.  
 DO NOT use solvents or thinners.

**In the event of swallowing:**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.  
 If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

**5 - FIRE-FIGHTING MEASURES**

Not relevant.

**6 - ACCIDENTAL RELEASE MEASURES**

**Personal precautions:**

Consult the safety measures listed under headings 7 and 8.

**Environmental precautions:**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.  
 Prevent any material from entering drains or waterways.

**Methods for cleaning up:**

Clean preferably with a detergent, do not use solvents.

**7 - HANDLING AND STORAGE**

The regulations relating to storage premises apply to workshops where the product is handled.

**Handling:**

Handle in well-ventilated areas.

**Fire prevention:**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures:**

Packages which have been opened must be reclosed carefully and stored in an upright position

**Storage:**

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

**8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**



Use personal protection equipment as per Directive 89/686/EEC.

**Technical measures:**

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.

Personnel shall wear regularly laundered overalls.

If this ventilation is insufficient to maintain the concentration of solvent vapors below the exposure limits, wear breathing apparatus

**Exposure limit values per INRS ED 984:**

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N°:
78-83-1	50	150	-	-	-	84
Germany	Class:	MAK-ppm:	MAK-mg/m3:	Notes:	Notes:	
78-83-1	II.1	100	310	C		
ACGIH(TLV)	TWA-ppm:	TWA-mg/m3:	STEL-ppm:	STEL-mg/m3:	Notes:	Notes:
78-83-1	50	152	-	-	-	-

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH) Version 3.1 (25/05/2010) - Page 3/6  
 Name: Huile fine XL Glacis toutes couleurs / XL oil glaze all colours Component 201902 PEBEO ARTIST COLORS (KUNSHAN) Co. LTD

**Exposure limit values (2003-2006):**

Country/Region	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Temps:	RSB:
Switzerland	150	50	150	50	15 min	-
South Africa-DOL RL		TWA:	STEL:	Ceiling:	Definition:	Criterion:
78-83-1	50 ppm	75 ppm	-	-	-	-
Canada-Quebec	TWA:	STEL:	Ceiling:	Definition:	Criteria:	
78-83-1	50 ppm	-	-	-	-	-
New Zealand	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Mexico	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	75 ppm	-	-	-	-
Malaysia	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Canada-British Columbia	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Brazil	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	40 ppm	-	-	-	-	-
Canada-Alberta	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Australia	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Germany/AGW	AGW:	AGW:	Faktor:	Bemerkungen:		
78-83-1	100 ml/m3	310 mg/m3	1(I)	DFG, Y		
Denmark(3.4/3.4.1)	TWA:	STEL:	Anm:	TWA:	STEL:	Anm:
78-83-1	50 ppm	150 mg/m3	LH	50 ppm		LH
Slovakia	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	100 ppm	310 mg/m3	-	-	-	-
UK/WELs	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	75 ppm	-	-	-	-
Ireland	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	75 ppm	-	-	-	-
Hong Kong	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Czech Rep.	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	300 mg/m3	600 mg/m3	-	-	-	-
ACGIH/TLV	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Germany/MAK	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	100 ppm	100 ppm	-	-	-	-
Germany/TRK	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	100 ppm	310 mg/m3	=1=	Y DFG	-	-
UK/OES	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	75 ppm	-	-	-	-
Japan/JSOH	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Nederland	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Belgique	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-
Polska	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
64742-48-9	300 mg/m3	900 mg/m3	-	-	-	-
78-83-1	100 mg/m3	200 mg/m3	-	-	-	-
España	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
78-83-1	50 ppm	-	-	-	-	-

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH)

Version 3.1 (25/05/2010) - Page 4/6

Name: Huile fine XL Glacis toutes couleurs / XL oil glaze all colours - COMPAGNIE BEBEO ARTIST COLORS (KUNSHAN) Co. LTD

USA/NIOSH REL	TWA:	STEL:	Ceiling:	Definition:	Criterion:
78-83-1	50 ppm	-	-	-	-
USA/NIOSH IDLH	TWA:	STEL:	Ceiling:	Definition:	Criterion:
78-83-1	-	-	1600 ppm	-	-
USA/OSHA PEL	TWA:	STEL:	Ceiling:	Definition:	Criterion:
78-83-1	100 ppm	-	-	-	-

**Respiratory protection:**

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.

Anti-gas filters :

- A1,A2,A3 (brown)

**Hand protection:**

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

In the event of prolonged or repeated contact with the hands, use appropriate gloves.

Type of gloves recommended :

- Nitrile
- PVA (polyvinylalcohol)

**Eye and face protection:**

Use eye protectors designed to protect against liquid splashes

**9 - PHYSICAL AND CHEMICAL PROPERTIES****General information:**

Physical state: viscous liquid

**Important health, safety and environmental information:**

pH of the substance or preparation: not relevant.

The pH is impossible to measure or its value is not relevant.

Boiling point/boiling range: 180 °C.

Flash point interval: Flash point > 60°C

Flash point: 67.50 °C.

Vapour pressure: Below 110 kPa (1.10 bar).

Density: < 1

Water solubility: Insoluble.

**Other information:**

melting point/melting range: not relevant.

Self-ignition temperature: not relevant.

Decomposition point/decomposition range : not relevant.

VOC (g/l): 37.33

**10 - STABILITY AND REACTIVITY**

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide

**11 - TOXICOLOGICAL INFORMATION**

No data is available regarding the preparation itself.

Exposure to vapors from solvents contained in the preparation beyond the exposure limits stated may produce effects harmful to health, such as:

Irritation of mucous membrane and respiratory system, kidneys, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic dermatitis on contact and absorption through the epidermis.

Splashes in the eyes may cause irritation and reversible damage

**Other data:**

CAS 7631-86-9 : IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH) Version 3.1 (25/05/2010) - Page 5/6  
 Name: Huile fine XL Glacis toutes couleurs / XL oil glaze all colours Company: PEBO ARTIST COLORS (KUNSHAN) Co. LTD

## 12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

## 13 - DISPOSAL CONSIDERATIONS

Do not pour into drains or waterways.

### Waste:

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

08 01 11 \* waste paint and varnish containing organic solvents or other dangerous substances

## 14 - TRANSPORT INFORMATION

Exempt from transport classification and labelling.

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2009 - IMDG 2008 - ICAO/IATA 2009).

## 15 - REGULATORY INFORMATION

### Classification by:

So called 'all preparations' Directive 1999/45/EC and its adaptations.


EC regulation 1272/2008 (CLP) and its adaptations (EC regulation 790/2009).

### Particular hazards associated with the preparation and safety recommendations:

S 2	Keep out of the reach of children.
S 23	Do not breathe vapour
S 24	Avoid contact with skin.
S 62	If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

### Particular provisions:

NFPA 704 Label: Health=0 Flammability=2 Instability=1 Special Hazards=none



## 16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

### Full text of risk phrases appearing in section 3:

R 10	Flammable.
R 37/38	Irritating to respiratory system and skin.
R 41	Risk of serious damage to eyes.
R 65	Harmful: may cause lung damage if swallowed.

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH) Version 3.1 (25/05/2010) - Page 6/6  
 Name: Huile fine XL Glacis toutes couleurs / XL oil glaze all colours ~~Compa 401~~ PEBEO ARTIST COLORS (KUNSHAN) Co. LTD

R 67

Vapours may cause drowsiness and dizziness.

### Difference Report

Revision: N°3 (25/05/2010) / Version: N°1 (25/05/2010)

~~Revision: N°2 (16/03/2009) / Version: N°2 (09/06/2009)~~

### 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Other components:

~~INDEX 649 221 00 X CAS 64742 46 7 CE 265 148 2 DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE |~~  
~~Concentration >=25.00% and <50.00%. Symbol: R-~~

DISTILLAT MOYEN (PETROLE) HYDROTRAITÉ | Concentration &gt;=25.00% and &lt;50.00%. Symbol: Xn R: 65

### 9 - PHYSICAL AND CHEMICAL PROPERTIES

Important health, safety and environmental information:

<del>Flash point:</del>	<del>101.00 °C.</del>
Flash point:	67.50 °C.
Other information:	
<del>VOC (g/l):</del>	<del>31.77</del>
melting point/melting range:	not relevant.
Self-ignition temperature:	not relevant.
Decomposition point/decomposition range :	not relevant.
VOC (g/l):	37.33

### 11 - TOXICOLOGICAL INFORMATION

Other data:

CAS 7631-86-9 : IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.


### 15 - REGULATORY INFORMATION

~~This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations~~  
~~In addition directive 2008/58/EC with the 30<sup>th</sup> adaptation of directive 67/548/EEC (Hazardous substances) has been taken into~~  
~~account.~~

~~This preparation is not classified as hazardous to health by directive 1999/45/EC.~~

~~This product is not classified as flammable.~~

Particular provisions:

NFPA 704 Label: ~~Health=0 Flammability=1 Instability=1 Special Hazards=none~~

Classification by:

So called 'all preparations' Directive 1999/45/EC and its adaptations.

EC regulation 1272/2008 (CLP) and its adaptations (EC regulation 790/2009).

NFPA 704 Label: Health=0 Flammability=2 Instability=1 Special Hazards=none

