

MANUFACTURED BY: Tara Materials, Inc.
 322 Industrial Park Drive
 Lawrenceville, GA 30045

SECTION 2. COMPOSITION INFORMATION ON HAZARDOUS INGREDIENTS

COMPONENT	%WT	CAS NO.	OSHA PEL	ACGIH TLV
Titanium Dioxide	15 - 25	13463-67-7	15 mg/m ³	
Calcium Carbonate	50 - 60	471-34-1	10 mg/m ³	
Linseed Oil	10 - 15	68649-95-6	N / A	
2-[(Hydroxymethyl)-Amino]-Ethanol	0.01	34375-28-5	100	
Mineral Spirits	5 - 10	8052-41-3		

SECTION 3. HAZARDS IDENTIFICATION

DESCRIPTION: This product presents hazards from inhalation, eye contact, skin contact, and ingestion. Its flash point also presents a potential fire hazard if ambient temperatures approach or exceed 100° F. This material may also accumulate static charges which can cause an incendiary electrical discharge.

POTENTIAL HEALTH EFFECTS:

Inhalation: High vapor concentrations are irritating to the eyes and respiratory tract. This could result in a burning sensation in the eyes, headaches, dizziness, nausea, drowsiness, and progressive effects on the central nervous system up to and including death.

Ingestion: Small amounts of this material aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly even death. Minimal toxicity.

Eye Contact: Slightly to moderately irritating. Not likely to cause permanent injury.

Skin Contact: Slightly to moderately irritating. May cause redness, rash, and swelling. Not likely to cause permanent injury.

SECTION 4. FIRST AID MEASURES

other items. **CAUTION:** Clothing or rags soaked with this material may be prone to spontaneous combustion.

INGESTION: If swallowed DO NOT induce vomiting. For very small amounts drink one or two glasses of water. For larger amounts monitor victim. Seek medical assistance if symptoms or circumstances warrant. NEVER give an unconscious person anything by mouth.

SECTION 5. FIRE FIGHTING MEASURES

FLASH POINT: 104° F.

EXPLOSIVE LIMITS: LEL = 0.7% UEL = 5.5%

HAZARDOUS COMBUSTION PRODUCTS: Typical products of combustion from organic solvents and oils. May also produce an irritating smoke due to entrained pigment and filler particles.

AUTOIGNITION TEMPERATURE: Approximately 500° F.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition. For small quantities, provide good ventilation and implement clean up procedures. For larger spills, control spread of material and remove all persons not involved in the control and clean up activities from the area. Prevent material from entering drains, sewers, watercourses, or other areas not designed for hazardous liquids. **CAUTION:** Towels or rags soaked with this material are capable of spontaneous combustion. Recover by pumping if appropriate or use only inert absorbent materials for clean up. NEVER use organic absorbents, sawdust, etc. Prevent contact with strong bleach or other oxidizers, or acids. Follow all local, state, and Federal regulations when disposing of any recovered or waste material.

SECTION 7. HANDLING AND STORING

Keep away from heat and open flame. Store at ambient temperatures. Keep in mind the electrostatic discharge potential when mixing, handling, or transferring this material.

EYE PROTECTION: Safety glasses with side shields recommended.

SKIN PROTECTION: Disposable rubber gloves as a minimum if skin contact is likely.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Strong aromatic odor due to linseed oil and solvent

PHYSICAL STATE: Liquid / solid mixture **BOILING POINT:** > 300° F

pH: N/A **MELTING POINT:** N/A

VAPOR PRESSURE: ~1.5 mmHg @70° F **SOLUBILITY IN WATER:** Very low to insoluble

-VAPOR DENSITY: Heavier than air **SPECIFIC GRAVITY:** > 2

SECTION 10. STABILITY AND REACTIVITY

STABILITY: Stable at ambient conditions. As temperatures increase, so does the potential for exothermic reaction as well as build up of pressure in closed containers.

CONDITIONS TO AVOID: High temperatures, fire and other sources of ignition.

INCOMPATIBILITY, MATERIALS TO AVOID: Bleach and other oxidizers. Acids, especially mineral acids. Do not mix with dirt, sawdust, or other organic materials.

HAZARDOUS COMBUSTION PRODUCTS: None other than those generally associated with combustion of organics.

HAZARDOUS POLYMERIZATION: May occur if mixed with other organic materials.

SECTION 12. DISPOSAL CONSIDERATIONS

Follow all local, state, and Federal regulations when disposing of this material in either liquid or dry form. Do not pour into drains, sewers, waterways, etc.

SECTION 13. TRANSPORTATION INFORMATION

This product as packaged meets the criteria of a "consumer commodity" under 49 CFR 171.8 and related sections. As a result it is not regulated for ground transportation.

SECTION 14. REGULATORY INFORMATION

This product complies with ASTM d4236 and the Labeling of Hazardous Air Materials (LHAMA) regulations.

Warning: This product may contain trace quantities of antimony, chromium, lead, and crystalline silica; chemicals known to the State of California to cause cancer or reproductive toxicity.

This product has been evaluated under LHAMA regulations and conforms to the standards of ASTM D4236.

SECTION 15. MISCELLANEOUS INFORMATION

This MSDS was prepared based on the best available information from vendors, health and safety, and transportation regulations.

Date prepared: 5/1/06
Prepared by: R. January
Revised: May, 2010