

08925-1000

REVISION DATE: 01/07/08

**SAFETY DATA SHEET
WINSOR & NEWTON OIL PAINTING PRIMER****1 IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND COMPANY UNDERTAKING**

PRODUCT NAME WINSOR & NEWTON OIL PAINTING PRIMER

APPLICATION Oil primer for art and creative use

SUPPLIER ColArt America Inc.
11 Constitution Avenue
Piscataway
New Jersey
08855-1396Emergency telephone number 1-800-628-3385
Tel. number for information 732-562-0770**2. COMPOSITION INFORMATION ON INGREDIENTS**

COMPOSITION COMMENTS:

Hazardous Components	CAS Number	OSHA PEL	TLV
Petroleum hydrocarbons	64742-82-1	No data	No data
2-butanone oxime	96-29-7	No data	No data

3. HAZARD IDENTIFICATION

CLASSIFICATION

In accordance with ASTM D-4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Effects this product labeled as:

WARNING: MAY BE HARMFUL BY BREATHING VAPORS. OVEREXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. CONTAINS PETROLEUM DISTILLATES. Avoid breathing vapors. Use extraction fan to ensure adequate cross ventilation.

KEEP OUT OF REACH OF CHILDREN

4. FIRST AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort

1

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get prompt medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lid. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES**EXTINGUISHING MEDIA**

Fire can be extinguished using foam, dry chemicals, sand, dolomite etc.

6. ACCIDENTAL RELEASE MEASURES**SPILL CLEAN UP METHODS**

Ventilate well. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place in to containers. Do not contaminate water courses or sewer. Dispose of the colour in accordance with local regulations.

7. HANDLING AND STORAGE**USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapors.

STORAGE PRECAUTIONS

Keep in original container. Store at moderate temperatures in dry, well ventilated area.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION**ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

HAND PROTECTION

Use suitable protective gloves if risk of skin contamination.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

HYGEINE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Paste
COLOR	White
ODOR	Hydrocarbon
SOLUBILITY	Insoluble in water
BOILING POINT (°C)	> 200 760 mm Hg
RELATIVE DENSITY	1.5
VOLATILE BY VOL (%)	25
FLASH POINT (°C)	42 (Closed cup)
FLAMMABLE LIMITS	LEL = 0.9; UEL = 6.0
pH-VALUE CONC. SOL .	Not applicable

10. STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with acids and oxidizing substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire generates fumes of carbon dioxide and carbon monoxide.

11. TOXICOLOGICAL INFORMATION**GENERAL INFORMATION****INHALATION**

Prolonged inhalation of high concentrations may damage respiratory system.

INGESTION

May cause discomfort if swallowed

SKIN CONTACT

Acts as a defatting agent. May cause cracking of skin and eczema. Prolonged contact may cause irritation..

EYE CONTACT

Spray and vapor in the eyes may cause irritation and smarting.

ROUTE OF ENTRY

Inhalation. Skin and eye contact.

MEDICAL SYMPTOMS

Inhalation of large quantities of vapor may cause dizziness, headache. Prolonged contact with skin may cause irritation.

12. ECOLOGICAL INFORMATION**ECOTOXICITY**

This product is insoluble in water.

13. DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION

PROPER SHIPPING NAME	PAINT RELATED MATERIAL		
UN NO. ROAD	1263	ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids	ADR pack group	III
ADR label number	3		
RID CLASS NO.	3	RID pack group	III
UN NO. SEA	1263	IMDG CLASS	3
IMDG PACK GROUP	III		
UN NO. AIR	1263	AIR CLASS	3
AIR PACK GROUP	III		

15. REGULATORY INFORMATION

This product has been evaluated by a toxicologist and is labeled for acute and chronic health hazards in accordance with the Labeling of Hazardous Art Materials Act and Federal regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act.

This product conforms to ASTM D 4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Hazards. The warning given on the product label is:

In accordance with ASTM D-4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Effects this product labeled as:

WARNING: MAY BE HARMFUL BY BREATHING VAPORS. OVEREXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. CONTAINS PETROLEUM DISTILLATES. Avoid breathing vapors. Use extraction fan to ensure adequate cross ventilation.

KEEP OUT OF REACH OF CHILDREN

16. OTHER INFORMATION

INFORMATION SOURCE

Material Safety ~Data Sheet, Misc. manufacturers.

REVISION DATE
01/07/08