

**PLASKOLITE, INC.**  
1770 Joyce Avenue  
Columbus, OH 43219

**EMERGENCY HOTLINE:**  
(614) 294-3281

18908-XXXX

**MATERIAL SAFETY DATA SHEET**

**1. PRODUCT IDENTIFICATION**

**Material:** Plaskolite Polystyrene Plastic  
(includes Polystyrene (PS) Sheet, Run-to-Size Polystyrene Sheet,  
Patterned Styrene Sheet, Styrene Lighting Sheet)

**Chemical Name  
or Synonyms:** Polystyrene

**2. PRODUCT COMPONENTS**

<u>COMPONENTS</u>	<u>CAS REG. NO.</u>	<u>WEIGHT (%)</u>
1. Polystyrene (PS)	9003-53-6	100

**3. PHYSICAL PROPERTIES**

**Appearance:** Clear to opaque solid  
**Odor:** N/A  
**Viscosity:** N/A  
**Melting Point:** 104°C/220°F  
**Boiling Point:** N/A  
**Vapor Pressure:** N/A  
**Vapor Density:** N/A (Air =1)  
**Specific Gravity:** 1.05 (Water =1)  
**pH:** N/A  
**Solubility in Water:** Negligible  
**Volatility:** Negligible (Weight %)  
**Evaporation Rate:** Negligible (Butyl Acetate = 1)

**4. FIRE AND EXPLOSION HAZARD INFORMATION**

**Flash Point:** 340°C/650°F  
**Auto Ignition Temperature:** 490°C/910°F  
**Upper Explosion Limit (%):** N/A  
**Lower Explosion Limit (%):** N/A  
**Extinguishing Media:** Carbon dioxide, dry chemical, or water.  
**Fire Protection Equipment:** Wear self-contained, positive pressure breathing apparatus  
(MSHA/NIOSH approved, or equivalent) and full protective gear.

**Unusual Fire and  
Explosion Hazard:** Product is combustible thermoplastic material that burns  
vigorously with intense heat.

**Date Issued:** 1/4/2000  
**Date Revised:** 8/27/2012

Page 1 of 5

**PLASKOLITE, INC.**  
1770 Joyce Avenue  
Columbus, OH 43219

**EMERGENCY HOTLINE:**  
(614) 294-3281

#### **5. WORKPLACE EXPOSURE LIMITS**

<u>COMPONENTS</u>	<u>OSHA</u>		<u>ACGIH</u>	
	<u>PEL</u>	<u>STEL</u>	<u>TLV</u>	<u>STEL</u>
1. PS	None	None	None	None
2. Nuisance dusts (as inhalable particles not otherwise specified)	5 mg/m <sup>3</sup>	None	10 mg/m <sup>3</sup>	None

#### **6. HAZARD INFORMATION**

Hazard Scale: 0 = Insignificant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme

Health Designation: 0  
Fire Designation: 1  
Reactivity Designation: 0

Inhalation: Inhalation of vapors from heated product can cause nausea, headache, dizziness as well as irritation of lungs, nose, and throat.  
Eye Contact: Vapors from heated product can irritate the eyes.  
Ingestion: Low hazard associated with normal conditions.  
Skin Contact: Possible skin irritation. Contact with molten material can result in burns.  
Carcinogenicity: N/A

#### **7. EMERGENCY AND FIRST AID PROCEDURES**

Inhalation: Move subject to fresh air.  
Eye Contact: Flush eyes with plenty of water for at least 15 minutes. Call a physician.  
Ingestion: This material is not expected to be absorbed within the gastrointestinal tract, so induction of vomiting should not be necessary.  
Skin Contact: If molten material contacts skin, cool rapidly with cold water and obtain medical attention for thermal burn.

#### **8. REACTIVITY INFORMATION**

Stability: Stable  
Conditions to Avoid: None  
Hazardous Decomposition Products: Thermal decomposition or combustion may emit vapors,

Date Issued: 1/4/2000  
Date Revised: 8/27/2012

Page 2 of 5

**PLASKOLITE, INC.**  
1770 Joyce Avenue  
Columbus, OH 43219

**EMERGENCY HOTLINE:**  
(614) 294-3281

Incompatible Compounds: carbon monoxide, or carbon dioxide.  
N/A

#### **9. SPILL OR LEAK INFORMATION**

Sweep or scoop up and remove.

#### **10. WASTE DISPOSAL**

Landfill or incinerate at a facility that complies with local, state and federal regulations.

#### **11. EXPOSURE CONTROLS/PERSONAL PROTECTION MEASURES**

Respiratory Protection: None required under normal conditions. See Section 12.  
Hand Protection: Canvas or cotton gloves.  
Eye Protection: Safety glasses with side shields (ANSI Z87.1 equivalent).  
Other Protection: N/A  
Ventilation: Local exhaust ventilation systems should be constructed and installed in accordance with ANSI Z9.2 or ACGIH guidelines to control potential emissions near the source.

#### **12. STORAGE AND HANDLING INFORMATION**

Maximum Storage Temperature: N/A  
Storage Measures: If material is stored under ambient temperature conditions, it is not hazardous. However, extensive storing at higher than the maximum temperature will emit vapors, carbon monoxide or carbon dioxide.  
Handling Measures: Processing of the material under high temperatures will cause hazardous emissions of vapors, carbon monoxide or carbon dioxide. Blower collecting and local exhaust ventilation systems should be installed to prevent contaminant dispersion into the air. Sawing of this product generates particulates regulated as "inert" or "nuisance" dusts. To minimize dust emissions, engineering controls should be employed, such as baghouse filters and cyclone separators.

Date Issued: 1/4/2000  
Date Revised: 8/27/2012

Page 3 of 5

**PLASKOLITE, INC.**  
1770 Joyce Avenue  
Columbus, OH 43219

**EMERGENCY HOTLINE:**  
(614) 294-3281

### **13. REGULATORY INFORMATION**

#### **Environment**

Comprehensive  
Environmental Response,  
Compensation, and  
Liability Act (CERCLA):

Under section 102(a) of the Act, this product is NOT designated as hazardous. In addition, no reportable quantities and no notification requirements to the National Response Center in Washington, DC are set forth for its release from a vessel, an offshore or an onshore facility (40 CFR Part 302).

Resource Conservation and  
Recovery Act (RCRA):

When this product becomes a waste, it is identified as solid but NOT hazardous waste under RCRA criteria (40 CFR Part 261).

Toxic Substances Control  
Act (TSCA):

The components of this product are on the TSCA inventory list. Any impurities present in this product are exempt from listing.

Superfund Amendment and  
Reauthorization Act  
of 1986 (SARA) Title III:

N/A

#### **Transportation**

DOT Hazard Class:  
DOT Shipping Name:

Not regulated.  
N/A

#### **Labor Awareness**

This product as supplied is non-hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). However, under processing conditions it may become a health hazard to employees because vapors and/or particulates could be released. See Section 12 for Storage and Handling Information.

### **14. GLOSSARY**

ACGIH	American Conference of Governmental Industrial Hygienists
CFR	Code of Federal Regulations
DOT	United States Department of Transportation
mg/m <sup>3</sup>	milligrams per cubic meter(concentration)
MSHA	Mine Safety and Health Administration

Date Issued: 1/4/2000  
Date Revised: 8/27/2012

Page 4 of 5

**PLASKOLITE, INC.**  
1770 Joyce Avenue  
Columbus, OH 43219

**EMERGENCY HOTLINE:**  
**(614) 294-3281**

**N/A**            **Not Applicable or Not Available**

**NIOSH**        **National Institute for Occupational Safety and Health**

**OSHA**        **Occupational Safety and Health Administration (Department of Labor)**

**PEL**         **Permissible Exposure Limit (time-weighted average)**

**ppm**         **parts per million (concentration)**

**PS**          **Polystyrene**

**STEL**        **Short-Term Exposure Limit (15-minute)**

**TLV**         **Threshold Limit Value (time-weighted average)**

The information presented herein is believed to be factual and reliable. It is offered in good faith, but without guarantee, since conditions and methods for the use of our products are beyond our control. We recommend that the prospective user determine the suitability of our products and these suggestions before adopting them on a commercial scale.

Please direct comments and questions to Plaskolite Environmental, Health and Safety

Filename: MSDS - Polystyrene Plastic.doc

**Date Issued: 1/4/2000**  
**Date Revised: 8/27/2012**

**Page 5 of 5**