

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

19903-2070

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
 24 hour Chemtrec telephone number:* (800) 424-9300 Page 1 of 3
 24 hour Chemtrec International number:* (703) 527-3887 (collect calls accepted.)
 *TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
 A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.
 Date prepared: 4/21/2011

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

----- SECTION I - PRODUCT IDENTIFICATION -----

PRODUCT IDENTITY (TRADE NAME): #2547 Gloss Black Paint Marker Oil Base Brushing
 Enamel.

----- SECTION II - HAZARDOUS INGREDIENTS -----

SPECIFIC CHEMICAL NAME	CAS #	% WT	OSHA PEL/TWA	ACGIH TLV/TWA
Mineral Spirits	64742-88-7	35-40	500 ppm.*	100 ppm.*
Ethyl Benzene	100-41-4	0.1-1	100 ppm.	100 ppm.
VM&P Naphtha	64742-89-8	15-20	300 ppm.	300 ppm.
Xylol (Xylene)	1330-20-7	1-5	100 ppm	100 ppm.
High Boiling Aliphatic Hydrocarbon	64742-47-8	1-5	500 ppm.	100 ppm.
Carbon Black Pigment	1333-86-4	1-5	3.5 mg/cu.m.	3.5 mg/cu.m.

* Stoddard Solvent as Guide

----- SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS -----

BOILING RANGE: 246 to 404 deg.F	SPECIFIC GRAVITY (Water=1): .876
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 7.30	VAPOR PRESSURE: 5.6 mm Hg @ 20 deg.C (calc.)
PERCENT VOLATILES (By Volume): 68.1	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Slower than Ethyl Ether.

----- SECTION IV - FIRE & EXPLOSION HAZARD DATA -----

FLASH POINT (SFCC): 73 deg.F
 OSHA FLAMMABILITY CLASSIFICATION: Flammable Liquid - CLASS IC
 FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 7.0
 EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.
 SPECIAL FIRE FIGHTING PROCEDURES: Caution: Flammable. A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
 UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel considerable distance to ignition source and flash back. Product may float and be reignited at water's surface. Overexposure to decomposition products may cause a health hazard.

MATERIAL SAFETY DATA SHEET
 THE TESTOR CORPORATION
 440 BLACKHAWK PARK AVENUE
 ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
 24 hour Chemtrec telephone number: *(800) 424-9300 Page 2 of 3
 24 hour Chemtrec International number: *(703) 527-3887 (collect calls accepted.)
 Date prepared: 4/21/2011

 Product Identity: #2547 Gloss Black Paint Marker Brushing Enamel

SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Flammable.
 Contain spilled product by diking. Eliminate all possible ignition sources.
 Provide adequate ventilation. Equip emergency responders with appropriate
 personal protection equipment. Take up spill with an absorbent material and
 place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local,
 state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? YES* OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Short term liquid or vapor contact may result in slight eye
 irritation. Prolonged and repeated contact may be more irritating.
 SKIN CONTACT: Prolonged and repeated liquid contact can cause defatting and
 drying of the skin which may result in skin irritation and dermatitis.
 BREATHING: Vapors or mist may cause irritation to the throat, mucous membranes
 and upper respiratory tract. Inhalation overexposure can lead to central
 nervous system depression producing effects such as headaches, nausea,
 dizziness and loss of consciousness.
 SWALLOWING: May result in vomiting. Aspiration (breathing) of vomitus into
 lungs must be avoided as even small quantities in the lungs may result in
 chemical pneumonitis and pulmonary edema/hemorrhage.
 CHRONIC OVEREXPOSURE: Reports of animal test studies involving prolonged and
 repeated inhalation exposures to light hydrocarbon vapors have shown possible
 effects to the liver, kidney, and lungs. The relevance of these effects to
 man is unknown.
 *Ethyl Benzene component is an IARC Group 2B-Possible carcinogen.
 *Carbon Black component is an IARC Group 2B-Possible carcinogen.
 WARNING: This product contains a chemical known to the State of California
 to cause cancer and birth defects or other reproductive harm.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding
 eye lids open. Call a physician.
 SKIN CONTACT: Remove any contaminated clothing and wash skin with soap
 and water thoroughly. If irritation persists, get medical attention.
 BREATHING: Remove victim to fresh air and provide oxygen if breathing is
 difficult. Give artificial respiration if not breathing. Get medical attention.
 SWALLOWING: Do not induce vomiting. Call a physician at once. If vomiting
 occurs, keep head below hips to prevent aspiration of liquid into lungs.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300 Page 3 of 3
24 hour Chemtrec International number: *(703) 527-3887 (collect calls accepted.)
Date prepared: 4/21/2011

Product Identity: #2547 Gloss Black Paint Marker Brushing Enamel

----- SECTION VIII- REACTIVITY DATA -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- SECTION IX SPECIAL PROTECTION INFORMATION -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,
mists and/or dusts. If exposure may or does exceed occupational
exposure limits (Section II) use a NIOSH-approved respirator to
prevent overexposure. In accord with 29 CFR 1910.134 use either an
atmosphere-supplying respirator or an air purifying respirator with
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- SECTION X SPECIAL PRECAUTIONS -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as flammable liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.