

MSDS for #19919 - LIQUITEX PAINT MARKERS SAFETY DATA SHEET

LIQUITEX MARKER PEN COLOUR FORMULATIONS

According to Regulation (EU) No 453/2010

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name LIQUITEX MARKER PEN COLOUR FORMULATIONS
Product No. 3013646647604 to 3013646648106

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Marker Intermediate

1.3. Details of the supplier of the safety data sheet

Contact Person Jon Lloyd Group Regulatory Affairs Manager +44 (0)2084243224; j.lloyd@colart.co.uk
Manufacturer ColArt International SA
5 Rue Rene Panhard
Z.I .Nord
72021 Le Mans Cedex 2
+33 2 43 83 83 00
Lefranc-Bourgeois@colart.fr

1.4. Emergency telephone number

33 (0)2 43 83 83 00 This number is only available during office hours.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) R10.

2.2. Label elements

Risk Phrases R10 Flammable.
Safety Phrases S2 Keep out of the reach of children.
S46 If swallowed, seek medical advice immediately and show this container or label.
S51 Use only in well-ventilated areas.
S56 Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

2-BUTOXYETHANOL		< 1%
CAS-No.: 111-76-2	EC No.: 203-905-0	Registration Number: 01-2119475108-36-xxxx
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	Classification (67/548/EEC) Xn;R20/21/22 Xi;R36/38	

MSDS for #19919 - LIQUITEX PAINT MARKER

2-DIMETHYLAMINOETHANOL		< 1%
CAS-No.: 108-01-0	EC No.: 203-542-8	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Corr. 1B - H314 STOT SE 3 - H335	Classification (67/548/EEC) R10 C;R34 Xn;R20/21/22	
BUTANOL-norm		< 1%
CAS-No.: 71-36-3	EC No.: 200-751-6	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335 STOT SE 3 - H336	Classification (67/548/EEC) R10 Xn;R22 Xi;R37/38,R41 R67	
ETHANOL		10-30%
CAS-No.: 64-17-5	EC No.: 200-578-6	Registration Number: 01-2119457610-43-xxxx
Classification (EC 1272/2008) Flam. Liq. 2 - H225	Classification (67/548/EEC) F;R11	
METHANOL		< 1%
CAS-No.: 67-56-1	EC No.: 200-659-6	Registration Number: 01-2119433307-44-xxxx
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	Classification (67/548/EEC) F;R11 T;R23/24/25,R39/23/24/25	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

NOTE! Effects may be delayed. Keep affected person under observation.

Inhalation

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

Immediately rinse mouth and provide fresh air. DO NOT INDUCE VOMITING! Get medical attention.

Skin contact

Wash the skin immediately with soap and water. Remove contaminated clothing. Get medical attention if irritation persists after washing.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

MSDS for #19919 - LIQUITEX PAINT MARKER

~~4.2. Most important symptoms and effects, both acute and delayed~~~~4.3. Indication of any immediate medical attention and special treatment needed~~**SECTION 5: FIREFIGHTING MEASURES****5.1. Extinguishing media**

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

FLAMMABLE.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Avoid inhalation of vapours and aerosol spray.

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material.

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment.

6.4. Reference to other sections**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for safe handling**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool and well-ventilated place.

Storage Class

Flammable liquid storage.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-BUTOXYETHANOL	OES	25 ppm(Sk)		50 ppm(Sk)		
2-DIMETHYLAMINOETHANOL	OES	2 ppm	7.4 mg/m3	6 ppm	22 mg/m3	
BUTANOL-norm	OES			50 ppm(Sk)	154 mg/m3(Sk)	
ETHANOL	OES	1000 ppm	1920 mg/m3			
METHANOL	OES	200 ppm(Sk)	266 mg/m3(Sk)	250 ppm(Sk)	333 mg/m3(Sk)	

Ingredient Comments

OES = Occupational Exposure Standard.

MSDS for #19919 - LIQUITEX PAINT MARKER

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

In case of inadequate ventilation use suitable respirator.

Hand protection

Use suitable protective gloves if risk of skin contact.

Eye protection

Use eye protection. Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Use appropriate skin cream to prevent drying of skin.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Misc. colours.
Odour	Characteristic.
Solubility	Miscible with water
pH-Value, Conc. Solution	8.5
Viscosity	50 seconds Ford 406/2 cup s 20
Flash point	33 CC (Closed cup).

9.2. Other information

Not available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Avoid Heat, sparks, flames.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

10.6. Hazardous decomposition products

In case of fire, toxic gases (CO, CO2, NOx) may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity:

Acute Toxicity (Oral LD50)

Not determined.

Acute Toxicity (Dermal LD50)

Not determined.

MSDS for #19919 - LIQUITEX PAINT MARKER

Acute Toxicity (Inhalation LC50)

Not determined.

Inhalation

Prolonged inhalation of high concentrations may damage respiratory system. May cause irritation to the respiratory system.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Eye contact

Spray and vapour in the eyes may cause irritation and smarting.

Health Warnings

Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes.

Route of entry

Inhalation. Skin and/or eye contact.

Target Organs

Respiratory system, lungs Eyes Skin

Medical Symptoms

Inhalation may cause: Headache. Dizziness. Stupor.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Not known.

12.1. Toxicity

Acute Toxicity - Fish

Not determined.

Acute Toxicity - Aquatic Invertebrates

Not determined.

Acute Toxicity - Aquatic Plants

Not determined.

Acute Toxicity - Microorganisms

Not determined.

12.2. Persistence and degradability

Degradability

The degradability of the product has not been stated.

12.3. Bioaccumulative potential

Bioaccumulation factor

Not determined.

12.4. Mobility in soil

Mobility:

Highly volatile and will rapidly evaporate to the air

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

MSDS for #19919 - LIQUITEX PAINT MARKER

LIQUITEX PAINT MARKER

LIQUITEX PAINT MARKER PEN COLOUR FORMULATIONS

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

UN No. (ADR/RID/ADN)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

14.2. UN proper shipping name

Proper Shipping Name	PAINT RELATED MATERIAL
Proper Shipping Name	PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

**14.4. Packing group**

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

Hazard No. (ADR)	30 Flammable liquid (flash-point between 23°C and 60°C, inclusive) or flammable liquid or solid in the molten state with a flash-point above 60°C, heated to a temperature equal to or above its flash-point, or s heating liquid.
Tunnel Restriction Code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

15.2. Chemical Safety Assessment

Item Numbers: 19919-1021, 19919-1022, 19919-1091, 19919-1092, 19919-1569, 19919-2051, 19919-2052, 19919-2069, 19919-2071, 19919-2072, 19919-2081, 19919-2082, 19919-2121, 19919-2122, 19919-3181, 19919-3182, 19919-3231, 19919-3232, 19919-3311, 19919-3312, 19919-3711, 19919-3712, 19919-3721, 19919-3722, 19919-3731, 19919-3732, 19919-3741, 19919-3742, 19919-3781, 19919-3782, 19919-4111, 19919-4112, 19919-4131, 19919-4132, 19919-4191, 19919-4192, 19919-4221, 19919-4222, 19919-4241, 19919-4242, 19919-4281, 19919-4282, 19919-4541, 19919-4542, 19919-4561, 19919-4562, 19919-4601, 19919-4602, 19919-4911, 19919-4912, 19919-5061, 19919-5062, 19919-5091, 19919-5092, 19919-5171, 19919-5172, 19919-5191, 19919-5192, 19919-5221, 19919-5222, 19919-5241, 19919-5242, 19919-5371, 19919-5372, 19919-5381, 19919-5382, 19919-5751, 19919-5752, 19919-5941, 19919-5942, 19919-6011, 19919-6012, 19919-6021, 19919-6022, 19919-6531, 19919-6532, 19919-7051, 19919-7052, 19919-7201, 19919-7202, 19919-7271, 19919-7272, 19919-7381, 19919-7382, 19919-7551, 19919-7552, 19919-7711, 19919-7712, 19919-7871, 19919-7872, 19919-8041, 19919-8042, 19919-8051, 19919-8052, 19919-8061, 19919-8062, 19919-8071, 19919-8072, 19919-9101, 19919-9102, 19919-9381, 19919-9382, 19919-1019

MSDS for #19919 - LIQUITEX PAINT MARKER PEN COLOUR FORMULATIONS

SECTION 16: OTHER INFORMATION

Date	11/04/12
Risk Phrases In Full	
R34	Causes burns.
R10	Flammable.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R22	Harmful if swallowed.
R11	Highly flammable
R36/38	Irritating to eyes and skin.
R37/38	Irritating to respiratory system and skin.
R37	Irritating to respiratory system.
R41	Risk of serious damage to eyes.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R67	Vapours may cause drowsiness and dizziness.
Hazard Statements In Full	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs <<Organs>>.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in a process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Item Numbers: 19919-1021, 19919-1022, 19919-1081, 19919-1092, 19919-1569, 19919-2051, 19919-2052, 19919-2069, 19919-2071, 19919-2072, 19919-2081, 19919-2082, 19919-2121, 19919-2122, 19919-3181, 19919-3182, 19919-3231, 19919-3232, 19919-3311, 19919-3312, 19919-3711, 19919-3712, 19919-3721, 19919-3722, 19919-3731, 19919-3732, 19919-3741, 19919-3742, 19919-3781, 19919-3782, 19919-4111, 19919-4112, 19919-4131, 19919-4132, 19919-4191, 19919-4192, 19919-4221, 19919-4222, 19919-4241, 19919-4242, 19919-4281, 19919-4282, 19919-4541, 19919-4542, 19919-4561, 19919-4562, 19919-4601, 19919-4602, 19919-4911, 19919-4912, 19919-5061, 19919-5062, 19919-5091, 19919-5092, 19919-5171, 19919-5172, 19919-5191, 19919-5192, 19919-5221, 19919-5222, 19919-5241, 19919-5242, 19919-5371, 19919-5372, 19919-5381, 19919-5382, 19919-5751, 19919-5752, 19919-5941, 19919-5942, 19919-6011, 19919-6012, 19919-6021, 19919-6022, 19919-6531, 19919-6532, 19919-7051, 19919-7052, 19919-7201, 19919-7202, 19919-7271, 19919-7272, 19919-7381, 19919-7382, 19919-7551, 19919-7552, 19919-7711, 19919-7712, 19919-7871, 19919-7872, 19919-8041, 19919-8042, 19919-8051, 19919-8052, 19919-8061, 19919-8062, 19919-8071, 19919-8072, 19919-9101, 19919-9102, 19919-9381, 19919-9382, 19919-1019