MAY-21-2008 12:54

FROM-SAKURA OF AMERICA

+5104750973

T-130 P.001/002 F-512

MATELIAL SAFETY DATA SHEET 21377-0169 -1001

(Required under OSHA's Hazard Communication Standard 29 CFR 1910.1200) (XZPK·S) Page 1 of 2 IDENTITY (As Used on Label and List) -4201 -4751 -5071 Permapaque - fine point, 13 colors -6001 XZPK-S-12, brown/ XZPK-S-19, red/ XZPK-S-24, purple/ XZPK-S-29, green/ XZPK-S-03, yellow/ XZPK-S-36, blue XZPK-S-49, black/ XZPK-S-05, orange/ XZPK-S-50, white/ XZPK-S-20, pink/ XZPK-S-27, yellow-green/ -7001 XZPK-S-425, sky blue/ XZPK-S-07, pale orange -8001 Section I Manufacturer's Name: Telephone Number:

Sakura Color Products Corporation +81 (0)6 - 6910 - 8824 (Japan) Address: FAX Number: 1-6-20, Morinomiya Chuo, Chuo ku, Osaka, 540-8508 Japan +81 (0)6 - 6910 - 8834 (Japan) Published Date: Publisher: April 15, 2002 Takahiro Shirai

Section II - Hazardous Ingredients / Identity Information
Hazardous Components CAS No. WT %

OSHA PEL

ACGIH TLV

This product is approved by ACMI (The Art & Creative Material Institute, Inc.), and carries the "A P" seal of non-toxic approval in USA.

Boiling Point:	about 100℃	Specific Gravity: (H₂O = 1 at 25°C)	1.0 ~1.1 N.D.	
Vapor Pressure: (mmHg)	N.D.	Melting Point:		
Vapor Density: (Air = 1)	N.D.	Evaporation Rate: (Butyl Acetate = 1)	N.D.	
Solubility in Water Solul	ole (except pigments)			
Appearance and Odor No or	lor			
Section IV – Fire and Expl	osion Hazard Data			
Flash Point (Method Uses):		Flammable Limits:		
N.D.		LEL: N.D.	UEL: N.D.	
Extinguish Media:	······································			
•				
In case of fire, u	se water spray, loam (or dry chemical powder.		
In case of fire, use Special Fire Fighting Proce No special ment	dures:	or dry chemical powder.		
Special Fire Fighting Proce No special ment Unusual Fire and Explosion	dures: ion h Hazards:	or dry chemical powder. on oxides and sulfur oxide) will form	upon combustion	

-	K-S-05 grange/ YZPK-S-	50 white/ YZPK-S-20 pink/	マフロビ	7 unline amont YZDV C 425 alackles (YZOV C	CAPA-5-49, DIRECTOR 2 (
	PK-S-12, brown/ XZPK-S-19, red/ XZPK-S-24, purple/ XZPK-S-29, green/ XZPK-S-03, yellow/ XZPK-S-36, blue XZPK-S-49, black/ 2PK-S-05, orange/ XZPK-S-50, white/ XZPK-S-20, plnk/ XZPK-S-27, yellow-green/ XZPK-S-425, sky blue/ XZPK-S-07, paic orange Section V - Reactivity Data							
		Unstable	1	Condition to avoid:				
	Stability	Stable	•					
	Incompatibility (Mate							
-								
	Hazardous Decomposition or Byproducts:							
	Hazardous Polymerization	May Occur	П	Condition to avoid				
		May not Occur	•		~			
	Section VI - Health							
- - -	Route(s) of Entry:	?: Yes						
	Carcinogenic:	Health Hazards	(ACUI	ind Chromio): Unknown				
	NTP?: None IARC Monographs?: None OSHA Regulated?: None							
	Signs and Symptoms of Exposure: Not applicable in normal use.							
		Generally Aggravated by			·			
	Emorgopou and Sira	t Aid Departure:		Unknown				
	Emergency and First Aid Procedure:							
	Rout of Entry		Seek medical adv					
	Inhalation	Not applicable						
	Eyes	Gently rinse the aminutes.	Ø					
	Skin	Rinse with running	Rinse with running water and soap.					
	Ingestion	If the victim stops in the mouth and respiration.	Ø					
	Section VII – Precautions for Safe Handling and Use							
	Steps to be taken in Case Material is Released or Spilled.							
	The ink is not spilled so that it soaked into the ink reservoir by normal handling. In the case of stuck to the skin, rinse with running water and soap.							
	Waste Disposal Method:							
	Follow all regulations in your country. Precautions to be taken in Handling and Storing: Keep away high temperature or direct sunlight.							
	Other Precautions: Keep away a strong acid.							
	Section VIII - Con	trol Measures						
	Respiratory Protection (Specify Type):							
			ot nec		·			
		Local Exhaust	ot nec		Special: Not necessary			
	Ventilation	Mechanical (General): Not necessary		Other:	Other: Not necessary			
	Protective Gloves:			Eye Protection:				
		Not necessary Other Protective Clothing or Equipment:						
				Tible Incoessury	<u> </u>			
		othing or Equipment:	t nece					