

#125 / #140 / #200 / #300 / #120 / #130 /
TRICOOLOR OPAQUE PAINT MARKERS

22117-XXXX

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name UCHIDA OF AMERICA, CORP.	Emergency Telephone Number (310) 793 2200
Address (Number, Street, City, State, and ZIP Code) 3535 DEL AMO BLVD. TORRANCE CALIFORNIA, 90503	Telephone Number for Information (310) 793 2215 FAX
	Date Prepared JAN. 27, 1997
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Names)	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
PIGMENTS: COLORED PIGMENTS				10
VEHICLE: RESINS				30
SOLVENTS: XYLENE		100 (ppm)		40
OTHERS: TITANIUM OXIDE				20

CONFORMS TO CONSUMER SAFETY ACT REGULATIONS CFR-16 PART 1500

Section III — Physical/Chemical Characteristics

Boiling Point	280	Specific Gravity (H ₂ O = 1)	N/A
Vapor Pressure (mm Hg.) (at 68°F)	7	Melting Point	.60-75
Vapor Density (AIR = 1)	4	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water INSOLUBLE			
Appearance and Odor PETROLEUM SOLVENT ODOR.			

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) 105°F TAG OPEN	Flammable Limits N/A	LEL	UEL
Extinguishing Media CO₂ or CHEMICAL FORM			
Special Fire Fighting Procedures N/A			
Unusual Fire and Explosion Hazards N/A			

Reproduce locally

Item Numbers: 22117-3731, 22117-5081, 22117-6171, 22117-7941, 22117-8031, 22117-8911, 22117-9011, 22117-9331

OSHA 174, Sept. 1985

Page 1 of 2

No. 2403 P. 2

Feb. 2, 2006 11:51AM Uchida of America, Corp.

#125/ /#200/#300/#120/#130 DECOCOLOR OPAQUE PAINT MARKERS

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	N/A PROLONGED TEMPERATURE AT 110°F

Incompatibility (Materials to Avoid)

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	N/A

Section VI - Health Hazard Data

Routes of Entry:	Inhalation?	Skin?	Ingestion?
	N/A		
Health Hazards (Acute and Chronic)	N/A		

Carcinogenicity:	NTP?	IARC Monographs?	OSHA-Regulated?
N/A			

Signs and Symptoms of Exposure

N/A

Medical Conditions Generally Aggravated by Exposure ANESTHESIA WITHOUT ADEQUATE VENTILATION WHEN USED IN VERY LARGE QUANTITIES.

Emergency and First Aid Procedures IF INGESTED, DO NOT INDUCE VOMITING, CALL PHYSICIAN.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled
ADEQUATE VENTILATION, TREAT AS FLAMMABLE SOLVENT OR PAINT SPILL.

Waste Disposal Method WITH OTHER PETROLEUM PRODUCTS.

Precautions to Be Taken in Handling and Storage DO NOT STORE NEAR HEAT SOURCE

Other Precautions N/A

Section VIII - Control Measures

Respiratory Protection (Specify Type) AVOID PROLONGED INHALATION OF CONCENTRATED VAPOR

Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (General)	N/A	Other	N/A

Protective Gloves N/A Eye Protection N/A

Other Protective Clothing or Equipment N/A

Work/Hygienic Practices N/A