

**MATERIALS SAFETY DATA SHEET**Date Revised June 16, 2010 3rd Edition

FOR CHEMICAL EMERGENCY

During Business Hours: (800) 966-3458**Outside Business Hours:** (800) 420-7186**1. IDENTIFICATION OF THE PRODUCT**

PRODUCT NAME: Gorilla Epoxy (Green Package) - Resin
SYNONYMS: Epoxy Resin

DISTRIBUTOR: The Gorilla Glue Company
 4550 Red Bank Expressway
 Cincinnati, OH 45227
 Tel: (513) 271-3300
 Fax: (513) 527-3742

2. HAZARDS IDENTIFICATION**OVEREXPOSURE EFFECTS:****ACUTE EFFECTS:****EYES:** Contact with eyes can cause severe irritation, possible irreparable eye damage.**SKIN:** Contact with skin can cause irritation, (minor itching, burning and/or redness), Dermatitis, defatting may be readily absorbed through the skin.**INHALATION:** Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and/or asphyxiation. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal.**INGESTION:** Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea.**PRIMARY ROUTES OF EXPOSURE:** skin, inhalation**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<u>INGREDIENTS</u>	<u>WGT%</u>	<u>CAS #</u>
Epoxy Resin	80-90%	25068-38-6
Modified Epoxy Resin	5-15%	Supplier Trade Secret
Alkyl Glycidyl Ether	5-15%	68609-97-2

4. FIRST AID MEASURES**INHALATION:** If inhaled, remove victim from exposure to a well-ventilated area. Make them comfortably warm, but not hot. Use oxygen or artificial respiration as required. Consult a physician.**SKIN:** For skin contact, wash promptly with soap and excess water.**EYES:** For eye contact, flush promptly with excess water for at least fifteen minutes. Consult a physician.**INGESTION:** If ingested, do not induce vomiting. Give victim a glass of water. Call a physician immediately.



MATERIALS SAFETY DATA SHEET

Date Revised June 16, 2010 3rd Edition

FOR CHEMICAL EMERGENCY

During Business Hours: (800) 966-3458

Outside Business Hours: (800) 420-7186

5. FIRE- FIGHTING MEASURES

FIRE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam

SPECIAL FIRE FIGHTING PROCEDURES: Fight like a fuel oil fire. Cool fire exposed containers with water spray.

Firefighter should wear OSHA/NIOSH approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: Closed containers exposed to high temperatures, such as fire conditions may rupture.

6. ACCIDENTAL RELEASE MEASURES

SPILLS, LEAK OR RELEASE: Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapor. Contain spill with absorbent.

7. HANDLING AND STORAGE

STORAGE AND HANDLING: Use with adequate ventilation. Avoid contact with eyes and skin. Avoid breathing vapors. Do not store the product above 100°F/38°C. Do not flame, cut, braze weld or melt empty containers. Keep the product away from heat, open flame, and other sources of ignition. Avoid contact with strong acids, alkalis, and oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENTS

CAS

TLV

Epoxy Resin	25068-38-6	N/E
Modified Epoxy Resin	Supplier Trade Secret	N/E
Alkyl Glycidyl Ether	68609-97-2	N/E

RESPIRATORY PROTECTION: If component TLV limits are exceeded, use NIOSH/MSHA approved respirator to remove vapors. Use an air-supplied respirator if necessary. With general room ventilation, does not require a respirator.

VENTILATION: Use adequate ventilation in volume and pattern to keep TLV/PEL below recommended levels. Explosion-proof ventilation may be necessary.

PROTECTIVE GLOVES: To prevent prolonged exposure use rubber gloves; solvents may be absorbed through the skin.

EYE PROTECTION: Safety Glasses or goggles with splash guards or side shields.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing as required to prevent skin contact.

**MATERIALS SAFETY DATA SHEET**Date Revised June 16, 2010 3rd Edition**FOR CHEMICAL EMERGENCY****During Business Hours: (800) 966-3458****Outside Business Hours: (800) 420-7186****9. PHYSICAL AND CHEMICAL PROPERTIES**

FLASH POINT: >200°F/ 93°C Seta Flash Closed cup

LOWER FLAMMABLE LIMIT %: N/E

UPPER FLAMMABLE LIMIT %: N/E

APPEARANCE: Clear viscous liquid

SPECIFIC GRAVITY: 1.14

VAPOR PRESSURE (mmHg): < 1

BOILING POINT: N/AV

VAPOR DENSITY: Heavier than air

EVAPORATION RATE (Ethyl Ether = 1): Slower than Ethyl Ether

VOLATILES BY WEIGHT: Nil

SOLUBILITY IN WATER: Nil

VOC: Grams/Liter = Nil

Lbs/Gallon = Nil

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Open flames, sparks, heat, electrical and static discharge.

INCOMPATIBILITY MATERIALS TO AVOID: Strong acids, alkalis, oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide, and Carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION**CHRONIC EFFECTS:**

Overexposure to this material has apparently been known to cause the following effects in lab animals: skin sensitization, respiratory system irritation.

CARCINOGEN: YES NO TERATOGEN: YES NO MUTAGEN: YES NO **12. ECOLOGICAL INFORMATION**

NOT A MARINE POLLUTANT

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION**For Ground Transport: In USA**

Not Regulated

For Air Transport:

Not Regulated

For Ocean Transport:

Not Regulated

**MATERIALS SAFETY DATA SHEET**Date Revised June 16, 2010 3rd Edition**FOR CHEMICAL EMERGENCY****During Business Hours: (800) 966-3458****Outside Business Hours: (800) 420-7186****15. REGULATORY INFORMATION****CALIFORNIA PROPOSITION 65:**

Trace amounts of epichlorohydrin, a chemical known to the State of California to cause cancer, is present in this product. However, given the low level and application of this product, typical uses do not constitute a significant risk under the standard.

SECTION 313 SUPPLIER NOTIFICATION:

This product contains the following toxic chemicals subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CHEMICAL NAME</u>	<u>CAS</u>	<u>% BY WGT</u>
----------------------	------------	-----------------

N/AP

This information must be included in all MSDS that are copied and distributed for this chemical.

16. OTHER INFORMATION

HMIS RATING:	Health	2	4 = Extreme
	Fire	1	3 = High
	Reactivity	0	2 = Moderate
			1 = Slight
			0 = Insignificant

Personal Protection - See Section 8

ABBREVIATIONS

IARC = International Agency for Research on Cancer
 ACGIH = American Conference of Governmental Industrial Hygienists
 NIOSH = National Institute of Occupational Safety and Health
 TLV = Threshold Limit Value
 PEL = Permissible Emission Level
 DOT = Department of Transportation
 NTP = National Toxicology Program
 N/AV = Not Available
 N/AP = Not Applicable
 N/E = Not Established
 N/D = Not Determined

The information presented in this Material Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.