

82489 MSDS for #23702 - BLAIR XSTRNGTH ADHSV
01 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

| | | | |
|---------------------|---|---------------------------|----------------|
| PRODUCT NUMBER | 82489 | HMIS CODES | |
| | | Health | 1 |
| | | Flammability | 4 |
| | | Reactivity | 0 |
| PRODUCT NAME | Blair Spary Adhesive | | |
| MANUFACTURER'S NAME | Dist. by: Creative Chemical Solutions Ltd. Cleveland, OH 44128 | | |
| DATE OF PREPARATION | 30-MAR-05 | EMERGENCY TELEPHONE NO. | (216) 566-2917 |
| | | INFORMATION TELEPHONE NO. | (866) 833-7797 |

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

| % by WT | CAS No. | INGREDIENT | UNITS | VAPOR PRESSURE |
|---------|----------|------------|--------------|----------------|
| 9 | 74-98-6 | Propane | | |
| | | ACGIH TLV | 2500 ppm | 760 mm |
| | | OSHA PEL | 1000 ppm | |
| 21 | 106-97-8 | Butane | | |
| | | ACGIH TLV | 800 ppm | 760 mm |
| | | OSHA PEL | 800 ppm | |
| 33 | 142-82-5 | Heptane | | |
| | | ACGIH TLV | 400 ppm | 50 mm |
| | | ACGIH TLV | 500 ppm STEL | |
| | | OSHA PEL | 400 ppm | |
| | | OSHA PEL | 500 ppm STEL | |
| 19 | 67-64-1 | Acetone | | |
| | | ACGIH TLV | 500 ppm | 180 mm |
| | | ACGIH TLV | 750 ppm STEL | |
| | | OSHA PEL | 1000 ppm | |

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE
 INHALATION of vapor or spray mist.
 EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE
 EYES: Irritation.
 SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.
 May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE
 Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.
 Redness and itching or burning sensation may indicate eye or excessive skin exposure.

Continued on page 2

MSDS for #23702-13 LARGESTRONGTH ADSV EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and laundry before re-use.

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Do not induce vomiting. Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT LEL UEL
Propellant < 0 F 1.0 12.8

EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY

Not Available

Continued on page 3

MSDS No #23702-2-BLACK STRING HANDS
PRECAUTIONS TO BE TAKEN IN USE AND STORAGE

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.
During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.
Consult NFPA Code. Use approved Bonding and Grounding procedures.
Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.
Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.
Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|--|--------------|
| PRODUCT WEIGHT | 5.83 lb/gal | 698 g/l |
| SPECIFIC GRAVITY | 0.70 | |
| BOILING POINT | <0 - 238 F | <-18 - 114 C |
| MELTING POINT | Not Available | |
| VOLATILE VOLUME | 87 % | |
| EVAPORATION RATE | Faster than ether | |
| VAPOR DENSITY | Heavier than air | |
| SOLUBILITY IN WATER | N.A. | |
| VOLATILE ORGANIC COMPOUNDS (VOC Theoretical) | | |
| Volatile Weight 63.40 % | Less Water and Federally Exempt Solvents | |

Continued on page 4

=====
 MSDS for #23702 on BLAIR X-STRONG ADHESIVE AND REACTIVITY
 =====
 Page 4 of 5

STABILITY -- Stable
 CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

 =====
 Section 11 -- TOXICOLOGICAL INFORMATION
 =====

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.
 Reports have associated repeated and prolonged overexposure to solvents
 with permanent brain and nervous system damage.

TOXICOLOGY DATA

| CAS No. | Ingredient Name | | | | |
|----------|-----------------|------|-----|-----|---------------|
| 74-98-6 | Propane | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |
| 106-97-8 | Butane | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |
| 142-82-5 | Heptane | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |
| 67-64-1 | Acetone | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | 5800 mg/kg |

 =====
 Section 12 -- ECOLOGICAL INFORMATION
 =====

ECOTOXICOLOGICAL INFORMATION

No data available.

 =====
 Section 13 -- DISPOSAL CONSIDERATIONS
 =====

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource
 Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA
 hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance
 with Federal, State/Provincial, and Local regulations regarding pollution.

 =====
 Section 14 -- TRANSPORT INFORMATION
 =====

No data available.

Continued on page 5

MSDS for #23702 on BLAIR X-STRENGTH ADHESIVE

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|---------|-------------------|---------|-----------|
|---------|-------------------|---------|-----------|

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.