

24000-1001
-1002
-1003

MATERIAL SAFETY DATA SHEET
 May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200 ~
 Standard must be consulted for specific requirements

U.S. DEPARTMENT OF LABOR
 OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION
 (Non Mandatory Form) FORM APPROVED
 OMB No. 1218-0072

IDENTITY: (As used on Label & List)
NORI PASTE: NP55K, NP56

NOTE: Blank spaces are not permitted. If any items are not applicable, or no information is available, the space must be marked to indicate that (N/A)

SECTION I

MANUFACTURER'S NAME
YASUTOMO & COMPANY
 ADDRESS (Number, Street, City, State & Zip)
490 ECCLES AVENUE

SOUTH SAN FRANCISCO, CA 94080

EMERGENCY PHONE NUMBER:
CALL YOUR LOCAL POISON CONTROL CENTER
 INFORMATION NUMBER:
650.737.8888
 DATE PREPARED:
updated: MAY 10, 2006
 SIGNATURE OF PREPARED (optional)

SECTION II - HAZARDOUS INGREDIENTS / IDENTIFY INFORMATION

HAZARDOUS COMPONENTS (Specific Chemical Identify: Common Name(s))	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED % (OPTIONAL)

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: 100 * C	SPECIFIC GRAVITY (H ₂ O = 1) 1.082
VAPOR PRESSURE (mm Hg): N/A	MELTING POINT: N/A
VAPOR DENSITY (AIR - 1) N/A	EVAPORATION RATE: (butyl acetate - 1) N/A
SOLUBILITY IN WATER MISCIBLE	
APPEARANCE & ODOR: WHITE PASTE, ODOR OF MATERIAL	

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (Method Used): N/A	FLAMMABLE LIMITS: N/A	LEL:	UEL:
EXTINGUISHING MEDIA: WATER DRY CHEMICAL			
SPECIAL FIRE FIGHTING PROCEDURES: NONE			
USUAL FIRE & EXPLOSION HAZARDS:			

SECTION V - REACTIVITY DATA

STABILITY:	UNSTABLE	CONDITIONS TO AVOID:
	STABLE	
	X	HIGH TEMPERATURE, HIGH HUMIDTY

OSHA 174, OCTOBER 2005
 7/25/2006 ~ PAGE 1 of 2

MATERIAL SAFETY DATA SHEET

(PAGE 2 OF 2)

U.S. DEPARTMENT OF LABOR

IDENTITY: (As used on Label & List)

NORI PASTE: NP55K, NP56

SECTION V – REACTIVITY DATA (continued)

INCOMPATIBILITY (Materials to Avoid)

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

HAZARDOUS POLYMERIZATION:	MAY OCCUR	CONDITIONS TO AVOID:
	WILL NOT OCCUR	
	X	

SECTION VI – HEALTH HAZARD DATA

ROUTE(S) OF ENTRY:	INHALATION?	SKIN?	INGESTION?
	N/A	N/A	N/A

HEALTH HAZARDS (Acute & Chronic):

N/A

CARCINOGENICITY:	NTP?	IARC MONOGRAPHS?	OSHA REGULATED?
------------------	------	------------------	-----------------

SIGNS & SYMPTOMS OF EXPOSURE:

MEDICAL CONDITIONS – GENERALLY AGGRAVATED BY EXPOSURE:

EMERGENCY & FIRST AID PROCEDURES:

REMOVE TO FRESH WATER. SEEK MEDICAL ADVICE.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING & USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID INHALATION & INGESTION. AVOID HIGH TEMPERATURE & HUMIDITY.
 RECAP AFTER EACH USE.

WASTE DISPOSAL METHOD

SALVAGE & INCINERATE AFTER CONSULTATION AT LOCAL AUTHORITIES.

PRECAUTIONS TO BE TAKEN IN HANDLING & STORING:

AVOID HIGH TEMPERATURE & HUMIDITY

OTHER PRECAUTIONS:

NONE

SECTION VIII – CONTROL MEASURES

RESPIRATORY PROTECTION (Specify Type)

NOT REQUIRED

VENTILATION:

LOCAL EXHAUST

SPECIAL:

MECHANICAL (General)

No

N/A

OTHER:

N/A

N/A

PROTECTIVE GLOVES:

NOT REQUIRED

EYE PROTECTION:

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

NOT REQUIRED

WORK / HYGENIC PRACTICES:

NOT REQUIRED

OSHA 174, OCTOBER 2005
 7/25/2006 – PAGE 2 of 2