

24203-1015

MATERIAL SAFETY DATA SHEET
 THE TESTOR CORPORATION (DISTRIBUTOR)
 440 BLACKHAWK PARK AVENUE
 ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
 24 hour Chemtrec telephone number: * (800) 424-9300 Page 1 of 3
 24 hour Chemtrec International number: * (703) 527-3887 (collect calls accepted.)
 *TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
 A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.
 Date prepared: 5/05/2011

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

----- SECTION I - PRODUCT IDENTIFICATION -----

PRODUCT IDENTITY (TRADE NAME): #3517 Super Glue for Plastic, Metal and
 Wood Models

----- SECTION II - HAZARDOUS INGREDIENTS -----

SPECIFIC CHEMICAL NAME	CAS #	% WT	OSHA PEL/TWA	ACGIH TLV/TWA
Ethyl-2-Cyanoacrylate	7085-85-0	80-99	Not Estab.	Not Estab.
Poly Methyl Methacrylate	9011-14-7	0-30	Not Estab.	Not Estab.

----- SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS -----

BOILING RANGE: @4mmHg	149 deg.F	SPECIFIC GRAVITY (Water=1):	1.05
GALLON WEIGHT OF PRODUCT (Lbs/Gal):	8.75	VAPOR PRESSURE:	0.2 mm Hg @ 20 deg.C (calc.)
PERCENT VOLATILES (By Volume):	98.8	VAPOR DENSITY:	3 (Ethyl Ether = 1)
		EVAPORATION RATE:	Not Estab

----- SECTION IV - FIRE & EXPLOSION HAZARD DATA -----

FLASH POINT (TCC): 176 deg.F
 OSHA FLAMMABILITY CLASSIFICATION: Combustible Liquid - CLASS IIIA
 FLAMMABLE LIMITS (calc.) IN AIR: LEL Not Available, UEL Not Available
 EXTINGUISHING MEDIA: Flush with large amounts of water or dry chemical
 extinguisher.
 SPECIAL FIRE FIGHTING PROCEDURES: Caution: Combustible. Use air mask to avoid
 respiratory tract or eye irritation. Wear gloves as material bonds skin
 instantly.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water
 spray (fog).

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION (DISTRIBUTOR)
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300 Page 2 of 3
24 hour Chemtrec International number: *(703) 527-3887 (collect calls accepted.)
Date prepared: 5/05/2011

Product Identity: #3517 Super Glue for Plastic, Metal and Wood Models

SECTION V - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Combustible.
Eliminate all possible ignition sources. Contain spilled product by diking.
Provide adequate ventilation. Take up spill with an absorbent material and
sweep into tray for liquid to be reacted with water for solid waste treatment.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Incinerate solid combustible waste or
dump as chemical waste according to local, state, and federal regulations.

SECTION VI - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation and Ingestion
CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO
EFFECTS OF OVEREXPOSURE:
EYE CONTACT: Vapor causes eye irritation and tearing.
SKIN CONTACT: To be avoided as material bonds skin instantly.
BREATHING: Causes irritation of mucous membranes and coughing. Can aggravate
asthmatic conditions of certain individuals.
SWALLOWING: Ingestion is not likely.
CHRONIC OVEREXPOSURE: No residual effects of acute properties.

SECTION VII EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding
eye lids open. Call a physician.
SKIN CONTACT: Remove any contaminated clothing. Wipe away any liquid adhesive
where possible and thoroughly flush and soak with water to remove residual
adhesive.
BREATHING: Remove victim to fresh air and provide oxygen if breathing is
difficult.
SWALLOWING: If lips are accidentally stuck together, apply lots of warm water
to the lips and encourage maximum wetting and pressure from saliva inside the
mouth. Peel or roll lips apart. Do not try to pull the lips with direct
opposing action. It is almost impossible to swallow cyanoacrylate. The
adhesive solidifies and adheres in the mouth. Saliva will lift the adhesive in
one half to two days. In case a lump forms in the mouth, position the
patient to prevent ingestion of the lump when it detaches.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION (DISTRIBUTOR)
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300 Page 3 of 3
24 hour Chemtrec International number: *(703) 527-3887 (collect calls accepted.)
Date prepared: 5/05/2011

Product Identity: #3517 Super Glue for Plastic, Metal and Wood Models

----- SECTION VIII- REACTIVITY DATA -----

STABILITY: Stable up to 122 deg F. Store in a cool, dry place.

CONDITIONS TO AVOID: Avoid excessive heat above 176 deg F, moisture
and alkalines.

INCOMPATIBILITY : Polymerized by water, alcohol, amines, alkaline materials
and direct ultra violet.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and Carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

----- SECTION IX SPECIAL PROTECTION INFORMATION -----

RESPIRATORY PROTECTION: Normally not necessary. A NIOSH approved organic vapor
canister may be used to prevent overexposure.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below 2 ppm to eliminate eye irritation. All
ignition sources (non-explosion proof equipment) should be
eliminated if flammable mixtures will be encountered.

PROTECTIVE GLOVES: Non-sticking vinyl or polyethylene are recommended.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- SECTION X SPECIAL PRECAUTIONS -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Avoid moisture and direct ultra violet sun light. Store away from ignition
sources in a cool, well ventilated area. Avoid breathing vapor and contact with
eyes and skin. Handle as combustible liquid.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.
