

MATERIAL SAFETY DATA SHEET
 THE TESTOR CORPORATION
 440 BLACKHAWK PARK AVENUE
 ROCKFORD, ILLINOIS 61104

24203-1078
 -3058

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
 24 hour Chemtrec telephone number:* (800) 424-9300 Page 1 of 3
 24 hour Chemtrec International number:* (703) 527-3887 (collect calls accepted.)
 *TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
 A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.
 Date prepared: 5/05/2011

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

----- SECTION I - PRODUCT IDENTIFICATION -----

PRODUCT IDENTITY (TRADE NAME): #3521, #3522, #3523, and #3996 Non-Toxic Cement
 for Plastic Models.

----- SECTION II - HAZARDOUS INGREDIENTS -----

SPECIFIC CHEMICAL NAME	CAS #	% WT	OSHA PEL/TWA	ACGIH TLV/TWA
d-Limonene	5989-27-5	70-75	Not Estab. LD50 (Rat) 20 grams/kg. Body Weight Considered Non-Toxic	Not Estab.

----- SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS -----

BOILING RANGE: 328 to 346 deg.F	SPECIFIC GRAVITY (Water=1): .884
GALLON WEIGHT OF	VAPOR PRESSURE: Not Established
PRODUCT (Lbs/Gal): 7.36	VAPOR DENSITY: Heavier than air.
PERCENT VOLATILES	EVAPORATION RATE: Slower than Ethyl Ether.
(By Volume): 78.6	

----- SECTION IV - FIRE & EXPLOSION HAZARD DATA -----

FLASH POINT (SFCC): 116 F
 OSHA FLAMMABILITY CLASSIFICATION: Combustible Liquid - CLASS II
 FLAMMABLE LIMITS (CALC) IN AIR: LEL Not Estab., UEL Not Estab.
 EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide or dry chemical.
 SPECIAL FIRE FIGHTING PROCEDURES: Treat as combustible liquid.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to heat may build up pressure in
 closed containers. Cool with water spray.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300 Page 2 of 3
24 hour Chemtrec International number: *(703) 527-3887 (collect calls accepted.)
Date prepared: 5/05/2011

Product Identity: #3521, #3522, & #3523 Non-Toxic Cement for Plastic Models

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Eliminate all possible ignition sources. Provide adequate ventilation. Take up with an absorbent material and place in non-leaking container. Seal for proper disposal.

WASTE DISPOSAL METHOD: Do not incinerate closed containers. Dispose of in accordance with local, state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? NO OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Excessive exposure can cause minor irritation and redness.

SKIN CONTACT: Non Toxic. The LD50 (rabbit) is greater than 2.0 g/kg of body weight. Prolonged and/or repeated exposure may, however, cause some slight irritation.

BREATHING: There was no evidence of toxicity in rats exposed to 49 mg/L (the highest concentration achievable during testing conditions) of the vapor from this cement product. Excessive inhalation of vapors, however, can cause minor irritation of respiratory tract.

SWALLOWING: Non-Toxic (LD50-Rat is 20 g/kg body weight). Can cause gastrointestinal irritation.

CHRONIC OVEREXPOSURE: None known.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding eye lids open.

SKIN CONTACT: Wash immediately with soap and water. Remove contaminated clothing.

BREATHING: Remove to fresh air.

SWALLOWING: Give water to dilute.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number:(815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300 Page 3 of 3
24 hour Chemtrec International number: *(703) 527-3887 (collect calls accepted.)
Date prepared: 5/05/2011

Product Identity: #3521, #3522, & #3523 Non-Toxic Cement for Plastic Models

----- SECTION VIII- REACTIVITY DATA -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and other ignition source.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide if burned with insufficient
air.

HAZARDOUS POLYMERIZATION: Will not occur.

----- SECTION IX SPECIAL PROTECTION INFORMATION -----

RESPIRATORY PROTECTION: None normally required with adequate ventilation.
Avoid prolonged or repeated breathing of vapors.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- SECTION X SPECIAL PRECAUTIONS -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as combustible liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.
