

UAAZ
3 MATERIAL SAFETY DATA SHEET
AAU

UAAZ
3 SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION
AAU

PRODUCT NAME : Sophisticated Finishes SEALER
IDENTIFICATION NUMBER: AM220 DATE PRINTED: 10/06/15
PRODUCT USE/CLASS :

SUPPLIER: Triangle Coatings, Inc. MANUFACTURER: Triangle Coatings, Inc.
4763 Bennett Drive 4763 Bennett Drive
Livermore, CA 94551 Livermore, CA 94551
800-895-8000 (8:00am-5:00pm) 800-895-8000 (8:00am-5:00pm)
CHEMTREC 24HR EMERGENCY TELEPHONE CHEMTREC 24HR EMERGENCY TELEPHONE
800-424-9300 800-424-9300

PREPARER: CMK, PHONE: , PREPARE DATE: 10/06/15

UAAZ
3 SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS
AAU

ITEM CHEMICAL NAME CAS NUMBER WT/WT % LESS THAN
AAU

No Hazardous Materials are Contained in this Product

(See Section 16 for abbreviation legend)

UAAZ
3 SECTION 3 - HAZARDS IDENTIFICATION
AAU

*** EMERGENCY OVERVIEW ***: Harmful if swallowed. Causes eye irritation.
EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause irritation including pain, tearing or reddening accompanied by stinging sensation.
EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation.
EFFECTS OF OVEREXPOSURE - INHALATION: No hazard in normal industrial use.
EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed.
EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: None.
PRIMARY ROUTE(S) OF ENTRY: Unknown

(Continued on Page 2)

Product: AM220 Preparation Date: 10/06/15 Page 2
 SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and shoes. Do not reuse until cleaned.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 200 F LOWER EXPLOSIVE LIMIT: N.A.
(SETAFLASH CLOSED CUP) UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE:

EXTINGUISHING MEDIA: Unknown

UNUSUAL FIRE AND EXPLOSION HAZARDS: Product will not burn but may spatter if temperature exceeds boiling point.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area. Absorb spill with suitable absorbent material, then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. If large spill, dike area and call spill response team. Notify appropriate state and local agencies.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling.

STORAGE: Keep from freezing. Keep container closed when not in use.

(Continued on Page 3)

Product: AM220 Preparation Date: 10/06/15 Page 3
 SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

RESPIRATORY PROTECTION: Atmospheric levels should be maintained below the exposure limits listed in Section 2 by using engineering controls. If not feasible, use a NIOSH approved respirator.

SKIN PROTECTION: General use of chemical resistant gloves are recommended to protect the skin from drying and irritation. Lotions and barrier creams are also recommended to prevent drying of the skin.

EYE PROTECTION: Eye protection is recommended.

OTHER PROTECTIVE EQUIPMENT: If repeated or prolonged skin contact or contamination is likely, protective clothing should be worn.

HYGIENIC PRACTICES: Establish good personal hygiene and work practices. Always wash hands before eating, drinking, or smoking.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: N.A.	VAPOR DENSITY	: Is lighter than air
ODOR	:	ODOR THRESHOLD	:
APPEARANCE	:	EVAPORATION RATE	: Is slower than Butyl Acetate
SOLUBILITY IN H2O	:	SPECIFIC GRAVITY	: 1.0190
FREEZE POINT	:	pH @ 0.0 %	:
VAPOR PRESSURE	:	VISCOSITY	:
PHYSICAL STATE	:		
VOLATILE BY VOLUME	: 70.4%		

COEFFICIENT OF WATER/OIL DISTRIBUTION:

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: No Information.

INCOMPATIBILITY: Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Can include carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

(Continued on Page 4)

Product: AM220 Preparation Date: 10/06/15 Page 4
 SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

TOXICOLOGICAL INFORMATION: This information shown in Section 3 is based on the toxicity profiles for a number of products that are compositionally similar to this product.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Refer to local, county, state and federal storm water and air quality regulations.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with local, county, state, and federal regulations. Incineration is preferred.

SECTION 14 - TRANSPORTATION INFORMATION

No transportation information is available.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Non-hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT/WT % IS LESS THAN
Anhydrous Ammonia	1336-21-6	1.0 %
ETHYL ALCOHOL	64-17-5	0.1 %

U.S. STATE REGULATIONS: AS FOLLOWS -

CALIFORNIA PROPOSITION 65: None Known.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

(Continued on Page 5)

Product: AM220 Preparation Date: 10/06/15 Page 5

SECTION 15 - REGULATORY INFORMATION

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 06/04/15

VOLATILE ORGANIC COMPOUNDS (VOCs): 0.82 lbs/gal, 99 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

<END OF MSDS>

□