SOPHISTICATED BLONDE BRONZE PRODUCT NAME IDENTIFICATION NUMBER: AM205 DATE PRINTED: 10/06/15 PRODUCT USE/CLASS SUPPLIER: MANUFACTURER: Triangle Coatings, Inc. Triangle Coatings, Inc. 4763 Bennett Drive 4763 Bennett Drive Livermore, CA 94551 800-895-8000 (8:00am-5:00pm) Livermore, CA 94551 800-895-8000 (8:00am-5:00pm) CHEMTREC 24HR EMERGENCY TELEPHONE 800-424-9300 CHEMTREC 24HR EMERGENCY TELEPHONE 800-424-9300 PREPARER: CMK, PHONE: , PREPARE DATE: 10/06/15 WT/WT % LESS THAN CAS NUMBER GOLD BRONZE WATER PASTE 10.0 % 02 Trans Red Oxide Water Dispersion 5.0 % ----- EXPOSURE LIMITS ------ACGIH OSHA N.E. 1MG/M3 N.E. N.E. N.E. NO N.E. N.F. N.F. NO *** EMERGENCY OVERVIEW ***: Harmful if swallowed. Causes eye irritation.

(Continued on Page 2)

Page 1

EFFECTS OF OVEREXPOSURE - INHALATION: No hazard in normal industrial use.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause irritation including pain, tearing or reddening accompanied by stinging sensation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation.

Item Numbers: 27111-8264, 27111-8265, 27111-8266 Page 1 of 6

 ${\tt EFFECTS}$ OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: None.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INGESTION EYE CONTACT

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and shoes. Do not reuse until cleaned.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

FLASH POINT: 400 F (SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: N.A. UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE:

EXTINGUISHING MEDIA: CO2 FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Product will not burn but may spatter if temperature exceeds boiling point.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area. Absorb spill with suitable absorbent material, then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. If large spill, dike area and call spill response team. Notify

(Continued on Page 3)

appropriate state and local agencies.

HANDLING: Wash thoroughly after handling.

STORAGE: Keep from freezing. Keep container closed when not in use.

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

RESPIRATORY PROTECTION: Atmospheric levels should be maintained below the exposure limits listed in Section 2 by using engineering controls. If not feasible, use a NIOSH approved respirator.

SKIN PROTECTION: General use of chemical resistant gloves are recommended to protect the skin from drying and irritation. Lotions and barrier creams are also recommended to prevent drying of the skin.

EYE PROTECTION: Eye protection is recommended.

OTHER PROTECTIVE EQUIPMENT: If repeated or prolonged skin contact or contamination is likely, protective clothing should be worn.

HYGIENIC PRACTICES: Establish good personal hygiene and work practices. Always wash hands before eating, drinking, or smoking.

BOILING RANGE VAPOR DENSITY : Is heavier than air : N.A. ODOR THRESHOLD ODOR APPEARANCE EVAPORATION RATE: Is slower than Butyl SOLUBILITY IN H2O: Acetate SPECIFIC GRAVITY: 1.1357 ph @ 0.0 % FREEZE POINT VAPOR PRESSURE PHYSICAL STATE : V
VOLATILE BY VOLUME: 72.0%
COEFFICIENT OF WATER/OIL DISTRIBUTION: VISCOSITY

CONDITIONS TO AVOID: No Information.

(Continued on Page 4)

INCOMPATIBILITY: Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Can include carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

No product or component toxicological information is available.

TOXICOLOGICAL INFORMATION: This information shown in Section 3 is based on the toxicity profiles for a number of products that are compositionally similar to this product.

ECOLOGICAL INFORMATION: Refer to local, county, state and federal storm water and air quality regulations.

DISPOSAL METHOD: Dispose of in accordance with local, county, state, and federal regulations. Incineration is preferred.

No transportation information is available.

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

(Continued on Page 5)

CERCLA - SARA HAZARD CATEGORY: This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----CAS NUMBER WT/WT % IS LESS THAN Anhydrous Ammonia 1336-21-6 0.1 %

U.S. STATE REGULATIONS: AS FOLLOWS -

CALIFORNIA PROPOSITION 65: None Known.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 06/04/15

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.65 lbs/gal, 78 grams/ltr

N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined LEGEND:

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. <END OF MSDS>