59152-04 27111-8264 -08 8265 8266 MATERIAL SAFETY DATA SHEET Revd 3 -10-04 SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION : Blonde Bronze Base IDENTIFICATION NUMBER: AM205 DATE PRINTED: 05/08/03 PRODUCT USE/CLASS : SUPPLIER: MANUFACTURER: Triangle Coatings, Inc. 1930 Fairway Drive San Leandro, CA 94577-5631 Modern Options, Inc 1930 Fairway Dr. San Leandro, CA 94577 TELEPHONE: 510-614-3900 9am to 5pm PST Monday-Friday EMERGENCY TELEPHONE:800-895-8000 (7:00 am - 5:00 pm PST) PREPARER: LY, PHONE: , PREPARE DATE: 07/02/96 SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS ------ CHEMICAL NAME ----- CAS NUMBER 01 Copper (CU as Dust/Mist) 7440508 10.0 % Zinc (as Dust) 7440666 5.0 % ----- EXPOSURE LIMITS ------ACGIH
ITEM TLV-TWA TLV-STEL ACGIH OSHA COMPANY
PEL-TWA PEL-CEILING TLV-TWA SKIN N.E. N.E. N.E. N.E. N.E. N.E. 01 1mg/m3 1mg/m3 NO 02 N.E. NO (See Section 16 for abbreviation legend) SECTION 3 - HAZARDS IDENTIFICATION \*\*\* EMERGENCY OVERVIEW \*\*\*: Harmful if swallowed. Causes eye irritation. EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause irritation including pain, tearing or reddening accompanied by stinging sensation. EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation. EFFECTS OF OVEREXPOSURE - INHALATION: No hazard in normal industrial use. EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed.

(Continued on Page 2)

Product: AM205 Preparation Date: 07/02/96 Page 2
EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: None.
PRIMARY ROUTE(S) OF ENTRY: INHALATION INGESTION EYE CONTACT
SECTION 4 - FIRST AID MEASURES
FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Get medical attention, if irritation persists.
FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and shoes. Do not reuse until cleaned.
FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
FIRST AID - INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
SECTION 5 - FIRE FIGHTING MEASURES
FLASH POINT: 400 F LOWER EXPLOSIVE LIMIT: N.A. (SETAFLASH CLOSED CUP) UPPER EXPLOSIVE LIMIT: N.A.
·
FLASH POINT: 400 F LOWER EXPLOSIVE LIMIT: N.A. (SETAFLASH CLOSED CUP) UPPER EXPLOSIVE LIMIT: N.A.
FLASH POINT: 400 F  (SETAFLASH CLOSED CUP)  AUTOIGNITION TEMPERATURE: N.D.
FLASH POINT: 400 F  (SETAFLASH CLOSED CUP)  AUTOIGNITION TEMPERATURE: N.D.  EXTINGUISHING MEDIA: DRY CHEMICAL FOAM  UNUSUAL FIRE AND EXPLOSION HAZARDS: Product will not burn but may spatter
FLASH POINT: 400 F  (SETAFLASH CLOSED CUP)  LOWER EXPLOSIVE LIMIT: N.A.  UPPER EXPLOSIVE LIMIT: N.A.  AUTOIGNITION TEMPERATURE: N.D.  EXTINGUISHING MEDIA: DRY CHEMICAL FOAM  UNUSUAL FIRE AND EXPLOSION HAZARDS: Product will not burn but may spatter if temperature exceeds boiling point.  SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and
FLASH POINT: 400 F  (SETAFLASH CLOSED CUP)  LOWER EXPLOSIVE LIMIT: N.A.  AUTOIGNITION TEMPERATURE: N.D.  EXTINGUISHING MEDIA: DRY CHEMICAL FOAM  UNUSUAL FIRE AND EXPLOSION HAZARDS: Product will not burn but may spatter if temperature exceeds boiling point.  SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.
FLASH POINT: 400 F  (SETAFLASH CLOSED CUP)  LOWER EXPLOSIVE LIMIT: N.A.  AUTOIGNITION TEMPERATURE: N.D.  EXTINGUISHING MEDIA: DRY CHEMICAL FOAM  UNUSUAL FIRE AND EXPLOSION HAZARDS: Product will not burn but may spatter if temperature exceeds boiling point.  SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.  SECTION 6 - ACCIDENTAL RELEASE MEASURES  STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area. Absorb spill with suitable absorbent material, then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. If large spill, dike area and call spill response team. Notify

Page 2 of 5 Item Numbers: 27111-8264, 27111-8265, 27111-8266

ŧ.

Product: AM205 Preparation Date: 07/02/96 Page 3 SECTION 7 - HANDLING AND STORAGE HANDLING: Wash thoroughly after handling. STORAGE: Keep from freezing. Keep container closed when not in use. SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels. RESPIRATORY PROTECTION: Atmospheric levels should be maintained below the exposure limits listed in Section 2 by using engineering controls. If not feasible, use a NIOSH approved respirator. SKIN PROTECTION: General use of chemical resistant gloves are recommended to protect the skin from drying and irritation. Lotions and barrier creams are also recommended to prevent drying of the skin. EYE PROTECTION: Eye protection is recommended. OTHER PROTECTIVE EQUIPMENT: If repeated or prolonged skin contact or contamination is likely, protective clothing should be worn. HYGIENIC PRACTICES: Establish good personal hygiene and work practices. Always wash hands before eating, drinking, or smoking. SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES \_\_\_\_\_\_\_\_ BOILING RANGE : 210 - 220 F VAPOR DENSITY : Is heavier than air ODOR : Mild ODOR THRESHOLD : N.E.

APPEARANCE : Med. Bronze Liq. EVAPORATION RATE: Is slower than Butyl APPEARANCE : Med. Bronze Liq. EVAPORATION RATE: Is slowe:
SOLUBILITY IN H2O : Soluble in Water
FREEZE POINT : 32 SPECIFIC GRAVITY: 1.1356
VAPOR PRESSURE : N.E. pH @ 100.0 % : 8.7
PHYSICAL STATE : LIQUID VISCOSITY : 54-57 KU
VOLATILE BY VOLUME: 74.7%
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.E. (See Section 16 for abbreviation legend) SECTION 10 - STABILITY AND REACTIVITY CONDITIONS TO AVOID: No Information. INCOMPATIBILITY: Avoid contact with strong oxidizing agents. HAZARDOUS DECOMPOSITION PRODUCTS: Can include carbon dioxide and carbon monoxide. HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

Item Numbers: 27111-8264, 27111-8265, 27111-8266 Page 3 of 5

(Continued on Page 4)

Product: AM205 Preparation Date: 07/02/96 Page Page Page Page Page Page Page Page	ge 4
SECTION 10 - STABILITY AND REACTIVITY	
STABILITY: This product is stable under normal storage conditions.	
SECTION 11 - TOXICOLOGICAL PROPERTIES	
	====
No product or component toxicological information is available.	
TOXICOLOGICAL INFORMATION: This information shown in Section 3 is bat the toxicity profiles for a number of products that are compositional similar to this product.	
SECTION 12 - ECOLOGICAL INFORMATION	:====  
ECOLOGICAL INFORMATION: Refer to local, county, state and federal stowater and air quality regulations.	orm
SECTION 13 - DISPOSAL CONSIDERATIONS	ĺ
	,
DISPOSAL METHOD: Dispose of in accordance with local, county, state, federal regulations. Incineration is preferred.	and
SECTION 14 - TRANSPORTATION INFORMATION	
No transportation information is available.	
SECTION 15 - REGULATORY INFORMATION	
U.S. FEDERAL REGULATIONS: AS FOLLOWS -	•
U.S. FEDERAL REGULATIONS: AS FOLLOWS -	
OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)	
CERCLA - SARA HAZARD CATEGORY: This product has been reviewed according to the EPA 'Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:	•
None	
(Continued on Pag	e 5)

Item Numbers: 27111-8264, 27111-8265, 27111-8266 Page 4 of 5

Product: AM205 Preparation Date: 07/02/96 Page 5 SECTION 15 - REGULATORY INFORMATION SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: ----- CHEMICAL NAME CAS NUMBER WT/WT % IS LESS THAN Copper (CU as Dust/Mist) 7440508 10.0 % Zinc (as Dust) Ammonium Hydroxide 7440666 5.0 % 1336216 0.1 % Naphthalene 91203 1,2,4-Trimethylbenzene 95636 INTERNATIONAL REGULATIONS: AS FOLLOWS -CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings. CANADIAN WHMIS CLASS: No information available. SECTION 16 - OTHER INFORMATION \_\_\_\_\_\_ FLAMMABILITY: 0 REACTIVITY: 0 HMIS RATINGS - HEALTH: 0 PREVIOUS MSDS REVISION DATE: 07/01/96 VOLATILE ORGANIC COMPOUNDS (VOCS): 1.34 lbs/gal, 160 grams/ltr LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

Item Numbers: 27111-8264, 27111-8265, 27111-8266 Page 5 of 5