1402-55

9/11/2008

**MATERIAL SAFETY DATA SHEET** 

PRODUCT / MATERIAL: GLAZE

MANUFACTURER / DISTRIBUTOR: LAGUNA CLAY COMPANY

**ADDRESS** 14400 Lomitas Avenue, City of Industry, CA 91746

PHONE / FAX / EMAIL: (626) 330-0631 / (626) 333-7694 / MSDS@lagunaclay.com

### SECTION I - PRODUCT INFORMATION

TRADE NAME: EM1014 **DUTCH BLUE** SYNONYM: CHEMICA: FAMILY: Ceramic Blend

#### SECTION II - HAZARDOUS INGREDIENTS

INGREDIE: NAME	Maximum Percent	CAS NUMBER	OSHA PEL TWA: (mg/m3)	NIOSH REL TWA: (mg/m3)	ACGIH TLV TWA: (mg/m3)
Cobalt or Cabalt Compounds	0.18	7440-48-4	0.1		0.02
Silica, Crystalline (Quartz)	3	14808-60-7	10 mg/m3 / %SiO2 + 2	0.05	0.05
Zirconium : Zirconium Compounds	6	7440-67-7	5		5

#### SECTION III - PHYSICAL DATA

BOILING COINT (°F) Not Applicable VAPOR PELSSURE VAPOR DELISITY Not Applicable Not Applicable SOLUBI. 1 Y IN WATER SPECIFIC GRAVITY Insoluble 1.7 - 3.7

PERCENT LOLATILE BY WEIGHT EVAPORATION RATE 0

APPEARANCE AND ODOR Color varies between moist and dry state; no odor.

## **SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT Not Flammable

EXTINGUISHING MEDIA Water UNUSUAL FIRE OR EXPLOSION HAZARDS SPECIAL FIGHTING PROCEDURES None None

# SECTION V - REACTIVITY DATA

STABILITY FACTOR INCOMPACEBILITY Product is stable.

HAZARDOUS DECOMPOSITION PRODUCTS None. Hazardous polymerization will not occur.

CONDITIONS TO AVOID Inhalation of dust.

# SECTION VI - HEALTH HAZARD DATA

# Cobalt = Cobalt Compounds

Exposure to cobalt compounds may cause sensitization by inhalation and skin contact. Dust from handling can cause intation of nose and throat. Prolonged exposure could cause serious respiratory illness and lung damage. The titled persons may develop wheezing and shortness of breath. Can also cause an allergic skin rash in some individuals. Avoid breathing dust. Wash thoroughly after handling. Keep container closed. Use EM1014 Page 1 of 3

Page 1 of 3 Item Numbers: 30402-5586

9/11/200



**MATERIAL SAFETY DATA SHEET** 

with adequate ventilation.

Silica, Crystalline (Quartz)

A single exposure will not result in serious adverse health effects. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death. Crystalline silica (quartz) inhaled from occupational sources is classifie: as carcinogenic to humans. There are some studies that show excess numbers of cases of scleroners a and other connective tissue disorders in workers exposed to respirable crystalline silica. Silicos simpreases the risk of tuberculosis. There are some studies that show an increased incidence of chronic klaney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

◆ Zirconium or Zirconium Compounds

Skin, June granulomas; in animals: irritation skin, mucous membrane; X-ray evidence of retention in lungs.

PRIMARY ROUTES OF ENTRY: Inhalation (dry form only), ingestion and dermal.

SUMMARY OF FISKS: Individuals with a lung disease/condition (e.g.: bronchitis, emphysema,

chronic pulmonary disease) can be aggravated by exposure.

EMFROE LIVE I PST AID: No specific first aid is necessary since the adverse health effects

associated with this compound results from chronic exposures.

May be an irritant, flush eyes with generous amounts of water for at least 15 minutes; call a physician if irritation persists.

Skin Contact May cause local dermatitis, which is relieved when removed.

Ingestion Toxicity due to ingestion is low.

Impletion Remove to fresh air, call a physician if irritation due to inhalation persists.

Physician's Note None.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Spills or Place Procedure Follow normal clean-up procedures. Care should be taken to avoid causing

dust to become airborne. Vacuum or use wet clean-up techniques.

Waste Discussal Procedure Dispose material in accordance with Federal, State, and Local regulations.

## SECTION VIII - CONTROL MEASURES

Provide a request ventilation to keep dust or vapor concentrations below acceptable exposure limits. Use gloves as needed for handling material containers. Wear safety glasses when needed. Appropriate respirators protection may be required to protect from certain dusts. Respirators must be selected and used in accordance with OSHA Subpart 1 of (29 CFR 1910.134).

EM1014 Page 2 of 3

Item Numbers: 30402-5586 Page 2 of 3

9/11/2008

<u>aquaa</u>

**MATERIAL SAFETY DATA SHEET** 

### SECTION IX - TOXICOLOGICAL INFORMATION

This product (and all of it's components) is in compliance with the U.S. EPA 15 U.S. C.2604 regulation.

This product is certified as NON-TOXIC, and conforms to ASTMD-4236 and C-1023 under the federal Labeling of Hazardous Art Materials Act (LHAMA). Specific Toxicology information on materials is available upon request.

#### SECTION X - REGULATORY

This product may contain materials that are reportable under Section 313 of the Emergency Planning and Community Right-To-Know Act (Superfund Amendments and Reauthorization Act – SARA), and 40 CFR Part 272.

SAFO (It a III Data:

Cobalt or Cabalt Compounds < 0.18 %

These levels are "typical quantities" and may change slightly with different lots.

THIS PRODUCT CONTAINS SUBSTANCES REGULATED UNDER CALIFORNIA'S SAFE DRINKING WATER AND TOXIC ENFORCED TO ACT (PROPOSITION 65).

#### SECTION AT - DISCLAIMER

The information provided in this MSDS document has been provided to Laguna Clay Company by its material suppliers in discrepresented by those suppliers as accurate and reliable.

Lagene Could Dempany is not liable for injury, loss, or damage, direct or consequential, arising out of the use or  $m_1$  and  $m_2$  perly use this product. This product is intended only for use in traditional ceramic application  $m_2$ .

This MSDE conforms to the ASTM D-4236 and C-1023 requirements defined by LHAMA, the Federal Labeling of Hazardous Art Materials Act. LHAMA was developed by the American Society of Testing and Materials (ASTM) to ensure the proper labeling of art materials.

EM1014 Page 3 of 3

Item Numbers: 30402-5586 Page 3 of 3