

33504-XXXX**MATERIAL SAFETY DATA SHEET**

Product Name: Flexwax 120	Product Code: Flexwax
Manufacturer's Name: American Art Clay Co., Inc. 6060 Guion Road Indianapolis, IN 46254	
Information Number: (800) 374 - 1600	Emergency Number: (800) 374 - 1600

Section I – Product Identification

Product Name: Flexwax 120	Product Class: Craft	Product Size: 2 1/2lbs. 5lbs
Flexwax 120		

Section II – Hazardous Ingredients

Reportable Components	CAS#	Vapor Pressure Mm Hg @ Temp	Weight Percent
------------------------------	-------------	--	---------------------------

No report hazardous ingredients.

This product carries the "AP" Seal. Labeling conforms to ASTM D-4236.**Section III – Physical / Chemical Characteristics**

Boiling Range: NA	Specific Gravity (1120=1): Less than 2.
Vapor Density: Heavier than air.	Evaporation Rate: NA
Coating V.O.C.: NA	Material V.O.C.: NA
Appearance & Odor: Solid block.	

Section IV – Fire and Explosion Hazards

Flash Point: NA	Method Used: NA
Flammable Limits in Air by Volume: NA – Lower	NA – Upper
Extinguishing Media: Foam, CO2, and Dry Chemical Water Fog	
Special Firefighting Procedures: Use fire extinguisher – suitable for wax.	
Unusual Fire & Explosion Hazards: Keep away from heat, sparks, and open flame.	

Section V – Reactivity Data

Stability: Stable	Conditions to Avoid: Open flame
Incompatibility (Materials to Avoid): None.	
Hazardous Decomposition or Byproducts: Will not occur.	
Hazardous Polymerization: Will not occur.	

Page 2
Flexwax

Section VI – Health Hazards

Inhalation Health Risks and Symptoms of Exposure: Molten wax fumes cause mild (upper) respiratory irritation.

Skin and Eye Contact Health Risks and Symptoms of Exposure: Eye – Molten fumes may be slightly irritating to eyes. Skin – molten wax will cause burns on contact.

Skin Absorption Health Risks and Symptoms of Exposure: See above.

Ingestion Health Risks and Symptoms of Exposure: No hazardous ingredients.

Health Hazards (Acute / Chronic): See above.

Carcinogenicity: No – NTP Carcinogen No – IARC Monographs No – OSHA Regulated

Medical Conditions Generally Aggravated by Exposure: Unknown.

Emergency and First Aid Practices: Contact your local poison control for further health information.

Section VII – Precautions for Safe Handling and Use

Steps to Be Taken In Case Material Released or Spilled: Uncontaminated material may be salvaged and used. If contaminated, dispose.

Waste Disposal Method: Dispose of in trash. In manufacturing, dispose of in accordance to Local, State or Federal regulations.

Precautions to Be Taken in Handling and Storing: Store away from open flame.

Other Precautions: Wax melting should be done by adult. Temperature of melted wax should be measured with a thermometer and kept at 120°F in order to prevent breakdown of wax or risk of skin burns.

Section VIII – Control Measures

Respiratory Protection: Adequate cross ventilation necessary due to vapors.

Ventilation: Adequate cross ventilation due to vapors.

Protective Gloves: Not needed.

Eye Protection: Not needed.

Other Protective Clothing or Equipment: Not needed.

Work / Hygienic Practices: Refer to AMACO Product Encyclopedia & Safety Manual.

Page 3
Flexwax

Section IX – Disclaimer

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control we make no warranties, expressed or implied, except for those that may be contained in our written acknowledgement.

Prepared by: L. Jenkins
1/2012