

06/27/2013 15:55 FAX 920 930 5099

PACON

33505-1005



global assurance

Shanghai NOA Certification Co., Ltd.

33505-1005  
1020

## Material Safety Data Sheet

### Section 1 - Chemical Product and Company Identification

Sample Name: Plaster of Paris Bandage

Company Identification: Anji Hongde Medical Products Co., Ltd.

Mainland Address: Jingeon Village, Tianhuangping Town, Anji County,  
Zhejiang Province, China

Tel: +86 572 5885288

FAX: +86 572 5885285

Post Code: 313300

### Section 2 - Composition, information on Ingredients

Chemical Name	Percent (by weight)	CAS No.	EC No.
Plaster of paris	85%	10034-76-1	Not listed
Water	15%	7732-18-5	231-791-2

### Section 3 - Hazards Identification

#### EMERGENCY OVERVIEW

This product is not expected to produce any unusual hazards during normal use.

Target Organs: None

Hazard Sorts: None

Potential Health Effects:

- > Eye: No health effects are expected. If contact with plaster of paris's dust in mechanical processing, may cause mechanical irritation of eyes, if burning, redness, itching, pain or other symptoms persist or develop, consult physician.
- > Skin: Prolonged or repeated contact with the skin may cause irritation.
- > Ingestion: Unlikely to occur, but if ingest, may cause partial or complete intestinal blockage and gastric disturbances. See First Aid Measure-Ingestion.
- > Inhalation: No health effects are expected. Breathing plaster of paris in mechanical processing, may irritate eyes, skin, nose, throat, and upper respiratory tract.

Page 1 of 6

Shanghai NOA Certification Co., Ltd. (SNOA)

Tel: (021) 50810697 68766986 50810751

Email: REACH@shnoa.com.cn



Shanghai NQA Certification Co., Ltd.

#### Section 4 – First Aid Measures

- Eye:** If contact with eyes, flush with plenty of water. If irritation persists, consult physician.
- Skin:** No health effects are expected under normal use. If irritation or other symptoms are experienced, seek medical attention.
- Ingestion:** Ingestion of this material is unlikely. If it does occur, drinking gelatin solutions or large volumes of water and watch the person for several days to make sure that partial or complete intestinal blockage does not occur.
- Inhalation:** Inhalation of plaster of paris in mechanical processing, remove to fresh air. Leave the area of exposure and remain away until coughing and other symptoms subside. If rapid recovery does not occur, obtain medical attention.

#### Section 5 – Fire Fighting Measures

- General Information:** Not expected to burn.
- Extinguishing Media:** Water or use extinguish media appropriate for surrounding fire.
- Special Fire Fighting Procedures:** Wear appropriate personal protective equipment.

#### Section 6 – Accidental Release Measures

- General Information:** Use proper personal protective equipment as indicated in Section 8.
- Spills/Leaks:** Collect up, then place into a suitable container for disposal. In mechanical processing, avoid plaster of paris's dust generation, and avoid inhalation of dust and contact with eyes and skin.

#### Section 7 – Handling and Storage

- Storage:** Store in a cool, dry area away from heat, moisture and incompatibilities.
- Handling:** Use with appropriate ventilation. In mechanical processing, avoid dust contact with eyes, wear the appropriate eye protection against dust. Treat carefully, avoid physical damage. Avoid generation dust. Use

Page 2 of 6

Shanghai NQA Certification Co., Ltd. (SNQA)

Tel: (021) 50810607 68766986 50810753

Email: REACT@snqa.com.cn



Global Assurance

Shanghai NQA Certification Co., Ltd.

good safety and industrial hygiene practices.

### Section 8 - Exposure Controls/Personal protection

#### Exposure Limits:

TWA: 15(mg/m<sup>3</sup>) from OSHA(PEL) [United States] Inhalation Total.  
 TWA: 5(mg/m<sup>3</sup>) [Canada] Inhalation Respirable.  
 TWA: 10(mg/m<sup>3</sup>) from NIOSH [United States] Inhalation Total.  
 TWA: 5(mg/m<sup>3</sup>) from NIOSH [United States] Inhalation Respirable.  
 TWA: 5(mg/m<sup>3</sup>) from OSHA(PEL) [United States] Inhalation Respirable.  
 TWA: 5(mg/m<sup>3</sup>) [United Kingdom] Inhalation Respirable.  
 TWA: 10(mg/m<sup>3</sup>) [United Kingdom] Inhalation Total.  
 TWA: 10(mg/m<sup>3</sup>) from ACGIH(TLV) [United States] Inhalation Total.  
 TWA: 10 STEL: 20(mg/m<sup>3</sup>) [Canada] Inhalation Total.

Monitoring Methods: No information found.

Engineering Controls: Appropriate ventilation.

Personal Protective Equipment:

- Eyes: No special requirement. In mechanical processing, wear eye protection (safety glasses or goggles) to avoid possible eye irritation.
- Skin: No special requirement. In mechanical processing, wear gloves and protective clothing to prevent plaster of paris repeated or prolonged contact with skin.
- Clothing: No special requirement. Wear appropriate working clothing if necessary.
- Respirators: No special requirement. In mechanical processing use appropriate respirator or mask if a lot of dust generate.

Other Protection: No smoking or eating scene work. To maintain good health habits.

### Section 9 - Physical and Chemical Properties

Physical State: White bandet solid

Odor: Odorless

Molecular Formula: N/A

Molecular Weight: N/A

Specific Gravity/Density: N/A

pH: N/A

Viscosity: N/A

Boiling Point: N/A

Freezing/Melting point: N/A

Page 3 of 6

Shanghai NQA Certification Co., Ltd. (SNQA)

Tel: (021) 50810697 68766286 50810753

Email: RFA@sh-nqa.com.cn



Global Assurance

Shanghai NQA Certification Co., Ltd.

Ignition Temperature: N/A  
 Decomposition Temperature: N/A  
 Solubility: Insoluble in water

### Section 10 - Stability and Reactivity

**Chemical Stability:** Stable under normal condition.  
**Conditions to Avoid:** Contact with acids, water, high humidity, and incompatibles.  
**Incompatibilities with Other Materials:** Acids. Exposure to water and acids must be supervised because the reactions are vigorous and produce large amounts of heat.  
**Hazardous Decomposition Products:** calcium oxide (CaO), and sulfur dioxide (SO<sub>2</sub>).  
**Hazardous Polymerization:** Will not occur.

### Section 11 - Toxicological Information

**Toxicological Information:**  
 CAS No. 10034-76-1  
 - LD50: >5000mg/kg(oral, rat)  
 - LC50: Not available.  
**Carcinogenicity:** Not listed by ACGIH, IARC, NTP, or CA Prop 65.  
**Sensitization Rate:** Not available.  
**Teratogenicity:** Not available.

### Section 12 - Ecological Information

**Ecological Toxicity:** Not available.  
**Ecological Degradation:** Not available.  
**Abiology Degradation:** Not available.  
**Environment:** Not available.

### Section 13 - Disposal Considerations

Never discharge directly into sewers or surface waters. Additionally, waste generators must consult state and local hazardous waste regulations to ensure

Page 4 of 6

Shanghai NQA Certification Co., Ltd. (SNQA)

Tel: (021) 50810697 68766986 50810753

Email: RFACHT@snqa.com.cn