



Material Safety Data Sheet

Smooth-Cast® 325, 326 and 327

Date of Preparation: April 22, 2014

MSDS No. 488

Revision: 0013

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Smooth-Cast® 325, 326 and 327 Part A

General Use: Polyurethane Elastomer

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924
International 813-248-0585

Section 2- Hazards Identification

Hazard Designation:

Europe



Canada



HMIS	
H	2
F	1
R	1

+T: Toxic Xn: Harmful N: Dangerous for the environment

Risk Phrases pertaining to particular dangers

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R40: Limited evidence of a carcinogenic effect.

R48/20: Harmful; danger of serious damage to health by prolonged exposure through inhalation

R50/53: Very toxic to aquatic organisms may cause long term adverse effects in the aquatic environment.

R61: May cause harm to the unborn child.

R62: Possible risk of impaired fertility.

Classified according to Articles 6 & 7 of Directive 1999/45/EC

Section 3 - Composition / Information on Ingredients

Component	ACGIH TWA	OSHA PEL	Hazard Designation	Weight Percent (%)
Butyl benzyl phthalate CAS Number: 85-68-7 EINECS Number: 201-622-7	None Established	None Established	+T N	10-15
4,4' Methylene bis (phenylisocyanate) (MDI) CAS Number: 101-68-8 EINECS Number: 202-966-0	0.005 ppm	0.02 ppm	Xn	70-80

MSDS No. 488

Smooth-Cast® 325, 326 and 327

Revision: 0013

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and laundry before reuse; seek medical attention if rash develops.

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: 390°F (200°C)

Flash Point Method: COC

LEL: Not Established **UEL:** Not Established


Flammability Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: Hazardous decomposition products may be formed. Avoid water contamination in closed containers or confined areas as exothermic heat and carbon dioxide can evolve.

Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

**Section 6 - Accidental Release Measures**

Spill /Leak Procedures: Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Avoid moisture contamination. Reseal partial containers. Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

MSDS No. 488

Smooth-Cast® 325, 326 and 327

Revision: 0013

Section 8 - Exposure Controls / Personal Protection



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance : Pale amber liquid

Odor : Characteristic odor

Vapor Pressure: <0.00001 @ 25°C

Vapor Density (Air=1): 8.6

Specific Gravity (H₂O=1, at 4 °C): 1.14

Water Solubility: Reacts with water

Boiling Point: None determined

% Volatile: Nil

Freezing/Melting Point: None Determined

Viscosity: 0.64 poise

Evaporation Rate: Not Applicable

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can occur.

Chemical Incompatibilities: Strong bases, water, amines, alcohols.

Conditions to Avoid: Avoid contamination with water and other materials that react with Isocyanates.

Hazardous Decomposition Products: MDI vapors, hydrogen cyanide gas, oxides of nitrogen, carbon monoxide and carbon dioxide.

Section 11- Toxicological Information

Hazardous Component	LD50 Oral	LC50 Inhalation
4,4' Methylene bis(phenylisocyanate) (MDI)	Mouse: 2200 mg/kg Rat: 9200 mg/kg	Rat: 178 mg/m ³
Butyl Benzyl Phthalate	Rat: 20,400 mg/kg	Rat: >6.7 g/l for 4 hours.

Section 12 - Ecological Information

MDI: Aquatic: Rapidly hydrolyzes to form an insoluble crust. Terrestrial: Will bind with moist soil no leaching will occur. Atmospheric: Remains in the vapor phase and half life is 32 hours. Will not biodegrade.

Butyl Benzyl Phthalate: Biodegradable according to OECD.
Ecotoxicity in water: 1.1-1.7 mg/l (Fish)

MSDS No. 488

Smooth-Cast® 325, 326 and 327

Revision: 0013

Section 13 - Disposal Considerations**Disposal:** Must be disposed of in accordance with local regulations.**Section 14 - Transport Information**

DOT	IATA	IMDG
<u>55 Gallon Quantities or Greater</u> Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Butyl Benzyl Phthalate Mixture UN #: 3082 Hazard Class: 9 Label: Miscellaneous	<u>All Quantities</u> Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Butyl Benzyl Phthalate Mixture UN #: 3082 Hazard Class: 9 Label: Miscellaneous	<u>All Quantities</u> Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Butyl Benzyl Phthalate Mixture UN #: 3082 Hazard Class: 9 Label: Marine Pollutant

Section 15 - Regulatory Information**United States EPA Regulations:**

CERCLA Hazardous Substance (40 CFR 302.4) listed specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

<u>Chemical Name</u>	<u>RQ</u>	<u>% Reportable Component</u>
Butyl Benzyl Phthalate	100 lbs.	75.0 Max
4, 4' Methylene bis (phenylisocyanate)	5000 lbs.	15.0 Max

These products contain the following chemicals that are subject to release reporting requirements under **section 313 of SARA Title III.**

<u>Chemical Name</u>	<u>CAS #</u>	<u>% by Weight</u>
4, 4' Methylene bis (phenylisocyanate)	101-68-8	75.0 Max

Clean Air Act

SOCMI Chemical: 4, 4' Methylene bis(phenylisocyanate)

Hap Code: XOY

TSCA Inventory Status (40 CFR710): All components of these formulations are listed in the TSCA Inventory.

California Proposition 65: These products contain Butyl Benzyl Phthalate, which has been identified by the state of California to cause birth defects or other reproductive harm.

Canadian Regulations:WHMIS Identification: **D2A, D2B**CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **Listed on CDSL**




MSDS No. 488

Smooth-Cast® 325, 326 and 327

Revision: 0013

Section 15 - Regulatory Information (continued)

Labeling according to EEC Directive

Risk Phrases	Symbol(s) Required for EU Label	Safety Phrases
<p>R20: Harmful by inhalation.</p> <p>R36/37/38: Irritating to eyes, respiratory system and skin.</p> <p>R40: Limited evidence of a carcinogenic effect.</p> <p>R48/20: Harmful; danger of serious damage to health by prolonged exposure through inhalation</p> <p>R50/53: Very toxic to aquatic organisms may cause long term adverse effects in the aquatic environment.</p> <p>R61: May cause harm to the unborn child.</p> <p>R62: Possible risk of impaired fertility.</p>	<p></p> <p>+T: Toxic</p> <p></p> <p>Xn: Harmful</p> <p></p> <p>N: Dangerous for the environment</p>	<p>S2: Keep out of reach of children.</p> <p>S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</p> <p>S28: After contact with skin, wash immediately with plenty of soap-suds.</p> <p>S36/37/39: Wear suitable protective clothing, gloves and eye and face protection.</p> <p>S45: In case of accident or if you feel ill, seek medical advice immediately.</p> <p>S53: Avoid exposure.</p> <p>S60: This material and container must be disposed as hazardous waste.</p> <p>S61: Avoid release to the environment. (See MSDS).</p>

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.



Material Safety Data Sheet

Smooth-Cast® 325, 326 and 327

MSDS No. 488

Date of Preparation: April 22, 2014

Revision: 0013

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Smooth-Cast® 325, 326 and 327 Part B

General Use: Polyurethane Elastomer

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924

International 813-248-0585

Section 2- Hazards Identification

Potential Health Effects

Hazard Designation

Europe



Xn = Harmful

Canada



HMIS	
H	2
F	1
R	0

Risk Phrases pertaining to particular dangers:

R20/21/22: Harmful by inhalation, contact with skin and if swallowed.

R33: Danger of cumulative effects.

R52/R53: Harmful to aquatic organisms may cause long-term adverse effects in the aquatic environment

Classified according to Articles 6 & 7 of Directive 1999/45/EC

Section 3 - Composition / Information on Ingredients

Component	ACGIH TWA	OSHA PEL	Hazard Designation	Weight Percent (%)
Polyol /Plasticizer Blend (Non-Hazardous)	None Established	None Established	None	99.5- 99.7
Phenylmercuric neodecanoate CAS No: 26545-49-3 EC No: 247-783-7 (Smooth-Cast 326 and Smooth-Cast 327 only)	None Established	None Established	Xn	<0.50

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse; seek medical attention if rash develops.

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately

After first aid, get appropriate in-plant, paramedic, or community medical support.

MSDS No. 488

Smooth-Cast® 325, 326 and 327

Revision: 0013

Section 5 - Fire-Fighting Measures

Flash Point: >300 °F (150°C)

Flash Point Method: COC

LEL: Not Established **UEL:** Not Established


Flammability Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: Hazardous decomposition products may be formed. Avoid water contamination in closed containers or confined areas as exothermic heat and carbon dioxide can evolve.

Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.



Section 6 - Accidental Release Measures

Spill /Leak Procedures: Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Avoid moisture contamination. Reseal partial containers. Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

MSDS No. 488

Smooth-Cast® 325, 326 and 327

Revision: 0013

Section 9 - Physical and Chemical Properties

Physical State: Liquid	Water Solubility: Negligible:
Appearance: Clear liquid	Boiling Point: None (Polymeric Resin)
Odor: Mild odor	% Volatile: Nil
Vapor Pressure: None (Polymeric Resin)	Freezing/Melting Point: None Determined
Vapor Density (Air=1): >1	Viscosity: 1.76 poise
Specific Gravity (H₂O=1, at 4 °C): 1.00	Evaporation Rate: None (Polymeric Resin)

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can not occur.

Chemical Incompatibilities: Strong acids and oxidizers.

Conditions to Avoid: Avoid contamination with water and other materials that react with amines.

Thermal Decomposition Products: Oxides of nitrogen, carbon monoxide and carbon dioxide.

Section 11- Toxicological Information

Toxicity Data:

Acute Inhalation Effects: None Established	Reproductive Toxicity: None Established
Acute Oral Effects: None Established	Mutagenicity: None Established
	Teratogenicity: None Established
	Sensitization: None Established

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations

Disposal: These materials must be disposed of in accordance with applicable Federal, state and local regulations.

Section 14 - Transport Information

DOT	IATA	IMDG
Not Regulated	Not Regulated	Not Regulated

Section 15 - Regulatory Information

United States EPA Regulations:

SARA Toxic Chemical (40 CFR 372.65): This product contains the following chemicals that are subject to release reporting requirements under section 313 of SARA Title III.

<u>Components That Require Reporting</u>	<u>RQ</u>	<u>% of Reportable Component</u>
Mercury (as part of catalyst)	1 lb.	0.074

TSCA Inventory Status (40 CFR 710): All components of these products are listed on the TSCA inventory.

MSDS No. 488

Smooth-Cast® 325, 326 and 327

Revision: 0013

California Proposition 65: These products contain a mercury compound, which has been identified by the state of California to cause birth defects or other reproductive harm.

Section 15 - Regulatory Information (continued)

Canadian Regulations;

WHMIS Identification: **D2A, D2B**

CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **Listed on CDSL**



Labeling according to EEC Directive:

Only for Smooth Cast 326 Part B and Smooth Cast 327 Part B

R20/21/22: Harmful by inhalation, contact with skin and if swallowed.

R33: Danger of cumulative effects.

R52/R53: Harmful to aquatic organisms may cause long-term adverse effects in the aquatic environment.



Xn = Harmful

S1/2: Keep locked up and out of reach of children.

S3: Keep in a cool place.

S28: After contact with skin, wash immediately with plenty of soap and water.

S35: This material and its container must be disposed of in a safe way.

S45: In case of an accident or if you feel sick, seek medical attention

S61: Avoid release to the environment. (See MSDS).

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.