

P.1  
34105-1009

## MATERIAL SAFETY DATA SHEET

Page 001  
Date Prepared: 10/14/03-----  
1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATIONProduct Name: Glasspro Low Odor Cutting Oil  
General or Generic ID: ALIPHATIC HYDROCARBONCompany: Creative Craftsmen Co., Inc.  
Warrenville, IL 60555-3838  
Medical Emergency Telephone Number: 1-888-215-4878-----  
2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
ALIPHATIC PETROLEUM DISTILLATES	64742-47-8	100.0

-----  
3. HAZARDS IDENTIFICATION

## Potential Health Effects

## Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

## Skin

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Additional symptoms of skin contact may include: skin blistering.

P.E

**MATERIAL SAFETY DATA SHEET**

Page 002

Date Prepared: 10/14/03

Glaspro Low Odor Cutting Oil

**Swallowing**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

**Inhalation**

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

**Symptoms of Exposure**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways), lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), loss of coordination, confusion, irregular heartbeat, narcosis (dazed or sluggish feeling), convulsions, coma.

**Target Organ Effects**

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, kidney damage.

**Developmental Information**

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

**Cancer Information**

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration. This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

Continued on next page

P.3

**MATERIAL SAFETY DATA SHEET**

Page 003

Date Prepared: 10/14/03

**Glasspro Low Odor Cutting Oil**

-----  
**Other Health Effects**  
No data

**Primary Route(s) of Entry**  
Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

-----  
**4. FIRST AID MEASURES**

**Eyes**  
If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

**Skin**  
Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Swallowing**  
Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**Inhalation**  
If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

**Note to Physicians**  
Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), kidney. Exposure to this material may aggravate any preexisting condition sensitive to a  
Continued on next page

P.4

## MATERIAL SAFETY DATA SHEET

Page 004  
Date Prepared: 10/14/03

## Glasspro Low Odor Cutting Oil

decrease in available oxygen, such as chronic lung disease,  
coronary artery disease or anemias.

## 5. FIRE FIGHTING MEASURES

Flash Point  
65.5 - 73.8 C (150.0 - 165.0 F) TCC

Explosive Limit  
(for product) Lower .6 Upper 7.0 %

Autoignition Temperature  
215.5 C (420.0 F)

Hazardous Products of Combustion  
May form: aldehydes, carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards  
Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media  
regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions  
Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

Continued on next page

P.5

**MATERIAL SAFETY DATA SHEET**

Page 005  
Date Prepared: 10/14/03

Glasspro Low Odor Cutting Oil

**NFPA Rating**  
Health - 0, Flammability - 2, Reactivity - 0

**NFPA 30 Classification**  
Combustible Liquid Class IIIA

**6. ACCIDENTAL RELEASE MEASURES**

**Small Spill**  
Absorb liquid on vermiculite, floor absorbent or other absorbent material.

**Large Spill**  
Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Per good environmental management practices, prevent run-off to sewers, streams and other bodies of water. Stop spill at the source. Cover sewer grates and dike the spill. Absorb spilled material on to absorbents. Shovel materials into container. Close container tightly and dispose of properly.

**7. HANDLING AND STORAGE**

**Handling**  
Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers, including tank cars and tank trucks, should be grounded and/or bonded when material is transferred. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Warning. Sudden release of hot organic chemical vapors  
Continued on next page

P.6

**MATERIAL SAFETY DATA SHEET**

Page 006  
Date Prepared: 10/14/03

**Glasspro Low Odor Cutting Oil**

or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Eye protection**

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

**Skin Protection**

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory Protections**

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

**Engineering Controls**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

**Exposure Guidelines****Component**

ALIPHATIC PETROLEUM DISTILLATES (64742-47-8)  
ACGIH TLV 200.000 mg/m3 - TWA (Skin)

Continued on next page

P.7

**MATERIAL SAFETY DATA SHEET**Page 007  
Date Prepared: 10/14/03

Glasspro Low Odor Cutting Oil

**9. PHYSICAL AND CHEMICAL PROPERTIES****Boiling Point**  
(for product) 187.7 - 287.7 C (370.0 - 550.0 F ) @ 760 mmHg**Vapor Pressure**  
(for product) .010 mmHg @ 68.00 F**Specific Vapor Density**  
> 5.000 @ AIR-1**Specific Gravity**  
.804 - .815 @ 60.00 F**Liquid Density**  
6.700 lbs/gal @ 60.00 F  
.804 kg/l @ 16.00 C**Percent Volatiles**  
100.0 %**Volatile Organic Compounds (VOC)**  
100.000 %  
804.000 g/l  
6.700 lbs/gal**Evaporation Rate**  
< .10 (N-BUTYL ACETATE )**Appearance**  
COLORLESS TRANSPARENT LIQUID**State**  
LIQUID**Physical Form**  
HOMOGENEOUS SOLUTION**Color**  
CLEAR & COLORLESS

Continued on next page

P.8

**MATERIAL SAFETY DATA SHEET**

Page 008

Date Prepared: 10/14/03

Glasspro Low Odor Cutting Oil

**Odor**

MILD PARAFFIN

**pH**

Not applicable

**Freezing Point**

-42.7 C (-45.0 F)

**Solubility in Water**

LESS THAN 0.01

**Bulk Density**.900 lbs/ft<sup>3</sup>**10. STABILITY AND REACTIVITY****Hazardous Polymerization**

Product will not undergo hazardous polymerization.

**Hazardous Decomposition**

May form: aldehydes, carbon dioxide and carbon monoxide, various hydrocarbons.

**Chemical Stability**

Stable.

**Incompatibility**

Avoid contact with: chlorine, hypochlorites, strong oxidizing agents.

**11. TOXICOLOGICAL INFORMATION****LD 50 and LC 50 Data**

PETROLEUM DISTILLATES (CAS# 64742-47-8)

Oral LD50 (rat): &gt;8000 mg/kg

Dermal LD50 (rabbit): &gt;4000 mg/kg

Inhalation LC50 (rat, 4 hour): &gt;2500 ppm

Continued on next page



P.9

**MATERIAL SAFETY DATA SHEET**

Page 009  
Date Prepared: 10/14/03

**Glasspro Low Odor Cutting Oil****12. ECOLOGICAL INFORMATION**

No data

**13. DISPOSAL CONSIDERATION****Waste Management Information**

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution Company, IC66 Environmental Services Group at 800-637-7922.

**14. TRANSPORTATION INFORMATION****TDG Information**

TDG Description:  
NOT REGULATED BY T.D.G.

Container/Mode  
55 GAL DRUM/TRUCK PACKAGE

NOS Component:  
None

**Other Transportation Information**

The Transport Information may vary with the container and mode of shipment.

**15. REGULATORY INFORMATION**

Canada

**WHMIS Classification**

Class A - Compressed Gas

Does not meet criteria

Continued on next page

P.10

**MATERIAL SAFETY DATA SHEET****Page 010  
Date Prepared: 10/14/03****Glasspro Low Odor Cutting Oil**

---

**Class B - Flammable & Combustible Material****B3 - Flammable and combustible material - Combustible liquid****Class C - Oxidizing Material****Does not meet criteria****Class D - Poisonous & Infectious - Division 1****Does not meet criteria****Class D - Poisonous & Infectious - Division 2****Does not meet criteria****Class E - Corrosive Material****Does not meet criteria****Class F - Dangerously Reactive Material****Does not meet criteria****This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.****DSL (Domestic Substance List) Status****DSL (CANADA) The intentional ingredients of this product are listed.****International Regulations****Inventory Status****AICS (AUSTRALIA) The intentional ingredients of this product are listed.****ECL (SOUTH KOREA) The intentional ingredients of this product are listed.****EINECS (EUROPE) The intentional ingredients of this product are listed.****ENCS (JAPAN) The intentional ingredients of this product are listed.****IECSC (CHINA) The intentional ingredients of this product are listed.****PICCS (PHILIPPINES) The intentional ingredients of this product are listed.****Continued on next page**

P.11

**MATERIAL SAFETY DATA SHEET**

Page 011  
Date Prepared: 10/14/03

**Glasspro Low Odor Cutting Oil**

---

listed.  
TSCA (UNITED STATES) The intentional ingredients of this product are listed.

---

**16. OTHER INFORMATION**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last Page

**MATERIAL SAFETY DATA SHEET****Product Name: AMACO Kiln Wash** **Product Code: Wash****Manufacturer's Name: American Art Clay Co., Inc.**  
6060 Guion Road  
Indianapolis, IN 46254**Information Number: (800) 374-1600****Emergency Number: (800) 374-1600****Section I – Product Identification****Product Name: AMACO Kiln Wash** **Product Class: Formulated** **Product Size: 11b, 4lbs & 40lbs****AMACO Kiln Wash****Section II – Hazardous Ingredients**

<b>Reportable Components</b>	<b>CAS #</b>	<b>Vapor Pressure Mm Hg @ Temp</b>	<b>Weight Percent</b>
------------------------------	--------------	--	---------------------------

No reportable quantities hazardous ingredients are present.

No hazardous ingredients. This product carries the "AP" seal for the 11b. and 4lbs. containers and carries the "CL Seal" for the 40lbs. Labeling conforms to ASTM D4236/LHAMA.

**Section III – Physical / Chemical Characteristics**

<b>Boiling Range: NA</b>	<b>Specific Gravity (H2O=1): Less than 2.</b>
<b>Vapor Density: Heavier than air.</b>	<b>Evaporation Rate: NA</b>
<b>Coating V.O.C.: NA</b>	<b>Material V.O.C.: NA</b>
<b>Appearance and Odor: Dry.</b>	

**Section IV \_ Fire and Explosion Hazard Data**

<b>Flash Point: NA</b>	<b>Method Used: NA</b>
<b>Flammable Limits in Air by Volume: NA – Lower</b>	<b>NA – Upper</b>
<b>Extinguishing Media: NA</b>	
<b>Special Firefighting Procedures: None. No fire hazard.</b>	
<b>Unusual Fire and Explosion Hazards: None. No fire hazard.</b>	

**Section V – Reactivity Data**

<b>Stability: Stable</b>	<b>Conditions To Avoid: None</b>
<b>Incompatibility (Materials to Avoid): None</b>	
<b>Hazardous Decomposition or Byproducts: Will not occur.</b>	
<b>Hazardous Polymerization: Will not occur</b>	

Product Code: Wash  
Page 2

#### Section VI Health Hazard Data

**Inhalation Health Risks and Symptoms of Exposure:** None.

**Skin and Eye Contact Health Risks and Symptoms of Exposure:** Eye – rinse thoroughly with water for 15 minutes. If irritation persists, contact physician. Skin – wash hands with soap and water after use.

**Skin Absorption Health Risks and Symptoms of Exposure:** None.

**Ingestion Health Risks and Symptoms of Exposure:** No hazardous ingredients.

**Health Hazards (Acute / Chronic):** No hazardous ingredients.

**Carcinogenicity:** NTP Carcinogen – No IARC Monographs – No OSHA Regulated – NO

**Medical Conditions Generally Aggravated by Exposure:** Unknown.

**Emergency and First Aid Procedures:** Contact your local poison Control for further health information.

---

#### Section VII – Precautions for Safe Handling and Use

**Steps to Be Taken In Case Material Is Released or Spilled:** Specific steps not necessary.

**Waste Disposal Method:** Dispose of contaminated material in trash. In manufacturing, dispose of in accordance to Local, State or Federal regulations.

**Precautions to Be Taken in Handling and Use:** No specific steps necessary.

**Other Precautions:** Do not create dust.

---

#### Section VIII – Control Measures

**Respiratory Protection:** Not needed.

**Ventilation:** Not needed.

**Protective Gloves:** Not needed.

**Eye Protection:** Not needed.

**Other Protective Clothing or Equipment:** Not needed.

**Work / Hygienic Practices:** Refer to AMACO Product Encyclopedia and Safety Manual.

---

#### Section IX – Disclaimer

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control we make no warranties, expressed or implied, except for those that may be contained in our written acknowledgement.

Prepared by: L. Jenkins  
1/2015