



Material Safety Data Sheet

Rebound 25

Date Of Preparation: April 5, 2012

MSDS No. 868

Revision: 0003

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Rebound 25 Part A
General Use: Silicone Elastomer
Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
 Phone (610) 252-5800, FAX (610) 252-6200
Emergency Contact: Chem-Tel
 Domestic 800-255-3924
 International 813-248-0585

Section 2- Hazards Identification

Not hazardous according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Council directive 1999/45/EC and its subsequent amendments.

HMIS	
H	1
F	1
R	0

Section 3 - Composition / Information on Ingredients


No hazardous ingredients

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air.
Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.
Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse.
Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately
After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: >300 °F
Flash Point Method: PMCC
LEL: Not Established
UEL: Not Established
Flammability Classification: Non-Flammable
Extinguishing Media: Dry Chemical, Carbon Dioxide, and Foam
Unusual Fire or Explosion Hazards: None
Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.
Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.



MSDS No. 868

Rebound 25

Revision: 0003

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Dike and contain spill; absorb or scrape up excess into suitable container for disposal. Stop or reduce discharge if it can be done safely.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standard EN 149; wear an MSHA/NIOSH or European Standard EN149 approved respirator.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Viscous Liquid
Appearance : Off White viscous liquid
Odor : Sweet odor
Vapor Pressure: None (Polymeric Resin)
Vapor Density (Air=1): >1
Specific Gravity (H₂O=1, at 4 °C): 1.17

Water Solubility: Insoluble
Boiling Point: None (Polymeric Resin)
% Volatile: Nil
Freezing/Melting Point: None (Polymeric Resin)
Viscosity: 300 poise
Evaporation Rate: Not Applicable

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can not occur.

Chemical Incompatibilities: Strong bases, and acids.

Hazardous Decomposition Products: Silica, carbon monoxide and carbon dioxide

MSDS No. 868

Rebound 25

Revision: 0003

Section 11- Toxicological Information

Eye Effects: Irritation
Skin Effects: Irritation

Carcinogenicity: None Determined
Mutagenicity: None Determined
Teratogenicity: None Determined

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations**Disposal:** Must be disposed of in accordance with applicable Federal, state and local regulations.**Section 14 - Transport Information**

DOT
Not Regulated

IATA
Not Regulated

IMDG
Not Regulated

Section 15 - Regulatory Information**United States Regulations****EPA Regulations:**

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

SARA Toxic Chemical (40 CFR 372.65): None

These products do not contain chemicals that are subject to release reporting requirements under **section 313 of SARA Title III.**

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

California Proposition 65: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

CANADA RegulationsWHMIS Identification: **Not controlled**CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **All are Listed****Labeling according to EEC Directive**

No special packaging or labeling requirements.

MSDS No. 868

Rebound 25

Revision: 0003

Section 16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.



Material Safety Data Sheet

Rebound 25

Date Of Preparation: April 5, 2012

MSDS No. 868

Revision: 0003

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Rebound 25 Part B
General Use: Silicone Elastomer
Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
 Phone (610) 252-5800, FAX (610) 252-6200
Emergency Contact: Chem-Tel
 Domestic 800-255-3924
 International 813-248-0585

Section 2- Hazards Identification

Not hazardous according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Council directive 1999/45/EC and its subsequent amendments.

HMIS	
H	1
F	1
R	0

Section 3 - Composition / Information on Ingredients


No hazardous ingredients

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air.
Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.
Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse.
Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately
After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: >300 °F
Flash Point Method: PMCC
LEL: Not Established
UEL: Not Established
Flammability Classification: Non-Flammable
Extinguishing Media: Dry Chemical, Carbon Dioxide, and Foam
Unusual Fire or Explosion Hazards: None
Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.
Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.



MSDS No. 868

Rebound 25

Revision: 0003

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Dike and contain spill; absorb or scrape up excess into suitable container for disposal. Stop or reduce discharge if it can be done safely.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standard EN 149; wear an MSHA/NIOSH or European Standard EN149 approved respirator.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Viscous Liquid

Appearance : Orange viscous liquid

Odor : Sweet odor

Vapor Pressure: None (Polymeric Resin)

Vapor Density (Air=1): >1

Specific Gravity (H₂O=1, at 4 °C): 1.17

Water Solubility: Insoluble

Boiling Point: None (Polymeric Resin)

% Volatile: Nil

Freezing/Melting Point: None (Polymeric Resin)

Viscosity: 300 poise

Evaporation Rate: Not Applicable

Section 10 - Stability and Reactivity

Stability: This product are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can not occur.

Chemical Incompatibilities: Strong bases, and acids.

Hazardous Decomposition Products: Silica, carbon monoxide and carbon dioxide

MSDS No. 868

Rebound 25

Revision: 0003

Section 11- Toxicological Information

Eye Effects: Irritation
Skin Effects: Irritation

Carcinogenicity: None Determined
Mutagenicity: None Determined
Teratogenicity: None Determined

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations**Disposal:** Must be disposed of in accordance with applicable Federal, state and local regulations.**Section 14 - Transport Information**

DOT
Not Regulated

IATA
Not Regulated

IMDG
Not Regulated

Section 15 - Regulatory Information**United States Regulations****EPA Regulations:**

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

SARA Toxic Chemical (40 CFR 372.65): None

These products do not contain chemicals that are subject to release reporting requirements under **section 313 of SARA Title III.**

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

California Proposition 65: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

CANADA RegulationsWHMIS Identification: **Not controlled**CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **All are Listed****Labeling according to EEC Directive**

No special packaging or labeling requirements.

MSDS No. 868

Rebound 25

Revision: 0003

Section 16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.



Material Safety Data Sheet

Smooth-Cast 300 Series

MSDS No. 476

Date of Preparation: April 5, 2012

Revision: 0010

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Smooth-Cast 300, 300Q, 305 and 310 Part A

General Use: Polyurethane Elastomer

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel
Domestic 800-255-3924
International 813-248-0585

Section 2 - Hazards Identification

Hazard Designation:

Europe



Xn = Harmful

Canada



HMIS	
H	2
F	1
R	1

Information pertaining to particular dangers

R20: Harmful by inhalation

R36/37/38: Irritating to eyes, respiratory system and skin

R40: Limited evidence of a carcinogenic effect

R48/20: Harmful; danger of serious damage to health by prolonged exposure through inhalation

Classified according to Articles 6 & 7 of Directive 1999/45/EC

Section 3 - Composition / Information on Ingredients

Component	ACGIH TWA	OSHA PEL	Hazard Designation	Weight Percent (%)
4,4' Methylene bis(phenylisocyanate) (MDI) CAS Number: 101-68-8 EINECS Number: 202-966-0	0.005 ppm	0.02 ppm	Xn	55-60

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse; seek medical attention if rash develops.


Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately

After first aid, get appropriate in-plant, paramedic, or community medical support.

MSDS No. 476

Smooth-Cast 300 Series

Revision: 0010

Section 5 - Fire-Fighting Measures**Flash Point:** 262 °F (128 °C)**Flash Point Method:** COC**LEL:** Not Established**UEL:** Not Established**Flammability Classification:** Non-Flammable**Extinguishing Media:** Water Fog, Dry Chemical, and Carbon Dioxide Foam**Unusual Fire or Explosion Hazards:** Hazardous decomposition products may be formed. Avoid water contamination in closed containers or confined areas as exothermic heat and carbon dioxide can evolve.**Fire-Fighting Instructions:** Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.**Fire-Fighting Equipment:** Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.**Section 6 - Accidental Release Measures****Spill /Leak Procedures:** Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.**Section 7 - Handling and Storage****Handling Precautions:** Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Avoid moisture contamination. Reseal partial containers. Use good general housekeeping procedures.**Storage Requirements:** Store in cool dry, well-ventilated area.**Section 8 - Exposure Controls / Personal Protection****Respiratory Protection:** Follow OSHA respirator regulations 29 CFR 1910.134 and European Standard EN 149; wear an MSHA/NIOSH or European Standard EN149 approved respirator.**Protective Clothing/Equipment:** Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics

MSDS No. 476

Smooth-Cast 300 Series

Revision: 0010

Section 9 - Physical and Chemical Properties

Physical State: Liquid	Water Solubility: Reacts with water
Appearance : Pale amber liquid	Boiling Point: None determined
Odor : Characteristic odor	% Volatile: Nil
Vapor Pressure: <0.00001 @ 25 °C	Freezing/Melting Point: None Determined
Vapor Density (Air=1): 8.6	Viscosity: 1 poise
Specific Gravity (H₂O=1, at 4 °C): 1.10	Evaporation Rate: Not Applicable

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can occur.

Chemical Incompatibilities: Strong bases, water, amines, alcohols.

Conditions to Avoid: Avoid contamination with water and other materials that react with Isocyanates.

Hazardous Decomposition Products: MDI vapors, hydrogen cyanide gas, oxides of nitrogen, carbon monoxide and carbon dioxide

Section 11- Toxicological Information

Hazardous Component	LD50 Oral	LC50 Inhalation
4,4' Methylene bis(phenylisocyanate) (MDI)	Mouse: 2200 mg/kg Rat: 9200 mg/kg	Rat: 178 mg/m ³

Section 12 - Ecological Information

For MDI:

Aquatic: Rapidly hydrolyzes to form an insoluble crust. Terrestrial: Will bind with moist soil no leaching will occur. Atmospheric: Remains in the vapor phase and half life is 32 hours. Will not biodegrade.

Section 13 - Disposal Considerations

Disposal: These materials must be disposed of in accordance with local regulations.

Section 14 - Transport Information

DOT	IATA	IMDG
Not Regulated	Not Regulated	Not Regulated

Section 15 - Regulatory Information

United States EPA Regulations:

Clean Air Act

SOCMI Chemical: 4, 4' Methylene bis(phenylisocyanate)

Hap Code: XOV

These products contain the following chemicals that are subject to release reporting requirements under **section 313 of SARA Title III.**

<u>Chemical Name</u>	<u>CAS #</u>	<u>% by Weight</u>
4, 4' Methylene bis(phenylisocyanate)	101-68-8	60.0 Max

MSDS No. 476

Smooth-Cast 300 Series

Revision: 0010

Section 15 - Regulatory Information (Continued)

TSCA Inventory Status (40 CFR710): All components of these formulations are listed in the TSCA Inventory.


California Proposition 65: These products do not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

Canadian Regulations;

WHMIS Identification: **D2A, D2B**

CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **Listed on CDSL**

**Labeling according to EEC Directive**

Risk Phrases	Symbol(s) Required for EU Label	Safety Phrases
R20: Harmful by inhalation R36/37/38: Irritating to eyes, respiratory system and skin R40: Limited evidence of a carcinogenic effect R48/20: Harmful; danger of serious damage to health by prolonged exposure through inhalation	 (Xn = Harmful)	S1/2: Keep locked up and out of reach of children S23: Do not breath vapors S36/37: Wear suitable protective equipment. S45: In case of an accident or if you feel sick , seek medical attention

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives



Material Safety Data Sheet

Smooth-Cast 300 Series

MSDS No. 476

Date of Preparation: April 5, 2012

Revision: 0010

Section 1 - Chemical Product and Company Identification

Product/Chemical Name Smooth-Cast 300, 300Q, 305 and 310 Part B

General Use: Polyurethane Elastomer

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924
International 813-248-0585

Section 2- Hazards Identification

Not hazardous according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and Council directive 1999/45/EC and its subsequent amendments

HMIS	
H	1
F	1
R	0

Section 3 - Composition / Information on Ingredients

No hazardous ingredients

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse.

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: 262 °F (128 °C)

Flash Point Method: PMCC


Flammability Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None

Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.



MSDS No. 476

Smooth-Cast 300 Series

Revision: 0010

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Dike and contain spill; absorb or scrape up excess into suitable container for disposal. Stop or reduce discharge if it can be done safely.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standard EN 149; wear an MSHA/NIOSH or European Standard EN149 approved respirator.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics

Section 9 - Physical and Chemical Properties

Physical State: Liquid	Water Solubility: Negligible:
Appearance: Clear colorless liquid	Boiling Point: None (Polymeric Resin)
Odor: Mild odor	% Volatile: Nil
Vapor Pressure: None (Polymeric Resin)	Freezing/Melting Point: None Determined
Vapor Density (Air=1): >1	Viscosity: 1.2 poise
Specific Gravity (H₂O=1, at 4 °C): 1.00	Evaporation Rate: None (Polymeric Resin)

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can not occur.

Chemical Incompatibilities: Strong acids and oxidizers.

Conditions to Avoid: Avoid contamination with water and other materials that react with amines.

Thermal Decomposition Products: Oxides of nitrogen, carbon monoxide and carbon dioxide

MSDS No. 476

Smooth-Cast 300 Series

Revision: 0010

Section 11- Toxicological Information

Acute Inhalation Effects: None established
Acute Oral Effects: None Established

Toxicity Data:

Reproductive Toxicity: None Established
Mutagenicity: None Established
Teratogenicity: None Established
Sensitization: None Established

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations

Disposal: These materials must be disposed of in accordance with applicable local regulations.

Section 14 - Transport Information

DOT
Not Regulated

IATA
Not Regulated

IMDG
Not Regulated

Section 15 - Regulatory Information

US TSCA Inventory Status (40 CFR 710): All components of these product sare listed on the TSCA inventory.

California Proposition 65: These products do not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm

WHMIS Identification: **Not controlled**

CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **All are Listed**

Labeling according to EEC Directive

No special packaging or labeling requirements

MSDS No. 476

Smooth-Cast 300 Series

Revision: 0010

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives



Material Safety Data Sheet

Sonite Wax

MSDS No. 915

Date of Preparation: February 22, 2012

Revision: 0011

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Sonite Wax

General Use: Release Agent

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924

International 813-248-0585

Section 2 - Hazards Identification

Hazard Designation:

Europe



Xn: Harmful

Canada



HMIS	
H	1
F	2
R	0

Risk phrases pertaining to particular dangers:

R53: May cause long term adverse effects in the aquatic environment

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking

Classified according to Articles 6 & 7 of Directive 1999/45/EC

Section 3 - Composition / Information on Ingredients

Component	ACGIH TWA	OSHA PEL	Hazard Designation	Weight Percent (%)
Alkanes, C9-12-iso- CAS Number: 90622-57-4 EINECS Number: 292-459-0	None Established	None Established	Xn	70-75%

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.


Ingestion: Ingestion is unlikely route of exposure. Do not induce vomiting unless instructed by a physician.

After first aid, get appropriate in-plant, paramedic, or community medical support.

MSDS No. 915

Sonite Wax

Revision: 0011

Section 5 - Fire-Fighting Measures**Flash Point:** >104 °F (>40 °C)**Flammable Limits:** LEL: 1.2 Note: Approximate
UEL: 9.6 Note: Approximate**Flash Point Method:** TCC**Autoignition Temperature:** 559° F (293° C) Note: Approximate**Flammability Classification:** Flammable Liquid**Extinguishing Media:** Water Fog, Dry Chemical, and Carbon Dioxide Foam**Unusual Fire or Explosion Hazards:** None**Fire and Explosion Hazards:** Vapors confined in a poorly ventilated area may be ignited by a spark or flame. Vapors may travel considerable distances to source of ignition. Vapors are heavier than air and may accumulate in low areas. Containers may rupture or explode under fire conditions. Hazardous decomposition products may be formed. Material can accumulate static charges, which can cause an incendiary electrical discharge. Empty containers retain product residue and can be dangerous.**Fire-Fighting Instructions:** Use dry chemical, foam or CO₂; water may be ineffective but should be used to keep containers cool.**Fire-Fighting Instructions:** Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.**Fire-Fighting Equipment:** Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.**Section 6 - Accidental Release Measures****Spill /Leak Procedures:** Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.**Section 7 - Handling and Storage****Handling Precautions:** Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Avoid moisture contamination. Reseal partial containers. Use good general housekeeping procedures.**Storage Requirements:** Store in cool dry, well-ventilated area.**Section 8 - Exposure Controls / Personal Protection****Respiratory Protection:** Follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.**Protective Clothing/Equipment:** Wear chemically protective gloves and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

MSDS No. 915

Sonite Wax

Revision: 0011

Section 8 - Exposure Controls / Personal Protection (continued)

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 – Physical and Chemical Properties

Product Form: Soft Paste	Water Solubility: Insoluble
Appearance and Odor: Yellow, slight ethereal odor	Boiling Point: >311 °F (155 °C)
Specific Gravity: 0.78	Evaporation Rate (BuAc=1): 0.16

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature.

Polymerization: Hazardous polymerization cannot occur.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce; carbon monoxide, carbon dioxide and hydrocarbons.

Section 11- Toxicological Information

Hazardous Component	LD50 Oral	LC50 Skin
Alkanes, C9-12-iso-	10000 mg/kg	3160 mg/kg

Section 12 - Ecological Information**Ecotoxicity:**

May cause long term adverse effects in the aquatic environment.

Mobility:

Material is highly volatile, will partition to air. Not expected to partition to sediment and wastewater solids.

Vapors are expected to degrade rapidly in air.

Section 13 - Disposal Considerations

Disposal: This material must be disposed of in accordance with local regulations.

Section 14 - Transport Information

DOT	IATA	IMDG
Not Regulated In Containers of 119 Gallons Capacity or Less	Shipping Name: Hydrocarbons, Liquid, N.O.S. Hazard Label: Flammable (Isodecane & isoundecane) UN #: 3295 Hazard Class: 3 Packing Group: III	Shipping Name: Hydrocarbons, Liquid, N.O.S. Hazard Label: Flammable (Isodecane & isoundecane) UN #: 3295 Hazard Class: 3 Packing Group: III

MSDS No. 915

Sonite Wax

Revision: 0011


Section 15 - Regulatory Information**United States EPA Regulations:**

SARA Toxic Chemical (40 CFR 372.65): None

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): None

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

States Right To Know, Substance List:California Proposition 65: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.**Canadian Regulations:**WHMIS Identification: CLASS D-2B: Material causing other toxic effects (TOXIC).**Labeling according to EEC Directive**

Risk Phrases	Symbol(s) Required for EU Label	Safety Phrases
<p>R53: May cause long term adverse effects in the aquatic environment</p> <p>R65: Harmful: may cause lung damage if swallowed.</p> <p>R66: Repeated exposure may cause skin dryness or cracking</p>	 Xn: Harmful	<p>S23: Do not breathe vapor.</p> <p>S24: Avoid contact with skin.</p> <p>S33: Take precautionary measures against static discharge.</p> <p>S43: In case of fire use chemical, foam or CO₂; water may be ineffective but should be used to keep containers cool.</p> <p>S62: If swallowed do not induce vomiting. Seek medical advice immediately and show this label.</p>

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Mann Release Technologies Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.



Material Safety Data Sheet

THI-VEX[®]

Date Of Preparation: November 5, 2014

MSDS No. 839

Revision: 0005

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: THI-VEX[®]

General Use: Silicone Elastomer

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042
Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel
Domestic 800-255-3924
International 813-248-0585

Section 2- Hazards Identification

Not hazardous according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Council directive 1999/45/EC and its subsequent amendments.

HMIS	
H	1
F	1
R	0

Section 3 - Composition / Information on Ingredients

No hazardous ingredients

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water; remove contaminated clothing and launder before reuse.

Ingestion: Do not induce vomiting unless instructed by a physician. Contact physician immediately

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: >356 °F (180 °C)

Flash Point Method: PMCC

LEL: Not Established

UEL: Not Established


Flammability Classification: Non-Flammable

Extinguishing Media: Dry Chemical, Carbon Dioxide, and Foam

Unusual Fire or Explosion Hazards: None

Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.



MSDS No. 839

THI-VEX®

Revision: 0005

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Dike and contain spill; absorb or scrape up excess into suitable container for disposal. Stop or reduce discharge if it can be done safely.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Viscous Liquid
Appearance : Pale-Yellow viscous liquid
Odor : Mild odor
Vapor Pressure: None (Polymeric Resin)
Vapor Density (Air=1): >1
Specific Gravity (H₂O=1, at 4 °C): 0.96

Water Solubility: Soluble
Boiling Point: None (Polymeric Resin)
% Volatile: Nil
Freezing/Melting Point: 19°F (-7°C)
Viscosity: 18 poise
Evaporation Rate: Not Applicable

Section 10 - Stability and Reactivity

Stability: Stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization can not occur.

Chemical Incompatibilities: Strong bases, and acids.

Hazardous Decomposition Products: Silica, carbon monoxide and carbon dioxide

MSDS No. 839

THI-VEX®

Revision: 0005

Section 11- Toxicological Information

Eye Effects: Irritation
Skin Effects: Irritation

Carcinogenicity: None Determined
Mutagenicity: None Determined
Teratogenicity: None Determined

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations**Disposal:** Must be disposed of in accordance with applicable Federal, state and local regulations.**Section 14 - Transport Information**

DOT	IATA	IMDG
Not Regulated	Not Regulated	Not Regulated

Section 15 - Regulatory Information**United States Regulations****EPA Regulations:**

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

SARA Toxic Chemical (40 CFR 372.65): None

These products do not contain chemicals that are subject to release reporting requirements under **section 313 of SARA Title III.**

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

California Proposition 65: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

CANADA RegulationsWHMIS Identification: **Not controlled**CDSL/NDL (Canadian Domestic Substance List/Non Domestic Substance List): **All are Listed****Labeling according to EEC Directive**

No special packaging or labeling requirements.

MSDS No. 839

THI-VEX®

Revision: 0005

Section 16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.