## **Material Safety Data Sheet**

## **U.S. Department of Labor**

May be used to comply with

OSHA's Hazard Communication Standard, 29 CFR 1910.1200

Occupational Safety and Health Administration (Non-Mandatory Form)

Standard must be consulted for specific requirements. Form Approved OMB No. 1218-0072 IDENTITY (As Used on Label and List) Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that. Water Soluble Transparent Extender Base (4532 & 4572) **Emergency Telephone Number** Section I Manufacturer's Name 704-838-1475 Speedball Art Products, LLC Telephone Number for Information Address (Number, Street, City, State, and ZIP Code) 2301 Speedball Road Statesville, NC 28677 USA 704-838-1475 Signature of Preparer (optional) Date Prepared: January 2, 2012

#### Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)): OSHA PEL ACGIH TLV Other Limits %(optional) Recommended

VOC: 106-134 grams per litre (.88-1.12 lbs. per gallon)

Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.

### **Section III - Physical/Chemical Characteristics**

Boiling Point	212°F-369°F	Specific Gravity ( $H_2O = 1$ )	1.11-1.57
Vapor Pressure (mm Hg.)	N/A	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	Semi-paste with slight odor

#### **Section IV - Fire and Explosion Hazard Data**

(Reproduce locally)

Flash Point (Method Used) <b>N/A</b>	Flammable Limits <b>N/A</b>	LEL N/A	UEL N/A
Extinguishing Media	I	П	, I
N/A Special Fire Fighting Procedures			
Wear self-contained breathing apparatus (pro	essure-demand MSHA/NIOSH approved	d or equivalent) an	d full protective

OSHA 174, Sept. 1985

Page 1 of 2 Item Numbers: 40321-1009

## Section V - Reactivity Data

**Screen Drawing Fluid** 

Page 2

Stability	Unstable	Stable 🗸	1	
Incompatibility (Materials to Avoid) N/A				
Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen				
Hazardous Polymerization	May Occur	Will Not Occur ✓	Conditions to Avoid N/A	

## Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A	
Health Hazards (Acute and C	Chronic)			
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A	
Signs and Symptoms of Exposure N/A				
Medical Conditions Generally Aggravated by Exposure None known				
Emergency and First Aid Procedures  Contact with eyes may cause slight irritation: Flush with water.				

# Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled  Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.
Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing  Keep from freezing-product may coagulate
Other Precautions N/A

# **Section VIII - Control Measures**

Respiratory Protection (Specify Type) None required with adequate ventilation & normal usage conditions.				
Ventilation	Local Exhaust N/A	Special N/A		
	Mechanical (General) N/A	Other N/A		
Protective Gloves Impervious Eye Protection Safety Glasses or goggles				
Other Protective Clothing or Equipment N/A				
Work/Hygienic Practices Use protective cream where excessive skin contact is likely.				

Item Numbers: 40321-1009 Page 2 of 2