# **Material Safety Data Sheet**

#### **U.S. Department of Labor**

May be used to comply with

OSHA's Hazard Communication Standard, 29 CFR 1910.1200

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Standard must be consulted for specific requirements.

IDENTITY (As Used on Label and List) Water Soluble Screen Printing Ink (4540-4549, 4580-4589, 4572)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.	
Section I Manufacturer's Name Speedball Art Products, LLC	Emergency Telephone Number <b>704-838-1475</b>	
Address (Number, Street, City, State, and ZIP Code) 2301 Speedball Road Statesville, NC 28677 USA	Telephone Number for Information 704-838-1475	
Date Prepared: January 2, 2013	Signature of Preparer (optional)	

## Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)): ACGIH TLV Other Limits %(optional) Recommended

VOC: 106-134 grams per litre (.88-1.12 lbs. per gallon)

Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.

### **Section III - Physical/Chemical Characteristics**

Boiling Point	212°F-369°F	Specific Gravity (H <sub>2</sub> O = 1)	1.11-1.57
Vapor Pressure (mm Hg.)	N/A	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	Semi-paste with slight odor

#### Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A	
Extinguishing Media N/A				
Special Fire Fighting Procedures  Wear self-contained breathing apparatus (pressure-demand MSHA/NIOSH approved or equivalent) and full protective gear.				
Unusual Fire and Explosion Hazards  Material can spatter above 212°F. Film can	burn.			

OSHA 174, Sept. 1985 (Reproduce locally)

# Section V - Reactivity Data

**Screen Drawing Fluid** 

Page 2

Stability	Unstable	Stable 🗸	Conditions to Avoid Onset of decomposition is 350°F		
Incompatibility (Materials to Avoid) N/A					
Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen					
Hazardous Polymerization	May Occur	Will Not Occur	Conditions to Avoid N/A		

# Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards (Acute and Chronic) N/A			
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure N/A			
Medical Conditions Generally Aggravated by Exposure None known			
Emergency and First Aid Procedures  Contact with eyes may cause slight irritation: Flush with water.			

# Section VII - Precautions for Safe Handling and Use $\,$

Steps to Be Taken in Case Material is Released or Spilled  Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.
Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing  Keep from freezing-product may coagulate
Other Precautions N/A

## **Section VIII - Control Measures**

Respiratory Protection (Specify Type) None required with adequate ventilation & normal usage conditions.				
Ventilation	Local Exhaust N/A	Special N/A		
	Mechanical (General) N/A	Other N/A		
Protective Gloves Impervious			Eye Protection Safety Glasses or goggles	
Other Protective Clothing or Equipment N/A				
Work/Hygienic Practices Use protective cream where excessive skin contact is likely.				

Item Numbers: 43205-1005, 43205-1007, 43205-1017, 43205-1825, 43205-2005, 43205-2007, 43205-3005, 43205-3007, 43205-3047, 43205-3047, 43205-3007, 43205-4007, 43205-4017, 43205-4517, 4320