Material Safety Data Sheet

U.S. Department of Labor

May be used to comply with

OSHA's Hazard Communication Standard, 29 CFR 1910.1200 Standard must be consulted for specific requirements. Occupational Safety and Health Administration (Non-Mandatory Form)

Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List) Water Soluble Transparent Extender Base (4532 & 4572)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
Section I Manufacturer's Name Speedball Art Products, LLC	Emergency Telephone Number 704-838-1475
Address (Number, Street, City, State, and ZIP Code) 2301 Speedball Road Statesville, NC 28677 USA	Telephone Number for Information 704-838-1475
Date Prepared: January 2, 2012	Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)): OSHA PEL ACGIH TLV Other Limits Recommended %(optional)

VOC: 106-134 grams per litre (.88-1.12 lbs. per gallon)

Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.

Section III - Physical/Chemical Characteristics

Boiling Point	212°F-369°F	Specific Gravity ($H_2O = 1$)	1.11-1.57
Vapor Pressure (mm Hg.)	N/A	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	Semi-paste with slight odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A			
Special Fire Fighting Procedures Wear self-contained breathing apparatus (pressu	re-demand MSHA/NIOSH approve	d or equivalent) an	d full protective
gear.			

(Reproduce locally) OSHA 174, Sept. 1985

Item Numbers: 43207-1007 Page 1 of 2

Section V - Reactivity Data

Screen Drawing Fluid

Page 2

Stability	Unstable	Stable 🗸	Conditions to Avoid Onset of decomposition is 350°F
Incompatibility (<i>Materi</i> N/A	als to Avoid)		
Hazardous Decompositi Oxides of carbon ar		ucts	
Hazardous Polymerization	May Occur	Will Not Occur ✓	Conditions to Avoid N/A

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards (Acute and C N/A	Chronic)		
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exp N/A	osure		
Medical Conditions General None known	ly Aggravated by Exposure		
Emergency and First Aid Pro Contact with eyes may	ocedures cause slight irritation: Flush	with water.	

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.
Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing Keep from freezing-product may coagulate
Other Precautions N/A

Section VIII - Control Measures

Ventilation	Local Exhaust N/A	Special N/A	
	Mechanical (General) N/A	Other N/A	
Protective Glove	s Impervious		Eye Protection Safety Glasses or goggles
Other Protective	Clothing or Equipment N/A		
Work/Hygienic F	Practices Use protective cream wh	ere excessive s	kin contact is likely.

Item Numbers: 43207-1007 Page 2 of 2