43232-1003 43234-1001

**Material Safety Data Sheet** 

Infosafe No: 3CM03

Issue Date: March 2007

ISSUED by COLORMAK

Product Name: Permaset Aqua Print Paste

Not classified as hazardous

Pl of 3

#### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY Chemical Product Aqueous polymer dispersion with propriety additives And Company Identification **Product Name** Permaset Agua Print Paste Product Code 0011 Product Use Textile printing on natural fibres & synthetic substrates. Company Name Colormaker Industries

44 Orchard Road, Brookvale Address

NSW 2100 Australia Telephone

Number/Fax

Tel: (02) 9939-7977 Fax: (02) 9939-6685

Product Type Aqueous printing base for textile applications Emergency Contact David Stuart

Emergency Contact 44 Orchard Rd., Brookvale NSW 2100 Australia

Address

24 hour Contact +61 438 317 811

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Aqueous polymer dispersion with specialty additives. Characterization Ingredients Proportion Haz Symbol Risk Phrase

Water and minor N/A ingredients Acrylic copolymer 10-30 %

7664-41-7 Ammonia 0.25-15 т R10, R23

#### 3. HAZARDS IDENTIFICATION

Harmful if swallowed.

### 4. FIRST AID MEASURES

Inhalation Not an inhalation risk.

Ingestion Immediately rinse mouth and then drink plenty of water. Seek

medical attention.

Skin

Instantly wash with soap and water and rinse thoroughly. Remove contaminated clothing and wash before re-use. If irritation occurs seek medical advice.

Eye

Immediately irrigate with copious quantity of water for at least  $15\ \mathrm{minutes}$ . Eyelids to be held open. In all cases of eye

contamination it is a sensible precaution to seek medical advice.

Advice to Doctor Treat symptomatically.

#### 5. FIRE FIGHTING MEASURES

Extinguishing Use extinguishing media suited to the primary source of the fire. Media Specific Hazards No known unusual fire or explosion hazards associated with the

product.

Hazardous Not flammable, however after evaporation of the aqueous component Combustion residual material may decompose evolving toxic fumes and gases.

## **Material Safety Data Sheet**

Issue Date: March 2007 ISSUED by COLORMAK Infosafe No: 3CM03

Product Name: Permaset Aqua Print Paste

Not classified as hazardous

P 2 of 3

Emergency Fire fighters to wear self contained breathing apparatus if risk

Action in Case of Fire

of exposure to products of combustion

#### 6. ACCIDENTAL RELEASE MEASURES

Spills/Disposal Slippery when spilt. Avoid accidents, clean up immediately.

Contain using sand and earth - prevent runoff into drains and waterways. Wear protective equipment to prevent skin and eye contamination. Contain - prevent contamination of drains and waterways. Use absorbent (soil, sand, sawdust, vermiculite). Collect and seal in properly labelled drums for disposal. Wash

area with excess water.

#### 7. HANDLING AND STORAGE

Handling Handle in accordance with good industrial hygiene and safety

practice.

Store in a cool, dry place (above 0°C and below 40°C) out of Storage

direct sunlight and away from sources of heat.

#### 8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Other exposure Information.

A Time Weighted Average(TWA) or a Short Term Exposure Limit (STEL) has not been established by the National Occupational Health and Safety Commission for this product or any of its major ingredients.

Eye Protection Safety glasses

Hand Protection PVC, neoprene or nitrile rubber gloves.

Body Protection Overalls or similar protective apparel.

Hygiene Measures Wash hands and face before smoking, eating, drinking or using the

toilet.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

White opaque liquid. Appearance Odour Mild, characteristic. Boiling Point Approx. 100°C (water) Solubility in Water Miscible.

Specific Gravity Approx. 1.04 (20°C)

(H2O=1)Approx. 9 (25°C) pH Value Approx 70,000 cP Viscosity Flash Point Not applicable Flammability Not flammable.

#### 10. STABILITY AND REACTIVITY

Stability Stable. Hazardous Will not occur.

Polymerization Hazardous

No decomposition if used correctly.

Decomposition

Products

P 3 of 3

Page 2 of 3 Item Numbers: 43234-1001

# **Material Safety Data Sheet**

ISSUED by COLORMAK Issue Date: March 2007 Infosafe No: 3CM03

Product Name: Permaset Aqua Print Paste

Not classified as hazardous

#### 11. TOXICOLOGICAL INFORMATION

Vapour or spray mist may irritate mucous membranes and respiratory Inhalation

tract

Ingestion

Ingestion may cause gastric upset, pain, diarrhea, lethargy.

Skin Eye

Prolonged and/or repeated skin contact may result in irritation. Eye contact may result in slight irritation.

#### 12. ECOLOGICAL INFORMATION

No data.

Envir.

Prevent (undiluted) product reaching ground water, water bodies or

Protection sewerage system.

#### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Comply with local, state and federal regulations.

#### 14. TRANSPORT INFORMATION

U.N. Number

None Allocated

Sub Risk

Non hazardous material

DG Class

None Allocated

UN Number (Sea Transport)

None Allocated

Hazchem Code

None Allocated

Packing Group

None Allocated

### 15. REGULATORY INFORMATION

Poisons Schedule Not Scheduled

AICS (Australia) All components listed.

#### 16. OTHER INFORMATION

Last Change

This MSDS revision to meet requirements of 'National Code of Practice for the Preparation of Material Safety Data Sheets 3rd Edition [NOHSC:2011(2005)]

Uses and Restrictions

This MSDS summarises, at the date of issue, our best knowledge of the health and safety information of the product, and in particular how to safely handle and use the product in the workplace. Since Colormaker Industries cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is available on request.

Technical Contact David Stuart

Point

Ph: +61 2 9939-7977 Cell +61 438 317 811 Fax: +61 2 9939 6685 ...End of MSDS...