

44907-1009

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard, 29 CFR 1910.1200
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB No. 1218-0072

IDENTITY <i>(As Used on Label and List)</i> Diazo Photo Emulsion (component of #4559, 4520, 4523, 4524, 4522 & 4526; 4579)		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.	
Section I Manufacturer's Name Speedball Art Products, LLC		Emergency Telephone Number 704-838-1475	
Address <i>(Number, Street, City, State, and ZIP Code)</i> 2301 Speedball Road Statesville, NC 28677 USA		Telephone Number for Information 704-838-1475	
Date Prepared: January 1, 2010		Signature of Preparer <i>(optional)</i>	

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)):	OSHA PEL	ACGIH TLV	Other Limits Recommended	% <i>(optional)</i>
Ethyl Alcohol (CAS #64-17-5)	N/A	1000ppm	N/A	4%

This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.

Section III - Physical/Chemical Characteristics

Boiling Point	212°F	Specific Gravity (H ₂ O = 1)	1.1
Vapor Pressure (mm Hg.)	N/A	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	Light Blue with faint odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A			
Special Fire Fighting Procedures Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.			
Unusual Fire and Explosion Hazards Material can spatter above 212°F. Film can burn.			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Diazo Photo Emulsion

Page 2

Stability	Unstable	Stable ✓	Conditions to Avoid Onset of decomposition is 350°F
-----------	----------	-------------	--

Incompatibility (Materials to Avoid)	N/A
--------------------------------------	-----

Hazardous Decomposition or Byproducts	
---------------------------------------	--

Hazardous Polymerization	May Occur	Will Not Occur ✓	Conditions to Avoid N/A
--------------------------	-----------	---------------------	----------------------------

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
--------------------	--------------------	--------------	-------------------

Health Hazards (Acute and Chronic)	N/A
------------------------------------	-----

Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
-------------------------	-------------	-------------------------	------------------------

Signs and Symptoms of Exposure	N/A
--------------------------------	-----

Medical Conditions Generally Aggravated by Exposure	N/A
---	-----

Emergency and First Aid Procedures	N/A
------------------------------------	-----

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled	Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.
---	---

Waste Disposal Method	Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
-----------------------	--

Precautions to Be taken in Handling and Storing	Keep from freezing-product may coagulate
---	--

Other Precautions	N/A
-------------------	-----

Section VIII - Control Measures

Respiratory Protection (Specify Type)	None required with adequate ventilation & normal usage conditions.
---------------------------------------	--

Ventilation	Local Exhaust Adequate	Special N/A
	Mechanical (General) N/A	Other N/A

Protective Gloves Impervious	Eye Protection Safety Glasses or goggles
------------------------------	--

Other Protective Clothing or Equipment	N/A
--	-----

Work/Hygienic Practices	Use protective cream where excessive skin contact is likely.
-------------------------	--

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard, 29 CFR 1910.1200
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List)

Diazo Sensitizer (component of #4559, 4520, 4523, 4524, 4522 & 4526; 4578)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I Manufacturer's Name
Speedball Art Products, LLC

Emergency Telephone Number
704-838-1475

Address (Number, Street, City, State, and ZIP Code)
2301 Speedball Road Statesville, NC 28677 USA

Telephone Number for Information
704-838-1475

Date Prepared: **January 1, 2010**

Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s)):	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
Polymethylene-p-Diazo Benzene Dye (CAS #71550-45-3)	N/A	N/A	N/A	N/A
Phosphoric Acid (CAS #7664-38-2)	1 mg/m3	1 mg/m3	N/A	15%

This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.

Section III - Physical/Chemical Characteristics

Boiling Point	200°F Decomposition	Specific Gravity (H ₂ O = 1)	1.4
Vapor Pressure (mm Hg.)	N/A	Melting Point	<32°F
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	Infinite	Appearance and Odor	Brown paste with no odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
N/A	N/A	N/A	N/A

Extinguishing Media
N/A

Special Fire Fighting Procedures

If material is within a fire area, CO₂, water, or dry powder can be used. Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards

Material slowly darkens with heat and may exude acidic fumes and nitrogen gas. Wash with water.

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Diazo Sensitizer Page 2

Stability	Unstable	Stable ✓	Conditions to Avoid High temperatures above 200°F
Incompatibility (<i>Materials to Avoid</i>) Caustic materials			
Hazardous Decomposition or Byproducts Nitrogen, water vapor & acid fumes			
Hazardous Polymerization	May Occur	Will Not Occur ✓	Conditions to Avoid High temperatures above 200°F

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? Yes, see below	Skin? Can be an irritant	Ingestion? Low order of acute oral toxicity
Health Hazards (<i>Acute and Chronic</i>) See above. Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation.			
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure May cause skin rash in sensitive individuals.			
Medical Conditions Generally Aggravated by Exposure Pre-existing skin, eye, and respiratory disorders.			
Emergency and First Aid Procedures Contact with eyes and skin may cause mild irritation: Flush with water. If irritation persists, see Doctor. Ingestion: dilute by giving water. See Doctor. Inhalation: move to fresh air.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Dissolve with warm water.
Waste Disposal Method Dispose of according to EPA requirements or in aqueous waste storage units for commercial chemical disposal. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing Store in a cool, dark place. Refrigerate for longer shelf-life. Avoid sun and excess heat.
Other Precautions N/A

Section VIII - Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with adequate ventilation & normal usage conditions.			
Ventilation	Local Exhaust N/A	Special N/A	
	Mechanical (<i>General</i>) N/A	Other N/A	
Protective Gloves Impervious	Eye Protection Safety Glasses or goggles		
Other Protective Clothing or Equipment N/A			
Work/Hygienic Practices Use protective cream where excessive skin contact is likely.			

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard, 29 CFR 1910.1200
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List)
Diazo Photo Emulsion Remover (4557)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I Manufacturer's Name
Speedball Art Products, LLC

Emergency Telephone Number
704-838-1475

Address (Number, Street, City, State, and ZIP Code)
2301 Speedball Road Statesville, NC 28677 USA

Telephone Number for Information
704-838-1475

Date Prepared: **January 1, 2010**

Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.

Section III - Physical/Chemical Characteristics

Boiling Point	212°F	Specific Gravity (H ₂ O = 1)	1.02
Vapor Pressure (mm Hg.)	N/A	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	Transparent liquid with slight detergent odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	N/A	Flammable Limits	N/A	LEL	N/A	UEL	N/A
---------------------------	------------	------------------	------------	-----	------------	-----	------------

Extinguishing Media
N/A

Special Fire Fighting Procedures
Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards
Material can spatter above 212°F

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Diazo Photo Emulsion Remover

Page 2

Stability	Unstable	Stable ✓	Conditions to Avoid N/A
-----------	----------	-------------	----------------------------

Incompatibility (*Materials to Avoid*)

Avoid contact with strong oxidizing agents

Hazardous Decomposition or Byproducts

None

Hazardous Polymerization	May Occur	Will Not Occur ✓	Conditions to Avoid N/A
--------------------------	-----------	---------------------	----------------------------

Section VI - Health Hazard Data

Route(s) of Entry: Multiple	Inhalation? See below	Skin? Can be an irritant	Ingestion? Low order of acute oral toxicity
--------------------------------	--------------------------	-----------------------------	--

Health Hazards (*Acute and Chronic*)

Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation. Eyes & Skin: Can be an irritant

Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
-------------------------	-------------	-------------------------	------------------------

Signs and Symptoms of Exposure
N/AMedical Conditions Generally Aggravated by Exposure
Pre-existing eye, skin, and respiratory disorders

Emergency and First Aid Procedures

Contact with eyes and skin may cause irritation: Flush with water. If irritation persists, see doctor. Ingestion: dilute by giving water. See doctor. Inhalation: move to fresh air.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal.

Waste Disposal Method

Observe all Federal, State and local laws concerning health and environment.

Precautions to Be taken in Handling and Storing

N/A

Other Precautions

N/A

Section VIII - Control Measures

Respiratory Protection (*Specify Type*) None required with adequate ventilation & normal usage conditions.

Ventilation	Local Exhaust N/A	Special N/A
	Mechanical (General) N/A	Other N/A

Protective Gloves Impervious

Eye Protection Safety Glasses or goggles

Other Protective Clothing or Equipment N/A

Work/Hygienic Practices Use protective cream where excessive skin contact is likely.

37900-1006
1007
1009**MATERIAL SAFETY DATA SHEET**

12/01/2010

MANUFACTURER OR DISTRIBUTOR: Speedball Art Products Company
2301 Speedball Rd
Statesville North Carolina 28677

INFORMATION TELEPHONE NUMBER: 1-800-898-7224
EMERGENCY TELEPHONE NUMBER: 1-800-898-7224

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: SPEED CLEAN PRODUCT NUMBER: 4533&4590
PRODUCT SIZES: 474 ML & 947 ML BRAND NAME: SPEED CLEAN
PRODUCT CLASS: DETERGENT CLEANERS

SECTION II - HAZARDOUS INGREDIENTS

Ingredient	CAS #	PEL/TLV (MG/M#)	Max % Weight	NTP	IARC
NO HAZARD LABEL REQUIRED UNDER CCCR		N/A	100.00000	N	N
SODIUM METASILICATE	6834-92-0	N/A	0.88200	N	N

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING POINT: N/A MELTING POINT: N/A
VAPOR PRESSURE: N/A
SPECIFIC VAPOR DENSITY (AIR=1): N/A SPECIFIC GRAVITY: N/A
SOLUBILITY IN WATER: N/A REACTIVITY IN WATER: NON-REACTIVE
APPEARANCE AND ODOR:

SECTION IV - FIRE AND EXPLOSION INFORMATION

FLASH POINT (METHOD): N/A AUTOIGNITION TEMPERATURE: N/A
EXPLOSION LIMITS IN AIR (% BY VOLUME): NOT EXPLOSIVE
EXTINGUISHING MEDIA: NO SPECIAL MEDIA REQUIRED
FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED
UNUSUAL FIRE & EXPLOSION HAZARDS: NOT COMBUSTIBLE

SECTION V - PHYSICAL HAZARDS/REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: NONE
STABILITY: STABLE CONDITIONS TO AVOID: NONE
INCOMPATIBILITY (MATERIALS TO AVOID): NONE
HAZARDOUS DECOMPOSITION PRODUCTS: NONE

SECTION VI - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: SEE SECTION II FOR COMPONENT PEL/TLVs
PRIMARY ROUTES OF ENTRY: INHALATION, INGESTION, EYE, SKIN

COMPANY: Speedball Art Products Co.
PRODUCT: 4533&4590
BRAND NAME: SPEED CLEAN

12/01/2010

EFFECTS AND SYMPTOMS OF ACUTE EXPOSURE: VAPOR HARMFUL.
MAY BE HARMFUL BY BREATHING DUSTS OR MISTS.
SEVERE EYE PAIN AND IMPAIRMENT OF VISION. CONTACT MAY RESULT IN BLISTERING OR ULCERS OF SKIN.
MAY BE HARMFUL IF SWALLOWED. CONTACT MAY RESULT IN

EFFECTS AND SYMPTOMS OF CHRONIC EXPOSURE: NONE EXPECTED

CARCINOGEN LISTING: NTP: NO IARC: NO OSHA: NO

SEE SECTION II FOR COMPONENTS AFFECTED

MEDICAL CONDITIONS USUALLY AGGRAVATED BY OVER EXPOSURE TO THIS PRODUCT: ASTHMA, KIDNEY DISEASE.
PREGNANCY.

FIRST AID MEASURES: If swallowed, get prompt medical attention.

SECTION VII - SPILL OR LEAK PROCEDURES

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING:
KEEP OUT OF REACH OF CHILDREN.

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: NO SPECIAL SPILL PROCEDURES REQUIRED.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION VIII - PROTECTIVE EQUIPMENT/CONTROL MEASURES

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: Use NIOSH-certified mask for dusts and a locally exhausting hood appropriate for the operation.

OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): NONE REQUIRED

WORK/HYGIENE PRACTICES: Avoid ingestion. Avoid breathing dusts or mists.

SECTION IX - ADDITIONAL INFORMATION AND WARNINGS

THIS INFORMATION SHEET IS FOR THE CONSUMER USE OF THIS PRODUCT ONLY.

SPEEDBALL CUST SERV Fax: 704-838-1472

Nov 13 2009 09:55am P001/002

Material Safety Data Sheet

U.S. Department of Labor

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200 Standard must be consulted for specific requirements.

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB No. 1218-0072

21104-XXXX

IDENTITY (As Used on Label and List) Super Black India Ink (3338, 3378, 3398)		<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>	
Section I Manufacturer's Name Speedball Art Products, LLC		Emergency Telephone Number 704-838-1475	
Address (Number, Street, City, State, and ZIP Code) 2226 Speedball Road Statesville, NC 28677 USA		Telephone Number for Information 704-838-1475	
Date Prepared: May 11, 2007		Signature of Preparer (optional)	

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)):	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
None				
Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.				

Section III - Physical/Chemical Characteristics

Boiling Point	212°F-374°F	Specific Gravity (H₂O = 1)	1.1
Vapor Pressure (mm Hg.)	17mmHg	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	Thick paste with slight odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A			
Special Fire Fighting Procedures Wear self-contained breathing apparatus (pressure-demand MSHA/NIOSH approved or equivalent) and full protective gear.			
Unusual Fire and Explosion Hazards Material can spatter above 212°F. Film can burn.			

(Reproduce locally)

OSHA 174, Sept. 1985

SPEEDBALL CUST SERV Fax: 704-838-1472

Nov 13 2009 09:55am P002/002

Section V - Reactivity Data

Super Black India Ink Page 2

Stability	Unstable	Stable ✓	Conditions to Avoid Onset of decomposition is 350°F
Incompatibility (Materials to Avoid) N/A			
Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen			
Hazardous Polymerization	May Occur	Will Not Occur ✓	Conditions to Avoid N/A

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards (Acute and Chronic) N/A			
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure N/A			
Medical Conditions Generally Aggravated by Exposure None known			
Emergency and First Aid Procedures Contact with eyes may cause slight irritation: Flush with water.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.
Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing Keep from freezing-product may coagulate
Other Precautions N/A

Section VIII - Control Measures

Respiratory Protection (Specify Type) None required with adequate ventilation & normal usage conditions.		
Ventilation	Local Exhaust N/A	Special N/A
	Mechanical (General) N/A	Other N/A
Protective Gloves Impervious	Eye Protection Safety Glasses or goggles	
Other Protective Clothing or Equipment N/A		
Work/Hygienic Practices Use protective cream where excessive skin contact is likely.		

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard, 29 CFR 1910.1200
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB No. 1218-0072

43215-XXXX

IDENTITY (As Used on Label and List) Blick Textile Screen Inks All colors (43215-various skus)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
	Emergency Telephone Number 1-800-723-2787
Address (Number, Street, City, State, and ZIP Code)	Telephone Number for Information 1-800-723-2787
Date Prepared: January 1, 2011	Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)):	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
VOC: 85-199 grams per litre (.71-1.66 lbs. per gallon)				
Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.				

Section III - Physical/Chemical Characteristics

Boiling Point	212°F-369°F	Specific Gravity (H ₂ O = 1)	1.11-1.57
Vapor Pressure (mm Hg.)	17mmHg	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	High viscosity; acrylic emulsion odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A			
Special Fire Fighting Procedures Wear self-contained breathing apparatus (pressure-demand MSHA/NIOSH approved or equivalent) and full protective gear.			
Unusual Fire and Explosion Hazards Material can spatter above 212°F. Film can burn.			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Fabric Screen Printing Ink Page 2

Stability:	Unstable	Stable <input checked="" type="checkbox"/>	Conditions to Avoid Onset of decomposition is 350°F
Incompatibility (Materials to Avoid) N/A			
Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen			
Hazardous Polymerization	May Occur	Will Not Occur <input checked="" type="checkbox"/>	Conditions to Avoid N/A

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards (Acute and Chronic) N/A			
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure N/A			
Medical Conditions Generally Aggravated by Exposure None known			
Emergency and First Aid Procedures Contact with eyes may cause slight irritation: Flush with water.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.
Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing Keep from freezing-product may coagulate
Other Precautions N/A

Section VIII - Control Measures

Respiratory Protection (Specify Type) None required with adequate ventilation & normal usage conditions.			
Ventilation	Local Exhaust N/A	Special N/A	
	Mechanical (General) N/A	Other N/A	
Protective Gloves Impervious	Eye Protection Safety Glasses or goggles		
Other Protective Clothing or Equipment N/A			
Work/Hygenic Practices Use protective cream where excessive skin contact is likely.			

Item Numbers: 43215-1005, 43215-1007, 43215-2005, 43215-2007, 43215-3005, 43215-3007, 43215-30A5, 43215-30A7, 43215-31A7, 43215-32B7, 43215-3717, 43215-4005, 43215-4507, 43215-4607, 43215-4505, 43215-4507, 43215-4567, 43215-5005, 43215-5007, 43215-5217, 43215-5517, 43215-5917, 43215-6505, 43215-6507, 43215-7005, 43215-7007, 43215-7277, 43215-8005, 43215-8007

MSDS for #21312 - PAINTERS PAINT MRKR

Section V — reactivity Data

Stability	Unstable		Conditions to Avoid	Onset of decomposition is 350°F.
	Stable	X		
Incompatibility (Materials to Avoid) N/A				

Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen.				
Hazardous Polymerization	May Occur		Conditions to Avoid	
	Will Not Occur	X		

Section VI — Health Hazard Data

Route(s) of Entry:	N/A	Inhalation?	Skin?	Ingestion?
Health Hazards (Acute and Chronic) N/A				

Carcinogenicity:	N/A	NTP?	IARC Monographs?	OSHA Regulated?
------------------	-----	------	------------------	-----------------

Signs and Symptoms of Exposure	N/A
--------------------------------	-----

Medical Conditions Generally Aggravated by Exposure	N/A
---	-----

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water. Induce vomiting if large amounts are ingested.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.

Waste Disposal Method Incinerate at a permitted facility according to current local, state and federal regulations.

Precautions to Be Taken in Handling and Storing Keep from freezing - product may coagulate.

Other Precautions N/A

Section VIII — Control Measures

Respiratory Protection (Specify Type) None required with adequate ventilation & normal operating conditions

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves Impervious Eye Protection Safety glasses

Other Protective Clothing or Equipment N/A

Work Hygiene Practices Use protective cream where excessive skin contact is likely.