

6-28-09

(For Printing Ink and Related Materials)

Date: June 24, 2004

45211-4041
.4046

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company
P.O. Box 7027
728 North Yale
Villa Park, IL 60181

EMERGENCY PHONE: 800-535-5053

PRODUCT CLASS: TRADE NAME: MANUFACTURERS CODE:
Oil Base Ink Graphic Etching Yellow Ochre 1028

SECTION II - HAZARDOUS INGREDIENTS

.0004 Lead Acetate

SECTION III - PHYSICAL DATA

Boiling Range: 200 degrees F Type of Odor:
Vapor Density: Heavier than air Evaporation Rate: Slower than ether
Liquid Density: Percent Volatile Wt: N/A
Appearance:

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

V-1930

Oil Base Ink

Graphic Etching Yellow Ochre

1028

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water
Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:
Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.