45213-1004

(For Printing Ink and Related Materials)

Date: March 29, 2010

SECTION I

MANUFACTURED BY:

Graphic Chemical & Ink Company

P.O. Box 7027 728 North Yale

Villa Park, IL 60181

EMERGENCY PHONE:

800-535-5053

79.8%

PRODUCT CLASS:

TRADE NAME: Universal Etch Ground - Hard MANUFACTURERS CODE: 12390,12396

Petroleum Hydrocarbon

Petroleum Distillates N.O.S

D.O.T. Shipping Name: D.O.T. Hazard Class:

3 (Flammable Liquid)

D.O.T. Identification:

UN1268

D.O.T. Label: Flammable

SECTION II - HAZARDOUS INGREDIENTS

CAS#64742-89-8
PEL - not established

SECTION III - PHYSICAL DATA

VM&P Naphtha

Boiling Range: Vapor Density: Liquid Density: Appearance: Greater than 240 F Type of Odor: Bland petroleum

Heavier than air Evaporation Rate: Slower than ether Lighter than water Percent Volatile Wt: N/A

Black Vapor Pressure: 45 MM @ 25 DG C

Approximately

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 54 degrees F

Lowest Flash Point: N/A

LEL: 0.9% Estimated

Extinguishing Media: Foam, CO2 Dry Chemical or water fog

Special Fire Fighting Procedure: Use air supplied rescue equipment for

enclosed areas; cool containers with water.

Unusual Fire & Explosion Hazards: Do not store or mix with strong oxidants.

Petroleum Hydrocarbon Universal Etch Ground - Hard

12390,12393,12396

SECTION V - HEALTH HAZARD DATA

300 PPM (ACGIH-8 hour time weighted average) Threshold Limit Value:

Effects of Overexposure: Breathing high vapor concentration may result in mild

depression, convulsions, loss of consciousness or lung damage. Contact may irritate eyes or skin.

Move patient to fresh air and call physician. Emergency First Aid:

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Heat sparks and open flame. When heating above 200 F Conditions to Avoid:

use impermeable protective gloves. Use window fan to

remove fumes. Contains natural asphaltum.

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:

Remove ignition sources. Avoid breathing concentrated vapor. Recover free liquid. Use absorbent material for small spills.

Waste disposal method:

Dispose of in accordance with local, state & federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Use in well ventilated room.

Protective Equipment (Respiratory, Eye, Etc.):

Breathing apparatus if needed. Protective gloves and safety goggles.

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling: Keep away from sparks, heat and open flame. Keep

containers closed.

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.