

Nov 17 03 03:19P Palmer Paint

10.575 0 2
12481 588-3078 P.1

60415-XXXX

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29CFR 1910.1200. Sections must be
consulted for specific requirements.

U. S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OSHA NO. 1216-0072


IDENTITY (AS USED ON IARC AND MSDS)
PRISM ACRYLICS 9917

NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT

SECTION I	
MANUFACTURER'S NAME PALMER PAINT PRODUCTS, INC	EMERGENCY TELEPHONE NUMBER 1-(248)-588-4500
ADDRESS (NUMBER, STREET, CITY, AND ZIP CODE) 1291 ROCHESTER RD. TROY, MI 48063	TELEPHONE NUMBER FOR INFORMATION 1-(248)-588-4500
	DATE PREPARED July 26 01
	SIGNATURE OF PREPARER (OPTIONAL)

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY IN FORMATION

Hazardous Components (Specific chemical identity, Common Name(s))	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	% (OPTIONAL)
VINYL ACETATE ACRYLIC COPOLYMER			TRADE SECRET	
WATER			CAS 7732-18-5	
CALCIUM CARBONATE			CAS 1317-65-3	
PROPYLENE GLYCOL			CAS 57-55-6	
MINERAL CLAY			CAS 1302-78-9	



"PRODUCTS BEARING THE AP APPROVED PRODUCT SEAL OF ACMI ARE CERTIFIED IN A PROGRAM OF TOXICOLOGICAL EVALUATION BY A MEDICAL EXPERT TO CONTAIN NO MATERIALS IN SUFFICIENT QUANTITIES TO BE TOXIC OR INJURIOUS TO HUMANS OR TO CAUSE ACUTE OR CHRONIC HEALTH PROBLEMS. THIS PROGRAM IS REVIEWED BY ACMI'S TOXICOLOGICAL ADVISORY BOARD. THESE PRODUCTS ARE CERTIFIED BY ACMI TO BE LABELED IN ACCORDANCE WITH THE CHRONIC HAZARD LABELING STANDARD, ASTM D-4236 AND FEDERAL LAW, P.L. 100-695. IN ADDITION, THERE IS NO PHYSICAL HAZARD AS DEFINED WITHIN 29 CFR PART 1910.2200(C)."

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT	200°F	SPECIFIC GRAVITY (H2O=1)	1.32
VAPOR PRESSURE (mm Hg)	N/A	MELTING POINT	N/A
VAPOR DENSITY (AIR=1)	LIGHTER	EVAPORATION RATE (BUTYL ACETATE=1)	SLOWER
SOLUBILITY IN WATER	MISCIBLE		
APPEARANCE AND ODOR	MINIMAL ODOR		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED) NON FLAMMABLE IN LIQUID STATE	FLAMMABLE LIMITS N/A	L.P.L. N/A	U.E.L. N/A
EXTINGUISHED MEDIA USE WATER SPRAY, CO2, FOAM ON DRY PRODUCT			
SPECIAL FIRE FIGHTING PROCEDURES CONTAINED BREATHING APPARATUS	PERSONS EXPOSED TO PRODUCTS OF COMBUSTION SHOULD WEAR SELF		
UNUSUAL FIRE AND EXPLOSION HAZARDS USE WATER SPRAY TO COOL CONTAINERS.	POSSIBLE PRESSURE BUILDUP FOR BULK PRODUCT CONTAINERS IF HEATED.		

(REPRODUCE LOCALLY) OSHA 174 SEPT 1985

Nov JUL 30, 2013 9:27AM PRYOGLOSS PRODUCTS INC

(248) 588-10,575 9 3 P-2

IDENTITY PRISM ACRYLICS

SECTION V - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID	N/A
	STABLE	YES		
INCOMPATIBILITY (MATERIALS TO AVOID)		NONE KNOWN		
HAZARDOUS DECOMPOSITION OR BYPRODUCTS		INCOMPLETE COMBUSTION MAY YIELD CARBON MONOXIDE		

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID	NONE KNOWN
	WILL NOT OCCUR	X		

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY	INHALATION?	N/A	SKIN?	N/A	INGESTION?	N/A
HEALTH HAZARDS (ACUTE AND CHRONIC) NON-TOXIC WATER BASED ACRYLIC COLORS NO ACUTE OR CHRONIC HAZARDS ASSOCIATED WITH PRODUCT AS DEFINED BY 29 CFR 1910.1200... AND IN COMPLIANCE TO THE ASTM D-4236 LABELING REGULATIONS						
CARCINOGENICITY	NTP?	NO	IARC MONOGRAPHY	NO	OSHA REGULATED?	NO
SIGNS AND SYMPTOMS OF EXPOSURE		NONE KNOWN				

MEDICAL CONDITIONS		NONE KNOWN				
GENERALLY AGGRAVATED BY EXPOSURE		NONE KNOWN				
EMERGENCY AND FIRST AID PROCEDURES		CONSULT A PHYSICIAN IF EYE OR SKIN IRRITATION SHOULD PERSIST AFTER IRRIGATING AREA WITH WATER.				

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
WIPE UP WITH CLOTH OR INERT ABSORBENT MATERIAL

WASTE DISPOSAL METHOD USE NORMALLY ACCEPTED PROCEDURES FOR WASTE DISPOSAL WHICH MEET ALL FEDERAL, STATE, AND LOCAL REQUIREMENTS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
DO NOT STORE IN AREAS WHERE TEMPERATURES EXCEED NORMAL ROOM TEMPERATURES.

OTHER PRECAUTIONS
NONE KNOWN

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE)		NONE NEEDED			
VENTILATION	LOCAL EXHAUST	N/A		SPECIAL	N/A
	MECHANICAL (GENERAL)	RECOMMENDED		OTHER	N/A
PROTECTIVE GLOVES	SKIN CONTACT MAY BE IRRITATING		EYE PROTECTION	EYE CONTACT MAY BE IRRITATING	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT		NONE NEEDED			

WORK HYGIENIC PRACTICES WASH HANDS WITH SOAP AND WATER BEFORE EATING.

NOV 06 10 38 AM 2013 9:28AM

P-PYGLOSS PRODUCTS INC

(248) 588-10575 9/4 P-3

CONFIDENTIAL
TRADE SECRET INFORMATION

2200 West Main Street Suite 600A

ACTION: FORMULA CHANGE
EXPEDITED

MFG# COMPANY NAME
0056 Palmer Paint Products, Inc.

PRODUCT # PRODUCT CATEGORY
17(01-99) ACRYLIC PAINT, ARTISTS

APPROVAL STATUS
1 AP (NO LABEL)

BRAND NAME
PALMER "PRISM ACRYLICS"

ALTERNATE BRAND NAME (1)
BEN FRANKLIN CRAFT PAINT

ALTERNATE BRAND NAME (2)
S&S GUILD CRAFT ACRYLIC PAINT

PRODUCT SIZES
1.5L, 200 ML

#COLORS APPROVAL
101 04/24/2003

SUBMITTED BY
Christopher Bailey

SUB DATE
04/23/2003


WGT FACTOR PROD TYPE
0.0 0 1 LIQUID

NO LABELING REQUIRED

LABELING CONFORMS TO ASTM D-4236. THIS PRODUCT IS NOT A TOXIC OR HAZARDOUS SUBSTANCE AS DEFINED BY CFR 1500.3 OF THE FEDERAL HAZARDOUS SUBSTANCES ACT. IT DOES NOT REQUIRE ACUTE OR CHRONIC HAZARD LABELING.

TOXICOLOGISTS ACTION: APPROVED FOR AP (NO LABEL) CERTIFICATION BY THE ART & CREATIVE MATERIALS INSTITUTE, INC.

THIS FORM MUST BE SENT TO ACMI WITHIN 60 DAYS FOR AUTHORIZATION TO USE THEIR SEAL.

 DATE 04/24/2003
Woodhall Stopford MD, MSPH
Toxicologist