# ROYAL 🔁 TALENS Safety Data Sheet

MSDS for #00417 - REMBRIAN OT ONLOS HA's Hazard Communication Standard 29CFR 1910,1200

## Page 1 of 3

Printing date 03/17/2016

Reviewed on 03/16/2016

## **1** Identification

#### • Trade name: <u>REMBRANDT OILCOLOUR, 118 TITANIUM WHITE (LINSEED OIL)</u>

• Article number: 010x.1182

• **Manufacturer/Supplier:** Royal Talens

P.O.Box 4, Apeldoorn, The Netherlands 7300AA

USA-distributor: Royal Talens North America, Inc. 30 Industrial Drive, Northhampton, MA 01060 tel. +1- 413-300-1899

Information department: info.na@talens.com
Emergency telephone number: For further health information call a poison control center.

2 Hazard(s) identification

• Hazard warning in accordance with US Labeling of Hazardous Art Materials Act / Federal Hazardous Substances Act:

Hazard statements Void

## 3 Composition/information on ingredients

· Dangerous components:

1314-13-2 zinc oxide

### 4 First-aid measures

- · After inhalation: Not applicable.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

# **5 Fire-fighting measures**

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.

## <u>6 Accidental release measures</u>

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

## 7 Handling and storage

· Precautions for safe handling: No special precautions are necessary if used correctly.

(Contd. on page 2)

1-10%

Item Numbers: 00417-1713, 00417-1714

Page 2 of 3

# ROYAL 🔁 TALENS Safety Data Sheet

#### MSDS for #00417 - REMBRIAND OF CALOR A's Hazard Communication Standard 29CFR 1910.1200

Printing date 03/17/2016

Reviewed on 03/16/2016

(Contd. of page 1)

# 8 Exposure controls/personal protection

• General protective and hygienic measures: Wash hands before breaks and at the end of work. • Eye protection: Not required.

Appearance:		
Form:	Fluid	
Color:	According to product specification	
Odor:	Characteristic	
Change in condition Melting point/Melting rang Boiling point/Boiling range		
Flash point:	> 100 °C (> 212 °F)	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Density at 20 °C (68 °F):	2.05 g/cm <sup>3</sup> (17.107 lbs/gal)	
· Solubility in / Miscibility with Water:	h Not miscible	

## **10 Stability and reactivity**

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- $\cdot$  Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

#### **11 Toxicological information**

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

1314-13-2 zinc oxide

 $Oral \ LD50 \ > 5000 \ mg/kg \ (rat)$ 

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# 12 Ecological information

· General notes:

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 3)

US

#### Page 3/3

# ROYAL 🔁 TALENS Safety Data Sheet

# MSDS for #00417 - REMBRIAND OF CALOR A's Hazard Communication Standard 29CFR 1910.1200

Printing date 03/17/2016

Reviewed on 03/16/2016

Thing dule 03/17/20	10	<i>Reviewed on 05/10/2010</i>
The product contai	ins materials that are harmful to the environn	(Contd. of page 2)
13 Disposal consid	lerations	
		isposal must be made according to official
4 Transport infor	rmation	
· Transport hazard	class(es)	
· DOT, ADR, IMDO	F, IATA	
	>	
· Class	9 Miscellaneous dangerous substanc	es and articles
· Label	9	
· Packing group		
· DOT, ADR, IMDO	G, IATA III IATA): Symbol (fish and tree)	
		ZARDOUS SUBSTANCES, LIOUID, N.O.S.

# **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture

(ZINC OXIDE), 9, III

- · TSCA (Toxic Substances Control Act):
- All ingredients are listed.

#### **16 Other information**

- All colors in this Rembrandt Oilcolours productline, except color 207, 208, 210, 211, 242, 271, 303, 306, 309, 314, 513, 515, 517, 534, 539, 586, 610 and 682, are qualified to bear the AP(approved product) Seal of the Art & Creative Materials Institute, Inc. This means that they are certified in a program of toxicological evaluation by medical expert to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. Certified by ACMI to be labeled in accordance with the chronic hazard labeling standard, ASTM D 4236 and Federal law, P.L. 100-695.

- This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Date of preparation / last revision 03/17/2016 / -

#### • Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
- OSHA: Occupational Safety & Health