Version 1.1 (18/10/2012) - Page 1/13 Company: Max Sauer SAS

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : I	IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING	
1.1. Product i	identifier	
Product nam	ne : VERNIS À RETOUCHER TURNER	
Product code	le : N135181,83, 84, 85	
1.2. Relevant	t identified uses of the substance or mixture and uses advised against	
1.3. Details of	of the supplier of the safety data sheet	
Registered c	company name : Max Sauer SAS.	
Address : 2	rue Lamarck.22000.Saint Brieuc.France.	
•	: 0033(0)296682000. Fax : 0033(0)296770065.	
mail@rapha	ael.fr	
1.4. Emergen	ncy telephone number : +33 (0)1 45 42 59 59.	
Association	/Organisation : INRS / ORFILA http://www.centres-antipoison.net.	
SECTION 2 : H	HAZARDS IDENTIFICATION	
2.1. Classifica	ation of the substance or mixture	
In complianc	ce with EC regulation No. 1272/2008 and its amendments.	
Flammable	liquid, Category 2 (Flam. Liq. 2, H225).	
Acute oral to	toxicity, Category 4 (Acute Tox. 4, H302).	
	on, Category 2 (Skin Irrit. 2, H315).	
-	on, Category 2 (Eye Irrit. 2, H319).	
	sation, Category 1 (Skin Sens. 1, H317).	
	get organ toxicity (single exposure), Category 3 (STOT SE 3, H336).	
-	hazard, Category 1 (Asp. Tox. 1, H304).	
	to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).	
	ce with directives 67/548/EEC, 1999/45/EC and their amendments.	
	nmable (F, R 11).	
	toxicity: harmful (Xn, R 22).	
	neous toxicity: harmful (Xn, R 21).	
	ation toxicity: harmful (Xn, R 20). re represents an aspiration risk due to its low viscosity: harmful (Xn, R 65).	
	on (Xi, R 38).	
	on (Xi, R 36).	
-	sation (Xi, R 43).	
	vironmental hazard, chronic toxicity: toxic (N, R 51/53).	
2.2. Label ele		
	ce with EC regulation No. 1272/2008 and its amendments.	
Hazard picto	6	
GHS07	GHS09 GHS08 GHS02	
011507	01100/ 011002	

Version	1.1 (18/10/2012) - Page 2/13
	Company: Max Sauer SAS

Signal Word :	
DANGER	
Product identifiers :	ESSENCE DE TÉRÉBENTHINE
EC 927-510-4 EC 931-254-9 601-037-00-0 603-001-00-X	HYDROCARBURES, C7, N-ALKANES, ISOALKANES HYDROCARBURES, C6, ISOALKANES N-HEXANE METHANOL
Additional labeling :	
	For professional use only.
Hazard statements :	
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eve irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statemen	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
Precautionary statement	tts - Prevention :
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting//equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do no eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statement	tts - Response :
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P330	Rinse mouth.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

Item Numbers: 01539-1005

- Made under licence of European Label System $\ensuremath{\mathbb{R}}$ MSDS software from InfoDyne - http://www.infodyne.fr -

P337 + P313 P362 P363 P370 + P378 P391 Precautionary statements - Storage : P403 + P233 P403 + P235 P405 Precautionary statements - Disposal : P501 If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. In case of fire: Use ... for extinction. Collect spillage. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container to ...

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard	symbols	:

Hazara Symbols .	
★	
Harmful	Dangerous for the environment Highly flammable
Contains :	
601-017-00-1	CYCLOHEXANE
601-037-00-0	N-HEXANE
603-001-00-X	METHANOL
603-117-00-0	PROPAN-2-OL ESSENCE DE TÉRÉBENTHINE
EC 927-510-4	HYDROCARBURES, C7, N-ALKANES, ISOALKANES
EC 927-510-4 EC 931-254-9	HYDROCARBURES, C6, ISOALKANES
Risk phrase :	
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
K 51/55	environment.
R 43	May cause sensitisation by skin contact.
R 36/38	Irritating to eyes and skin.
R 20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R 11	Highly flammable.
R 65	Harmful: may cause lung damage if swallowed.
	For professional use only.
Safety phrase :	
S 2	Keep out of the reach of children.
S 29	Do not empty into drains.
S 36/37	Wear suitable protective clothing and gloves.
S 46	If swallowed, seek medical advice immediately and show this container or label.
S 13	Keep away from food, drink and animal feedingstuffs.
	Utiliser et conserver à l'écart de toute flamme ou source d'ignition ou d'étincelles, source de chaleur ou appareil électrique en fonctionnement- Ne pas fumer
S 25	Avoid contact with eyes.
S 26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S 51	Use only in well-ventilated areas.
S 56	Dispose of this material and its container to hazardous or special waste collection point.
S 64	If swallowed, rinse mouth with water (only if the person is conscious).
S 9	Keep container in a well-ventilated place.
S 23	Ne pas respirer les gaz

Item Numbers: 01539-1005

Version 1.1 (18/10/2012) - Page 3/13 Company: Max Sauer SAS

Version 1.1 (18/10/2012) - Page 4/13 Company: Max Sauer SAS

S 23	Ne pas respirer les fumées.
S 23	Ne pas respirer les vapeurs.
S 23	Ne as respirer les aérosols.
S 24	Avoid contact with skin.
	Product submitted to restrictions on the marketing and use: see Regulation (EC) No 1907/2006.

2.3. Other hazards

No data available.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

No substances fulfil the criteria set forth in annexe II section A of the REACH regulation (EC) nº 1907/2006.

3.2. Mixtures

Composition :

Identification	Name	Classification	%
	ESSENCE DE TÉRÉBENTHINE	GHS07, GHS09, GHS08, Dgr	25 <= x % < 50
		Xn,N	
		H:302-304-312-315-317-319-332-411	
		R: 10-20/21/22-36/38-43-51/53-65	
EC: 927-510-4	HYDROCARBURES, C7, N-ALKANES,	GHS07, GHS09, GHS08, Dgr	$10 \le x \% \le 25$
REACH: 01-211947551533-33	ISOALKANES	Xn,N	
		H:304-315-336-411	
		R: 11-38-65-67-51/53	
EC: 931-254-9	HYDROCARBURES, C6, ISOALKANES	GHS07, GHS09, GHS08, Dgr	$10 \le x \% \le 25$
		Xn.N	
		H:304-315-336-411	
		R: 11-38-65-67-51/53	
INDEX: 603-117-00-0	PROPAN-2-OL	GHS02, GHS07, Dgr	$2.5 \le x \% \le 10$
CAS: 67-63-0		Xi,F	
EC: 200-661-7		H:225-319-336	
		R: 11-36-67	
INDEX: 601-037-00-0	N-HEXANE	GHS02, GHS08, GHS07, GHS09, Dgr	$1 \le x \% \le 2.5$
CAS: 110-54-3		Xn,N,F	
EC: 203-777-6		H:225-361f-304-373-315-336-411	
		R: 11-38-48/20-62.F3-65-67-51/53	
INDEX: 601-017-00-1	CYCLOHEXANE	GHS02, GHS08, GHS07, GHS09, Dgr	0 <= x % < 1
CAS: 110-82-7		Xn,N,F	
EC: 203-806-2		H:225-304-315-336-410	
		R: 11-38-65-67-50/53	
INDEX: 603-001-00-X	METHANOL	GHS02, GHS06, GHS08, Dgr	0 <= x % < 1
CAS: 67-56-1		T,F	
EC: 200-659-6		H:225-331-311-301-370	
		R: 11-23/24/25-39/23/24/25	

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Version 1.1 (18/10/2012) - Page 5/13 Company: Max Sauer SAS

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

Version 1.1 (18/10/2012) - Page 6/13 Company: Max Sauer SAS

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non fire-fighters

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For fire-fighters

Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Never inhale this mixture.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

- Made under licence of European Label System® MSDS software from InfoDyne - http://www.infodyne.fr -

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH) Version 1.1 (18/10/2012) - Page 7/13 Name: VERNIS À RETOUCHER TURNER - N135181,83, 84, 85. Company: Max Sauer SAS **Recommended equipment and procedures :** For personal protection, see section 8. Observe precautions stated on label and also industrial safety regulations. Avoid inhaling vapors. Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus. Provide vapor extraction at the emission source and also general ventilation of the premises. Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions. In all cases, recover emissions at source, Avoid skin and eye contact with this mixture. Packages which have been opened must be reclosed carefully and stored in an upright position. Prohibited equipment and procedures : No smoking, eating or drinking in areas where the mixture is used. Never open the packages under pressure. 7.2. Conditions for safe storage, including any incompatibilities No data available. Storage Keep out of reach of children. Keep the container tightly closed in a dry, well-ventilated place Keep away from food and drink, including those for animals. Keep away from all sources of ignition - do not smoke. Keep well away from all sources of ignition, heat and direct sunlight Avoid accumulation of electrostatic charges. The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area. Packaging Always keep in packaging made of an identical material to the original. 7.3. Specific end use(s) No data available. SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION 8.1. Control parameters **Occupational exposure limits :** - European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC) CAS VME-mg/m3 : VME-ppm : VLE-mg/m3 : VLE-ppm : Notes : 110-54-3 72 20 _ 700 200 110-82-7 _ Peau 67-56-1 260 200 - ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) : CAS Definition : TWA: STEL : Ceiling : Criteria : 67-63-0 200 ppm 400 ppm 110-54-3 50 ppm 110-82-7 100 ppm _ 67-56-1 200 ppm 250 ppm - Germany - AGW (BAuA - TRGS 900, 21/06/2010) : CAS VME : VME : Excess Notes 67-63-0 200 ml/m3 500 mg/m3 2(II) DFG, Y 110-54-3 50 ml/m3 180 mg/m3 8(II) DFG, Y 110-82-7 200 ml/m3 700 mg/m3 4(II) DFG

67-56-1

200 ml/m3

270 mg/m3

- Made under licence of European Label System® MSDS software from InfoDyne - http://www.infodyne.fr -

DFG, EU, H, Y

4(II)

Page 7 of 13

Version 1.1 (18/10/2012) - Page 8/13

me: VERNIS À RETOU(CHER TURNER	- N135181,8	3, 84, 85.			Company: Max Sauer SAS
- France (INRS - ED9	84 :2008) :					
CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
67-63-0	-	-	400	980	-	84
110-54-3	20	72	-	-	R3	59, 84
110-82-7	200	700	-	-	-	84
67-56-1	200	260	1000	1300	(12)	84
- UK / WEL (Workpla	ce exposure lim	its, EH40/2005, 2	2007) :			
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
67-63-0	400 ppm	500 ppm	-	-	-	
110-54-3	20 ppm	-	-	-	-	

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH) Name: VERNIS À RETOUCHER TURNER - N135181.83.84.85.

8.2. Exposure controls

110-82-7

67-56-1

Personal protection measures, such as personal protective equipment

100 ppm

200 ppm

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :

300 ppm

250 ppm



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Item Numbers: 01539-1005

- Made under licence of European Label System® MSDS software from InfoDyne - http://www.infodyne.fr -

Name: VERNIS À RETOUCHER TURNER - N135181,83, 84, 85	Company: Max Sauer
Dominatory protection	
- Respiratory protection	
Avoid breathing vapours.	
If the ventilation is insufficient, wear appropriate breathing appa When workers are confronted with concentrations that are above	
respiratory protection device.	e occupational exposure limits, they must wear a suitable, appro
Anti-gas and vapour filter(s) (Combined filters) in accordance w	vith standard EN14387 :
- A1 (Brown)	
SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES	
9.1. Information on basic physical and chemical properties	
General information :	
Physical state :	viscous liquid.
Important health, safety and environmental information	
pH :	Not stated.
	neutral.
Boiling point/boiling range :	> 35°C
Flash Point :	20.00 °C.
Vapour pressure :	Below 110 kPa (1.10 bar).
Density :	> 1
Water solubility :	Insoluble.
Viscosity:	v < 7 mm2/s (40°C)
Melting point/melting range :	not specified.
Self-ignition temperature :	not specified.
Decomposition point/decomposition range :	not specified.
9.2. Other information	1
No data available.	
SECTION 10 : STABILITY AND REACTIVITY	
10.1. Reactivity	
No data available.	
10.2. Chemical stability	
This mixture is stable under the recommended handling and stora	age conditions in section 7.
10.3. Possibility of hazardous reactions	
When exposed to high temperatures, the mixture can release h dioxide, fumes and nitrogen oxide.	hazardous decomposition products, such as carbon monoxide
10.4. Conditions to avoid	
Any apparatus likely to produce a flame or to have a metallic su not be allowed on the premises.	rface at high temperature (burners, electric arcs, furnaces etc.)
Avoid :	
 accumulation of electrostatic charges. 	
- heating	
- heat	
- flames and hot surfaces	
10.5. Incompatible materials	
10.6. Hazardous decomposition products	
The thermal decomposition may release/form :	
- carbon monoxide (CO)	
- carbon dioxide (CO2)	

Version 1.1 (18/10/2012) - Page 10/13 Company: Max Sauer SAS

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful if swallowed.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

May cause an allergic reaction by skin contact.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

No toxicological data available for the mixture.

Aspiration hazard :

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

No aquatic toxicity data available for the substances.

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

- No data available.
- 12.5. Results of PBT and vPvB assessment

No data available.

Version 1.1 (18/10/2012) - Page 11/13 Company: Max Sauer SAS

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2011 - IMDG 2010 - ICAO/IATA 2012).

14.1. UN number

1263

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)





14.4. Packing group

III

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	33	5 L	163 640HF 650	E1	3	D/E
		-						_		
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	3	-	III	5 L	F-E,S-E	163 223 955	E1			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	III	355	60 L	366	220 L	A3	E1	
								A72		

Item Numbers: 01539-1005

SAFETY DATA SHEET (REGULATION (EC) No 1907/2006 - REACH) Version 1.1 (18/10/2012) - Page 12/13 Name: VERNIS À RETOUCHER TURNER - N135181,83, 84, 85. Company: Max Sauer SAS Ш Y344 10 L E1 3 A3 A72 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code No data available. **SECTION 15 : REGULATORY INFORMATION** 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3). Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3). Usage restrictions apply to the product : See annex XVII of EC regulation No. 1907/2006. Banned from sale to the general public (EC Regulation No. 1907/2006) - For professional users only. For professional users only. - Particular provisions : No data available. - Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704): NFPA 704, Labelling: Health=2 Inflammability=3 Instability/Reactivity=1 Specific Risk=none 15.2. Chemical safety assessment No data available. **SECTION 16 : OTHER INFORMATION** Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Title for H, EUH and R indications mentioned in section 3 :

The for H, EUH and K indications mentioned in section 3 :					
H225	Highly flammable liquid and vapour.				
H301	Toxic if swallowed.				
H302	Harmful if swallowed.				
H304	May be fatal if swallowed and enters airways.				
H311	Toxic in contact with skin.				
H312	Harmful in contact with skin.				
H315	Causes skin irritation.				
H317	May cause an allergic skin reaction.				
H319	Causes serious eye irritation.				
H331	Toxic if inhaled.				
H332	Harmful if inhaled.				
H336	May cause drowsiness or dizziness.				
H361f	Suspected of damaging fertility.				
H370	Causes damage to organs .				
H373	May cause damage to organs through prolonged or repeated exposure .				

Version 1.1 (18/10/2012) - Page 13/13 Company: Max Sauer SAS

H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
R 10	Flammable.
R 11	Highly flammable.
R 20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R 23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R 36	Irritating to eyes.
R 36/38	Irritating to eyes and skin.
R 38	Irritating to skin.
R 39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R 43	May cause sensitisation by skin contact.
R 48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R 50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 62.F3	Possible risk of impaired fertility.
R 65	Harmful: may cause lung damage if swallowed.
R 67	Vapours may cause drowsiness and dizziness.
Abbreviations :	

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

GHS09 : Environment